

## TELS-1

**Article Number:** 111-30000

**Extended Length Tie, POM, Black, 50ft reel of strap and 30 heads/pkg**



Download spec sheet

### Base Data

**Local Order Number** TELS-1

**Type** EL-TY (TELS1)

**Color** Black (BK)

- Features and Benefits**
- Continuous strap and separate heads allow for any bundle diameter, eliminating waste.
  - Smooth strap prevents cable damage.
  - UV resistant materials contain an inhibitor which prolongs the life of the tie in outdoor environments.

**Product Description** HellermannTyton's Extended Length Tie is a high tensile strength strapping system consisting of a continuous strap and separate locking head making it suitable for any bundle diameter, eliminating waste. The smooth strap and specially designed heads with stainless steel pawls, provides a strong hold on cables and wires without damage during vibration or in extreme environments. Spacers are available for dual bundle applications.

**Short Description** Extended Length Tie, POM, Black, 50ft reel of strap and 30 heads/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 250.0 lbs

**Minimum Tensile Strength (Metric)** 1112.0 N

**Length L (Imperial)** 50.0 ft

**Length L (Metric)** 15200 mm

**Fixation Method** None

**Releasable Closure** No

**Tie Closure** steel pawl

**Variant** Extended Length

**Width W (Imperial)** 0.5 "

**Width W (Metric)** 12.7 mm

**Width W2 (Imperial)** 0.8 "

**Width W2 (Metric)** 20.3 mm

**Thickness T (Imperial)** 0.06 "

**Thickness T (Metric)** 1.50 mm

### Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 50 ft

**Package Quantity (Metric)** 1

**Carton Quantity** 25

**Weight (Metric)** 0.6 kg

## Material and Specifications

---

<b>Material</b>	Polyacetal (POM)
<b>Material Shortcut</b>	POM
<b>Material Cable Tie</b>	Polyacetal (POM)
<b>Flammability</b>	UL94 HB
<b>Material Head</b>	Polyacetal (POM)
<b>Material Spacer</b>	Polypropylene, UV-resistant (PPW)
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes