



Nu-Pax Limited

TECHNICAL DATA SHEET

291 Aluminium Foil Tape

DESCRIPTION

A 30 micron dead soft Aluminium foil tape coated with a long lasting ultra violet resistant acrylic adhesive on one side and lined with a release paper to protect the adhesive face. This product has been tested to BS476 part 6 & 7 standards and meets class 1 and class 0 fire regulations.

APPLICATIONS

A highly specified aluminium foil tape for use in any situation where long life, great adhesive strength or ultra violet resistance is required.

PROPERTIES

Thickness	:	0.12 mm
Shear (static)	:	> 200 hours
Tensile Strength (no liner)	:	45N/25mm
Elongation	:	5%
Peel Adhesion	:	14.5 N/25mm
20 mins	:	14.3 N/25mm
60 mins	:	19.4 N/25mm
24 hours	:	12.0 N
Looptack	:	> 4 hours
Humidity Shear Test	:	-20 to +50°C (The surface must be free from ice or moisture)
Application Temperature	:	-40 to +120°C (can withstand 140°C for a few minutes)
Temperature Range	:	< 1gm/M ² /24 hours @ 38°C and 90% RH
Moisture vapour permeability	:	12 mths in original packaging cool dry conditions (+12 to 25°C)
Shelf Life / storage	:	Surfaces to be bonded must be clean, dry and free from dust.
Application	:	

Date of Issue 26/03/2014

Statements, technical information and recommendations contained herein are based on production data with properties, quoted being typical but intended only as a guide. They do not constitute a product specification nor are they to be construed in any manor as warranties expressed or implied.

The user shall determine the suitability of the product for its intended use and the user assumes all risk and liability whatsoever in connection therewith.

Unit 7, Spectrum Park, Cheadle Heath, Cheshire, SK3 0SA
Tel; 0161 968 4970 Fax; 0161 429 6612