


Product Search Data Sheet

MA40S4S

RoHS REACH In Production Recommended

Appearance & Shape





- 1. Compact and light weight.
- 2. High sensitivity and sound pressure.

Applications

Automotive Usage	Infotainment
Other Usage	1. Obstacle detection in home2. Distance measurement

Packaging Information

Packaging	Specifications	Minimum Order Quantity
-	Box	540

Attention

Attention 1. This datasheet is downloaded from the website of Wurata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products n it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





MA40S4S

Specifications

Operating Temperature Range	-40℃ to 85℃	
Construction	Open type	
Center Frequency	40kHz	
S.P.L.	120dB typ. (0dB=0.02mPa)	
Directivity	80deg. (typ.)	
Capacitance	2550pF	
Torelance	±20%	
Max. Input Voltage	20Vp-p Continuous signal, Square wave	

Attention

Attention 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products n it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2. This datasheet has only lippical specifications because ihere is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet



MA40S4S

Product Data





Freq. Characteristics

Directivity in S.P.L.

Attention

Attention 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products n it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2. This datasheet has only lypical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

3 of 3