PRODUCT CODE

AU-11SA-4K22

ONE LINE DESCRIPTION

HDMI Audio De-embedder (up to 7.1) with built-in Repeater (4K, HDCP2.2, HDMI2.0)

EXTRA ONE LINE DESCRIPTION

Breakout the digital audio signal from a HDMI signal path (7.1)

The AU-11SA-4K22 advanced digital audio decoder is designed to de-embed 2-channel or multi-channel audio from the connected HDMI input and breakout this audio to provide 7.1 analogue audio connections, plus a 5.1 optical audio output and a HDMI bypass output. This device supports bypass of high resolution digital audio formats including LPCM 7.1CH, Dolby TrueHD, Dolby Digital Plus, Dolby Atmos and DTS-HD Master Audio, and supports audio sampling rates up to 192kHz.

In addition, the AU-11SA-4K22 supports 4K video resolutions, HDMI 2.0, and HDCP 2.2 ensuring stunning results and maximum compatibility for any AV system.

Features

- HDMI 2.0, HDCP 2.2 and DVI compliant
- HDMI audio decoder with built in repeater
- Supports HDTV resolutions up to 4Kx2K (3840x2160@24/25/30/ 50/60 YUV_444 & 4096x2160@24/25/30/50/60 YUV_444)
- The optical output supported audio: LPCM, Dolby Digital and DTS up to 5.1
- HDMI Bypass output supported audio: Dolby True HD, Dolby Digital Plus, and DTS-HD Master Audio
- Analogue stereo audio outputs support LPCM 2 channel, 5.1 and 7.1
- Audio sampling rate up to 192 kHz
- HDMI supports high-bit-rate (HBR) audio
- Features CEC bypass function

Specification

Inputs	1x HDMI [1x HDMI 2.0 Uncompressed AV and Data]
	1x HDMI [1x HDMI 2.0 Uncompressed AV and Data]
Outputs	1x Toslink [1x Optical Dolby Digital / DTS / 2 Channel LPCM]
	1x RCA [1x Front Left Mono]
	1x RCA [1x Front Right Mono]
	1x RCA [1x Front Centre Mono]
	1x RCA [1x Low Frequency Effect Mono]
	1x RCA [1x Right Rear Mono]
	1x RCA [1x Rear Left Mono]
	1x RCA [1x Rear Right Centre Mono]
	1x RCA [1x Rear Left Centre Mono]
PSU:	5V/2.6A
Dimensions	118mm [W] x 231mm [D] x 25mm [H]
Net Weight	620g
<u> </u>	24.2

Gross Weight 818g