

Flexible Wiring Cable

BS6195 Type 5A

pro-POWER



RoHS
Compliant

Application:

Coil end leads are used mainly as a flexible connection to coil windings of motors, generators, transformers, circuit breakers and actuators.

Standards / Conformances:

BS6195, Type 5A

Construction:

Conductor : Tinned annealed copper to EN60228 Class 5

Insulation : Silicone rubber Type EI2 to EN 50363
In Black and Red colour

Electrical Characteristics:

Rated Voltage : 300 / 500V

Physical Characteristics:

Maximum temperature : 180°C

Flame propagation : IEC 60332-1-2

Bend radius : Fixed : 4 × cable OD Flexing : 6 × cable OD

Part Number Table

Description	Conductor Size (mm ²)	Nom. Cable diameter mm	Max. Conductor DC Resistance at 20°C (Ω/km)	Colour	Reel Length	Part Number
Silicone Insulated Wire	0.2	2.35	92.4	Black	25m	BSR29 BLACK 25M
	0.2	2.35	92.4	Red		BSR29 RED 25M
	0.5	2.7	40.1	Black		BSR39 BLACK 25M
	0.5	2.7	40.1	Red		BSR39 RED 25M
	0.75	2.9	26.7	Black		BSR49 BLACK 25M
	0.75	2.9	26.7	Red		BSR49 RED 25M
	1.0	3.2	20.0			114

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER