
Spec Sheet

SMD Power Inductors (NS series)

NS10165T1R5NNA



Features

- Item Summary
 1.5uH±30%, 8.04A, 10.1x10.1x6.5mm
- Lifecycle Stage

Mass Production

Standard packaging quantity (minimum)
 Taping Embossed 2000pcs(500pcs*4reel)


Products characteristics table

Inductance	1.5 uH ± 30 %
Case Size (mm)	10.1x10.1
Rated Current (max)	8.04 A
Saturation Current (max)	13.6 A
Temperature Rise Current (max)	8.04 A
DC Resistance (typ)	6.2 mΩ
DC Resistance (max)	7.4 mΩ
LQ Measuring Frequency	100 kHz
Self Resonant Frequency (min)	85.4 MHz
Operating Temp. Range	-40 to +125 ℃ (Including-self-generated heat)
RoHS2 Compliance	Yes
REACH Compliance	Yes
Soldering	Reflow

External Dimensions

Dimension L	10.1 ±0.3 mm
Dimension W	10.1 ±0.3 mm
Dimension H	6.5 ±0.35 mm

Recommended Land Patterns




2.5

2.5

2016.01.25

SMD Power Inductors (NS series)

NS10165T1R5NNA



Dimension unit: mm unit: inch

Length: 10.1 +/- 0.3 (0.398 +/- 0.012)

Width: 10.1 +/- 0.3 (0.398 +/- 0.012)

Height: 6.5 +/- 0.35 (0.256 +/- 0.014)

Inductance: 1.5 uH (test freq at 0.1MHz)

DC Resistance: 0.0062 / 0.00744 ohm (typ / max)

Saturation Current: 13.60 A (max) Temp. rise Current: 8.04 A (max)

Saturation current typical: 30% reduction from initial L value.

Temp rise Current typical: Temperature will rise by 40 deg C

