


Zero Smog® TL

Taking you to the next level
in removing dangerous
gases and particles




- > Longer service life due to exceptionally large filter surface
- > Low noise levels
- > Automated filter change notification system
- > Easily operated




Features and Benefits

- > Extraction unit for up to 2 workplaces
- > Low noise levels
- > Portable, for placement under or next to the bench
- > Easy filter replacement
- > Audio-visual filter change alarm
- > Quick and simple installation with Easy-Click system
- > Variable speed setting
- > Active carbon foam filter for effective gas cleaning
- > Maintenance-free, brushless EC blower

Fine dust
pre-filter F7



Particle filter H13
and 10% active
carbon foam



Filter Set

- > H13 particle filter and gas filter (10% active carbon foam filter) and ten F7 pre-filters

Order No. **T0058762858**



Remote switch

- > Cable length 2m

Order No. **FT91000033**

Technical Data

Dimensions (L x W x H) in mm	335 x 330 x 445
Weight in kg	9
Voltage	230 V, 50 Hz / 120 V, 60 Hz
Noise level	< 50 db (A)
Electrical power in W	120
Max. blower vacuum in Pa	3,000
Max. blower extraction rate	190 m³/h
Pre-filter	F7 fine dust filter
Compact filter	Particle filter H13 + gas filter (10% carbon foam filter)
Particle filter MPPS	>99.95%
Order no. FT91013699	Zero Smog TL Fume Extraction Unit 230V F/G
Order no. ZEROSMOGTL	Zero Smog TL 120V B
Order no. FT91013599	Zero Smog TL230V AUS/CN
Order no. FT91013999	Zero Smog TL 230V IND
Order no. FT91014699	Zero Smog TL with a Gas Filter 230V F/G



Zero Smog® TL Kit 1 with Funnel Nozzle

- > Zero Smog® TL fume extraction unit
- > Stop valve with bench mounting brackets
- > Flexible, adjustable extraction arm, 1 m, ø 60 mm
- > Extraction hose, flexible, 3 m, ø 60 mm
- > ALFA funnel nozzle
- > Remote switch

Order No. 230 V

FT91015699

Order No. 120 V

ZEROSMOGTLKIT1



Zero Smog® TL Kit 2 with Sloped Nozzle

- > Zero Smog® TL fume extraction unit
- > 2x Flexible, adjustable extraction arm, 1,5 m, ø 60 mm
- > 2x Sloped nozzle, length 130 mm, ø 60 mm
- > Remote switch
- > 2x Fixing clamps for the extraction arm

Order No. 230 V

FT91016699



Zero Smog® TL Kit 2 with Funnel Nozzle

- > Zero Smog® TL fume extraction unit
- > 2x Flexible, adjustable extraction arm, 1,5 m, ø 60 mm
- > 2x ALFA funnel nozzle
- > Remote switch
- > 2x Fixing clamps for the extraction arm

Order No. 230 V

FT91017699