

Isolation - Step Down (230VAC to 115VAC) 172 Series Plug-In




Features

- Primary 230VAC, 50/60 Hz. Secondary 115VAC
- Circuit breaker in primary.
- Provides circuit isolation & steps down primary voltage.
- Hi-pot tested to 2 KV RMS.
- Electrostatic shield between primary & secondary.
- Input (primary) connected to a 5 foot long cord & European (Schuko) grounded plug - NOTE: old inventory only.
- Input - due to U.L changes in 2007 - NEW production with the European (Shuko) parts would no longer be U.L. listed. Therefore, we have replaced this input plug with a standard North American 3-wire, 250V plug (NEMA 6-15P).
- Output (secondary) connected to a 1 foot long cord & standard North American 3-wire grounded receptacle (NEMA 5-15R).
- North American Mark of Safety - C UL & UL listed (File #E211544).
- Indoor use only.
- **Remember** - These units do NOT convert line frequency

Accessories

- International Grounded Adaptor Plugs



Part No.	Capacity Leakage		Full Load Total		Surge / Noise	Capacitance				
	VA	Current	Efficiency	Harmonic Distortion		Between Windings at 1KHz	Overall Dimer			
					Suppression	A	B	C		
172A	100	40.48 μ A	88%	0.19%	-35 dB	40 pF	3.80	5.06	4.68	3
172B	200	41.97 μ A	91%	0.18%	-34.32 dB	20 pF	3.80	5.56	4.68	3
172D	500	68.22 μ A	96%	0.23%	-37.69 dB	28 pF	3.80	7.06	4.68	3
172E	750	79.58 μ A	94%	0.19%	-38.24 dB	20 pF	4.40	8.70	5.39	3
172F	1000	94.08 μ A	96%	0.18%	-32.74 dB	40 pF	5.28	7.75	6.38	4

Data subject to change without notice