



TapeCase Ltd.
1982 Lunt Ave, Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

Hook and Loop Tape

Product Description

Hook and Loop Tape fasteners consist of two woven strips, one of which is covered with tiny stiff hooks and the other with pliable loops. Pressed together they fasten; to open simply pull apart. Hook and Loop Tapes are coated on the backside with a rubber pressure sensitive adhesive. This allows the products to be used in typical hook and loop fastening applications while adhering to a variety of different surfaces.

Applications

Hook and Loop can provide a firm adhesive bond to a variety of surfaces including CARC Paint, glass, bare and painted metal, sealed wood, acrylic, polycarbonate, flexible and rigid vinyl, ABS, polystyrene and plasticized plastics.

Typical Physical Properties

Peel Strength at 180°	
Initial Tack	31.4 PIW
Complete Cure	41.5 PIW
Holding Power	124 hours
Softening Point	93°C

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.