

4mm Banana Plug to 4mm Banana Plug Lead




**RoHS
Compliant**



Characteristics

Electrical Safety	: According to EN / IEC 61010-031:2008 : 1000 V CAT II / 1000 V CAT III / 600 V CAT IV, reinforced insulation, 12 A (at +40 °C). These specifications come from the creepage distances, clearances, accessible parts, and solid insulation of the lead. And the considered specifications of the environment are : Pollution degree, 1 or 2 ; Relative humidity, 80 % maximum for temperatures up to 31°C decreasing linearly to 50 % relative humidity at +40°C Temperature range, +5°C to +40°C Indoor use ; and Altitude, 2000 m maximum. According to EN / IEC 60529 : IP2X (touchproof).
Operating Temperature	: -20°C to +80°C
Materials	: Conductors: Nickel-coated brass and red annealed copper. Wire jackets: Silicone. Insulators and lantern contact spring
Colour	: Red, Black, Blue, Green & Yellow
Overall Length	: 1.5 meter (150cm)



Part Number Table

Description	Colour	Part Number
Straight 4mm Banana Male Plug to Straight 4mm Banana Male Plug Lead	Red	76-016
	Black	76-1400
	Blue	76-1402
	Green	76-1404
	Yellow	76-1406

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell Limited 2016.

