

0 601 9E7 170 – GSB 18-2-LI Plus

Material number	0 601 9E7 170	0 601 9E7 102	0 601 9E7 103	0 601 9E7 173	0 601 9E7 174	0 601 9E7 175
EAN	3165140817783					
Baretool number	3601JE7100	3601JE7100	3601JE7100	3601JE7100	3601JE7100	3601JE7100
1 x battery GBA 18 V 4.0 Ah 1 600 Z00 038					✓	
1/2 L-BOXX inlay for accessories 1 600 A00 2WC	✓					
1/2 L-BOXX inlay for tool 1 600 A00 2WA	✓	✓				
2 x battery GBA 18 V 1.5 Ah 1 600 Z00 035				✓		
2 x battery GBA 18 V 2.0 Ah 1 600 Z00 036	✓		✓			✓
25-piece screwdriver bit set 2 607 017 037			✓			✓
AL 1820 quick charger 2 607 225 425						✓
Carrying case			✓	✓	✓	✓
Carton L-BOXX-ready		✓				
Charger AL 1820 CV 2 607 225 426	✓			✓	✓	
L-BOXX 136 1 600 A00 1RR	✓					
Quick Charger AL 1820 CV 2 607 225 424			✓			
Weight incl. battery	1,5 kg	1,5 kg	1,5 kg	1,5 kg	1,5 kg	1,5 kg



Technical data

Technical data

Torque, max. (hard/soft)	63 / 24 Nm
No-load speed (1st gear / 2nd gear)	0 – 500 / 0 – 1.900 rpm
Chuck capacity, min./max.	1,5 / 13 mm
Drill spindle thread	1/2"
Battery voltage	18 V
Battery capacity	2,0 Ah
Weight excl. battery	1.2 kg
Torque settings	20+1
Length	202 mm
Height	230 mm

Drilling diameter


Max. drilling diameter in wood	38 mm
Max. drilling diameter in steel	13 mm
Max. drilling diameter in masonry	13 mm

Screw diameter

Max. screw diameter	8 mm
---------------------	------

Noise/vibration information

Sound pressure level	89 dB(A)
Sound power level	100 dB(A)
Uncertainty K	3 dB
Noise level	The A-rated noise level of the power tool is typically as follows: Sound pressure level 89 dB(A); Sound power level 100 dB(A). Uncertainty K= 3 dB.



Sales information

Positioning

- Best price/performance ratio among professional cordless combis

User benefit

- Attractive solution for the entry-level segment of professional applications
- Keyless chuck with 13mm bit holder for common accessories
- New ergonomics: Better handling due to compact design

Other features

- Bosch Electronic Cell Protection (ECP): protects the battery against overload, overheating and deep discharge Electronic
- Motor Protection (EMP) protects the motor against overload and ensures a long lifetime
- Integrated LED light for illuminating the work area, even in dark places
- Mountable bit holder for easy transport and storage of bits on the tool
- Practical belt clip for conveniently hanging the tool on a belt or ladder Motor
- brake for precise work when driving rows of screws