

Stripping tool - WIREFOX 4 - 1212156

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Stripping tool, for cables and conductors (especially for rubber and silicone insulations) from 0.1 - 4 mm², self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm² stranded/1.5 mm² solid, replaceable stripping blade

Product Description


Insertable stripping blades: 1212152 WIREFOX 10/SB, 1212153 WIREFOX 16/SB, and 1212314 WIREFOX 6SC/SB, direct replacement: 1212151 WIREFOX 4/SB

Why buy this product

- Flexible, adjustable limit stop for the stripping length
- WIREFOX ... stripping pliers feature an automatic adjustment mechanism for a wide range of different types of insulation and conductor diameters
- Practical integrated wire cutter



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 454421
GTIN	4046356454421
Weight per Piece (excluding packing)	211.700 g
Custom tariff number	82032000
Country of origin	Sweden

Technical data

Dimensions

Length (b)	191 mm
Width (a)	20 mm
Height	90 mm
Cable diameter	0.3 mm ... 2.4 mm

General

Color	Black/green
-------	-------------

Stripping tool - WIREFOX 4 - 1212156

Classifications

eCl@ss

eCl@ss 4.0	21040301
eCl@ss 4.1	21040301
eCl@ss 5.0	21040301
eCl@ss 5.1	21040301
eCl@ss 6.0	21043706
eCl@ss 7.0	21043706
eCl@ss 8.0	21049090
eCl@ss 9.0	21049090

ETIM

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC000163
ETIM 5.0	EC000163
ETIM 6.0	EC000163

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	27111518

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		EAC-Zulassung
-----	--	---------------

Accessories

Accessories

Stripping tool - WIREFOX 4 - 1212156

Accessories

Knife

Spare knife - WIREFOX 4/SB - 1212151



Replacement blade for WIREFOX 4, for cables and conductors (especially for rubber and silicone insulations) of 0.1 - 4 mm²
