

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Control cabinet feed-through, M12, 8-pos., A-coded on RJ45 socket, socket input 90°, IP65/67

Why buy this product

✓ 1 Gbps

☑ IP65/67

✓ UL



Ethernet Ethernet

Key Commercial Data

Packing unit	1 STK
GTIN	4 055626 166773
GTIN	4055626166773
Weight per Piece (excluding packing)	26.900 g
Custom tariff number	85366990
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

Mechanical characteristics

Shielded	yes	
Insertion/withdrawal cycles	≥ 100 angled	
Cable exit		
Color	black	
Mounting type	Rear mounting	
Degree of protection	IP65/IP67	
Design	Angled	

Ambient conditions



Technical data

Ambient conditions

Ambient temperature (operation)	-25 °C 85 °C

Material data

Flammability rating according to UL 94	V0
Housing material	PA
Contact material	Copper alloy

Electrical characteristics

Nominal voltage U _N	60 V	
Nominal current I _N	0.5 A	
Transmission characteristics (category)	CAT5 (IEC 11801:2002)	
GRP transmission properties	Ethernet	
Transmission speed	1 Gbps	
Rated current	1.75 A	
Rated voltage (III/3)	50 V	

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance


China RoHS	Environmentally Friendly Use Period = 50	
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"	

Drawings


Expitosion diagvimo

Einpolocitled diangvinning

Dimensional drawing



Dimensional drawing



Panel cutout



Classifications

eCl@ss

eCl@ss 8.0	27141134
eCl@ss 9.0	27141134

ETIM

ETIM 5.0	EC001283
ETIM 6.0	EC001283

UNSPSC

_		
	UNSPSC 13.2	39121410

Approvals

Approvals

Approvals

UL Listed / cUL Listed / EAC / cULus Listed

Ex Approvals

Approval details

UL Listed	LISTED	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E335024-20140306		
Nominal current IN			0.5 A	
Nominal voltage UN			60 V	

cUL Listed	CUL	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E335024-		E335024-20140306
Nominal current IN			0.5 A	
Nominal voltage UN			60 V	

EAC	EAC	B.01742



Approvals

cULus Listed



Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com