

SOLDER FLUX



Liquid Solder Flux

Completely non-corrosive liquid solder flux consisting of a solution of special rosin in alcohol. Contains no traces of acids or chlorides and is completely safe to use on even the most delicate electronic equipment. Will work also with Lead Free solder.

Part No. 10-4202	2 fl. oz. Bottle
Part No. 10-4216	16 fl. oz. Bottle



Soldering Paste

A strong flux for soldering sheet metal parts, bus wires to steel chassis, tinning and cleaning of soldering iron tips, etc. Not recommended for electronic or printed circuit soldering.

Part No. 10-1207	2 fl. oz. Bottle
------------------	------------------



Solder Flux

A flux for all metals, as effective as acid or chloride types but non-corrosive. Solders even hard-to-solder metals such as aluminum, zinc-based alloys, steel, etc. Ideal for soldering bus and ground wires to aluminum and steel chassis, to hermetically seal lids to metal cases, for pot-tinning of copper and brass parts, etc. Not recommended for electronic wiring, including printed circuits.

Part No. 10-200	2 fl. oz. Bottle
-----------------	------------------



Water Removable Soldering Paste

Lubricates, cleans, fluxes and rinses away.

Part No. 10-202	2 fl. oz. Bottle
-----------------	------------------

SPECIALTY CHEMICALS



Flux Remover and Cleaner

Convenient, fast and easy to use. Removes all types of organic flux. Pinpoint applicator supplied. Non ODC 75% VOC.

Part No. 22-271 -B	16 oz. Aerosol
--------------------	----------------



High Voltage Putty

Silicone rubber compound with excellent insulating characteristics. It will never harden, will not shrink and has good adhesive properties. Provides a corona and arc suppressing coating in high voltage systems. Especially useful for coating sharp points, edges or corners. Also useful to form gaskets and seals where a putty-like, non-hardening property is desired. (Approx. 550 Volts/MIL Di-electric strength).

Part No. 10-8880	1-1/4 oz. (1" wide x 1/4" thick x approx. 18" in length)
Part No. 10-8882	1/2 lb. Roll