

24x12x8x / 24x12x6x / 12x + 48x24x48x

eatures SATA Super AllWrite

DH-24AESH/ iHAS324/ iHAS124

_

- ★ SATA interface, Half-Height internal DVD+R / DVD+RW / DVD-RW / DVD-RW / DVD-R9/ DVD-R9/ DVD-RAM/ DVD-ROM / CD-R/ CD-RW / CD-ROM combination drive
- ★ Support Double Layer DVD+/- R9 Recording Function
- * Fast access time and high data transfer rate, could be vertical mounted
- ★ Seamless Link ® Smart Monitoring & Adapting Recording Technology for Burning
- ★ Support Fixed Packet, Variable Packet, TAO, SAO, DAO, Random Access Write, Incremental, sequential recording, restricted overwrite, Layer Jump recording, Raw Mode Burning & Over-Burn
- ★ DVD read compliant: DVD single / dual layer (PTP, OTP), DVD-R(4.7G), DVD-R multi-borders, DVD-R9, DVD+R / DVD+R9 single/multi sessions, DVD-RW, DVD+RW and DVD-RAM discs
- ★ CD read compliant: CD-DA, CD-ROM, CD-ROM/XA, Photo-CD, Multi-session, Karaoke-CD, Video-CD, CD-I FMV, CD Extra, CD Plus, CD-R, and CD-RW
- ★ Support both 8cm and 12cm disc of CD and DVD family
- ★ Conform to Orange Book: Part 2 CD-R Volume 1, Part 2 CD-R Volume 2 Multi Speed, Part 3 CD-RW Volume 1 (1x, 2x, and 4x)once, Part 3 CD-RW Volume2: High Speed, Part 3 CD-RW Volume 3: Ultra Speed. Support Fixed packet, Variable packet, Disc-at-once, Session-at-once and Track-at-once
- ★ Supported transfer mode: PIO mode 4, DMA mode 2 and Ultra DMA mode 5
- ★ Serial ATA Revision 2.6, ATA-8, MMC-6, SFF-8090 V7, and IMAPI compliant
- ★ ACPI compliant for power saving

Specifications

O DVD Family :

Write

DVD+R 24X maximum by CAV
DVD-R 24X maximum by CAV
DVD+R9 8 maximum by CAV
DVD-R9 8 maximum by CAV
DVD-RAM 6X maximum by CLV

ReWrite

DVD+RW 8X maximum by Zone CLV DVD-RW 6X maximum by Zone CLV

Read DVDROM SL:16X maximum by CAV ; DL 12X maximum by CAV

Rand. Access Time SL 160 ms/ DL 180 ms

○ CD Family :

Write

CD-R 48X by CAV

ReWrite

24X maximum by Z-CLV in UltraSpeed disc

Read

CD-ROM 48X maximum by CAV

Rand. Access Time 140ms

CD-RW

○ Buffer Size : 0.75MB (MAX)

O PC Required : 1GHz or faster CPU recommended.

Windows 8 requires SSE2, PAE and NX-bit Support

1GB RAM and 16GB free disk space required under 32-bit OS (2GB RAM and 20GB space under 64-bit OS) for creating DVD Disc.

Available SATA port required.

© Compatibility: DOS 6.xx, Windows 8 / Windows 7 / XP / 2003 / Vista and Linux operating system

⊚ S/N Ration : >75dB

 \odot Environment :

 $\begin{tabular}{lll} Operating & 5\% to 50\%; Relative Humidity: 20% to 80% \\ Non-Operating & -40\% to 65\%; Relative Humidity: 5% to 95% \\ \hline © {\bf Dimension:} & 146(W) \times 41.3(H) \times 170(D) \ (+/- 0.5 \ mm) \\ \hline \end{tabular}$

⊚ Weight: <0.9 Kg