# **Detailed Specifications & Technical Data**



### ENGLISH MEASUREMENT VERSION

## E601001 Cord Sets - DataTuff® Cat 6 IP20 RJ45 Cord Set



For more Information please call

1-800-Belden1



#### **General Description:**

1 meter (3.3 ft.), unshielded with solid conductors (ref: Belden Bonded-Pair Cable 7940A). Cable Rating NEC: CMR. CEC: CMR FT4.

EU Directive 2002/95/EC (RoHS):	Yes			
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2006			
MII Order #39 (China RoHS):	EUP 50			
es (Overall)				
Notes: For additional information about this product, visit	our web site at http://www.belden.com			
le				
Description:	4 pair, 23 AWG bare copper, Polyolefin Insulation, Bonded pairs, Industrial Grade PVC, Oil Res, Sun Res, CMR, FT4.			
Part Number:	7940A			
Shielding:	Unshielded			
Electrical Performance:	Category 6			
Maximum Operating Voltage:	300 V RMS			
Applicable Standards:	ANSI/TIA-568-C.2, ISO/IEC 11801, EtherNet/IP(tm) Specification, UL 1666 Riser			
nnectors				
Description:	RJ45 plugs Suitable for use in IP20 unsealed applications			
Connector Type:	Cat 6			
Sealing:	Suitable for IP20			
Connector Interface:	IEC 60603-7			
Shielding:	Unshielded			
Electrical Performance:	Cat 6			
Maximum Operating Voltage:	300 V RMS			
Applicable Standards:	ANSI/TIA-568-C.2, ISO/IEC 11801, EtherNet/IP Specification			
sembly				
Part Number:	E601001			
Electrical Performance:	Category 6			
Maximum Operating Voltage:	300 V RMS			
Storage Temperature Range:	-40°C To +70°C			
Installation Temperature Range:	-10°C To +60°C			
Operating Temperature Range:	-10°C To +60°C			
Applicable Standards:	ANSI/TIA/EIA-568-C.2, ISO/IEC 11801, UL 1863 and CSA-22.2 No. 233			
Shielding:	Unshielded			
Length:	1 meter (3.3 ft.)			

#### Put Ups and Colors:

Putup

Item #

Notes Item Desc

## **Detailed Specifications & Technical Data**



#### ENGLISH MEASUREMENT VERSION

#### E601001 Cord Sets - DataTuff® Cat 6 IP20 RJ45 Cord Set

E601001 002S1	1 EA	0.251 LB	RED	CORDSET IP20 C6 UTP SO 1M RD
E601001 006S1	1 EA	0.251 LB	BLUE, LIGHT	CORDSET IP20 C6 UTP SO 1M BL
E601001 008S1	1 EA	0.251 LB	GRAY	CORDSET IP20 C6 UTP SO 1M GY
E601001 010S1	1 EA	0.251 LB	BLACK	CORDSET IP20 C6 UTP SO 1M BK

Revision Number: 1 Revision Date: 12-16-2013

© 2016 Belden, Inc All Rights Reserved.

All Rights Reserved. Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information and belief at the date of its publication. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided of the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.