

H07V-K (X07V-K)

(does not affect the separate, VDE approved H05V-K product)

DB 4520001EN

valid from: 16.10.2015

Application

H07V-K (X07V-K) are single-conductor cables with thermoplastic PVC-insulation for installation inside of closed conduits and cable ducting systems and on or under plaster as well as in similar closed systems. They are suitable for protected, stationary use in or on lighting installation or control units/ switchgear in conjunction with voltages up to 1000 V AC or 750 V DC to-ground

Under individual part numbers, different core insulation colours and package types are offered for diverse application types. More and more automatic harnessing machines are made use of by the manufacturing sector for the harnessing of such hook-up wires. Especially therefor, we offer parts with embossed cable marking instead of printing and which are delivered inside big one-way cardboard boxes with enhanced cable amount per box. Further standard package types are classic coils with standard order length as well as spools with winded, fix standard length of this wire.

Package types

Coils:	Seven-digit part without final, alphabetic character
Plastic spool (up to max. 2,5 mm ²):	Eight-digit part with final letter "S" on the eighth place
Small version of big one-way cardboard box:	Eight-digit part with final letter "K" on the eighth place
Big version of big one-way cardboard box:	Eight-digit part with final letter "E" on the eighth place

Design

acc. to EN 50525-2-31 (VDE 0285-525-2-31)

Conductor	fine wire strands of bare copper, acc. to IEC 60228 resp. EN 60228 (VDE 0295), Class 5
Core insulation	PVC compound type TI 1 acc. to EN 50363-3 (VDE 0207-363-3)

Electrical properties

Nominal voltage U_0/U	450 / 750 V
Test voltage	2500 V AC

Mechanical and thermal properties

Minimum bending radius	at intended use:	
	AD ≤ 8 mm:	4 x outer diameter
	8 mm < AD ≤ 12 mm:	5 x outer diameter
	12 mm < AD:	6 x outer diameter
	at cautious bending:	
	AD ≤ 8 mm:	2 x outer diameter
8 mm < AD ≤ 12 mm:	3 x outer diameter	
12 mm < AD:	4 x outer diameter	

Temperature range	Fixed installation (without vibration): -40 °C to +80 °C	
	Moved operation:	+5 °C to +70 °C
	Laying/ handling:	Min. +5 °C
	Short-circuit and ground leakage:	Max. +160 °C
	Ambient temperature at storage:	Max. +40 °C
	Max. conductor temperature:	+70 °C

Flammability	acc. to IEC 60332-1-2 resp. EN 60332-1-2 (VDE 0482-332-1-2)
--------------	---

Tests	acc. to EN 60811-100 (VDE 0473-811-100); EN 50395 (VDE 0481-395); EN 50396 (VDE 0473-396);
-------	--

The cable is characterized with the <HAR> HAR-sign or HAR-identification thread.

EU-Directives	These cables are conform to the EU-Directives 2014/35/EU (Low Voltage Directive), and 2011/65/EU (RoHS, Restriction of the use of certain hazardous substances).
---------------	--

Originator:	ERBO1 / PCM	document:	DB4520001EN	page 1 of 1
approved:	HAPF / PDC			