# **DESCO INDUSTRIES INC. Technical Bulletin TB-7046**

# Application Instructions Reztore™ ESD Hand Lotion and Reztore™ Clean Hand Lotion







Figure 1. Reztore™ ESD Hand Lotion.

# **Description**

Desco Industries, Inc. Reztore™ ESD Hand Lotion and Reztore™ Clean Hand Lotion are specially formulated for use in the electronic manufacturing environment. Per ESD Handbook TR20.20 paragraph 5.3.2.4.3 Test Procedure, "If the [wrist strap test] resistance is still too high, dry skin might be the problem. Dry skin conditions can be resolved by applying moisturizing lotion on the wrist and repeating the resistance test again. The moisturizing lotion should be one that is compatible with process requirements." The moisturizing hand lotion can be used to enhance the effectiveness of ESD control wrist straps, particularly for individuals with dry skin. It will absorb immediately into the skin without interfering with grip or dexterity. The lotion is free of chemicals that may adversely affect solderability or cause corrosion of electronic components. Reztore™ Hand Lotion is available in 8 oz. (235 ml) plastic bottles (sold in cartons of twelve bottles), 32 oz. (1 litre) bottles with pumps, or in one 1 gallon (3.8 litre) bottles with pumps.

Reztore™ Hand Lotion can also be used with ESD footwear. Per ESD Handbook TR20.20 section 5.3.3.5 Common Testing Problems "Occasionally, footwear may indicate a high resistance. Outside of the shoe material itself being a contributor to high resistance, the wearer's skin (if dry), heavy or insulative socks, or the absence of a sweat layer due to differences in temperature between the inner surfaces of the shoes and the wearer's feet."

# **General Guidelines**

Reztore™ Hand Lotion can be applied to hands and wrists to increase the conductivity of the skin and reduce skin dryness. It is not recommended for application to the face. The lotion is chemically and biologically stable and is free of soaps, glycerin, lanolin, free-salts, silicone and mineral oil. Avoid contact with eyes. If eye contact occurs wash with water.

## **Directions**

Apply a small amount of Reztore™ Hand Lotion onto the palm of the hand. Using your hands, rub the lotion into skin areas which are either dry or where increased conductivity is desired, especially on the wrists where the wrist strap will be in direct contact. Gently rub the lotion into the skin until it is absorbed. Remove the excess lotion with a towel.

# **Specifications**

Viscosity: 6000 Brookfield 20 Speed Spindle #4

Color:WhiteOdor:PleasantpH: $7.5 \pm .5$ 

Contaminants: No soap, lanolin, free-salts, silicones,

or mineral oil

**% Solids:**  $7.5 \pm 2\%$ 

Package: 8 oz. (235 ml) plastic squeeze bottles, 32

oz. (1 litre) bottles with pumps, or 1 gallon

(3.8 litre) bottles with pumps

**Freeze:** Passes three freeze-thaw cycles

# Features - Benefits

- Moisturizing formula improves wrist strap contact with skin and relieves chapping and insulating dry skin
- Free of contaminants so that nothing is transferred to the work
- Non-acidic to prevent corrosion of electronic components
- Contains aloe vera, moisturizers, and vitamins to promote healing and help achieve healthier hands and mails
- No lanolin, silicone, mineral oil, or insulators that will contaminate electronic components

**NOTE:** Reztore<sup>™</sup> Hand Lotion does not have a set life span. The chemicals are not known to degrade over time when stored at the proper temperature conditions as stated in the Material Safety Data Sheet. We also recommend that this product be stored in its original container and be sealed when not in use.

DESCO INDUSTRIES INC. • 3651 Walnut Avenue, Chino, CA 91710 • (909) 627-8178 • Fax (909) 627-7449 • Web Site: Descolndustries.com

# **Limited Warranty**

Desco Industries, Inc. expressly warrants that for a period of one (1) year from the date of purchase, our Reztore™ ESD Hand Lotion and Reztore™ Clean Hand Lotion will be free of defects in material. Within the warranty period, the material will be replaced at our option, free of charge. Call our Customer Service Department at 781-821-8370 or 00 44 (0) 1892-665313 in Europe for a Return Material Authorization (RMA) and proper shipping instructions and address. You should include a copy of your original packing slip, invoice, or other proof of purchase date. Any material under warranty should be shipped prepaid to the Desco Industries, Inc. factory. Warranty replacements will take approximately two weeks.

## **Warranty Exclusions**

THE FOREGOING EXPRESS WARRANTY IS MADE IN LIEU OF ALL OTHER PRODUCT WARRANTIES, EXPRESSED AND IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE WHICH ARE SPECIFICALLY DISCLAIMED. The express warranty will not apply to defects or damage due to accidents, neglect, misuse, alterations, operator error, or failure to properly maintain, clean, or repair products.

# **Limit of Liability**

In no event will Desco Industries, Inc. or any seller be responsible or liable for any injury, loss, or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and users assume all risk and liability whatsoever in connection therewith.

DESCO INDUSTRIES INC. • 3651 Walnut Avenue, Chino, CA 91710 • (909) 627-8178 • Fax (909) 627-7449 • Web Site: Descolndustries.com

**Material Safety Data Sheet** 

May be used to comply with ANSI Z400.1-2004, 29 CFR 1910.1200, European 2001/58/EC, REACH 1907/2006/ EC, and GHS. Standard must be consulted for specific

requirements.

NFPA Designation 704

4 = Extreme 1 = Slight 3 = High0 = Insignificant

2 = Moderate

Degree of Hazard

Special Hazard

Health

(Blue)

0 Reactivity (Yellow)

Flammability

(Red)

0

0

0

HMIS RATING: Health 1, Flammability 0, Physical Hazard 0, Personal Protection B

## SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name/Identity: Reztore™ ESD Hand Lotion and Reztore™ Clean Hand Lotion

Chemical Name: Reztore™ ESD Hand Lotion

Manufacturer: Desco Industries, Inc. Address: One Colgate Way Canton, MA 02021

781-821-8370 Telephone: **Emergency Number:** 781-821-8370 Date Prepared: 2010-02-08

## **SECTION 2 — HAZARDS IDENTIFICATION**

Routes of Entry

Eyes: May cause irritation, tearing, or blurred vision.

May cause slight irritation of the skin. Skin: Ingestion: May cause nausea and vomiting.

Inhalation: None known.

### SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients: CAS No. Weight (%) 7732-18-5 60-100% Water Propylene Glycol 57-55-6 1-5% Stearic Acid 1-5% 57-11-4 Cetyl Alcohol 36653-82-4 1-5%

\*These items are listed and subjected to the reporting requirements of the SARA Title III Section 313 Inventory of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR372.

# **SECTION 4 — FIRST AID MEASURES**

**Emergency and First Aid Procedures:** 

Eye Contact: Flush with water for at least 15 minutes. Contact a physician if irritation persists. Skin Contact: Wash with soap and water. Wash clothing before reuse. Contact a physician if

irritation persists.

Ingestion: Drink several glasses of water. Induce vomiting. Contact a physician. Inhalation: Move subject to fresh air. Contact a physician if irritation persists.

# **SECTION 5 — FIREFIGHTING MEASURES**

Proper Extinguishing Media: N/A Unsuitable Extinguishing Methods: N/A

Protective Equipment & Precautions: Wearing of appropriate protective equipment and clothing

Flash Point (Method Used): N/A Flammable Limits: N/A

Special Fire Fighting Procedures: None required. Unusual Fire and Explosion Hazards: None known.

# SECTION 6 — ACCIDENTAL RELEASE MEASURES

Personal Precautions: None needed. **Environmental Precautions:** None known.

Waste Disposal Method: Mop with soap and water. Flush with copious amounts of water.

DESCO INDUSTRIES INC. • 3651 Walnut Avenue, Chino, CA 91710 • (909) 627-8178 • Fax (909) 627-7449 • Web Site: DescoIndustries.com

#### **SECTION 7 — HANDLING AND STORAGE**

Handling: No special precautions need be taken.

Storage: Store above 40°F to prevent freezing. Warm to melt. The maximum recommended

storage temperature is 120°F. Keep container tightly closed.

#### SECTION 8 — EXPOSURE CONTROL / PERSONAL PROTECTION

Control Parameters:

Measures for Technical Control:

Respiratory Protection (Specify Type):

Hand Protection:

Eye Protection:

Chemical splash goggles (ANSI Z-87.1)

None

Other Protective Clothing or Equipment: Eyewash station

Work/Hygienic Practices: Wash hands before eating, smoking or using washroom facilities

#### **SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES**

Viscous liquid Form: Colour: White lotion Odor: Peach or none **Boiling Point:** >200°F (94°C) Melting Point: >150°F Specific Gravity (H2O = 1): 1.01 Solubility in Water: Complete pH: 7-8

Flash Point: Noncombustible

Flammability Limits: N/A
Vapor Pressure (mm Hg): N/A
Vapor Density (air=1): N/A
Density at 20°C: N/A

Flammability: Classification according to EC-regulations "non-flammable"

Ignition Temperature: N/A Evaporation Rate: N/A

# **SECTION 10 — STABILITY AND REACTIVITY**

Hazardous Decomposition/Byproducts: None Incompatibility (Materials to Avoid): None

Stability/Reactivity: Stable product at normal conditions.

Conditions to Avoid: Temperatures above 49°C/120°F Below: 1°C/34°F

# **SECTION 11 — TOXICOLOGICAL INFORMATION**

# Propylene Glycol (57-55-6)

Acute Toxicity Lethal Doses LD50 Oral Rat 02020KMGG BWT LD50 Skin Rabbit 82000KMGGBWT

#### Stearic Acid (57-11-4)

Acute toxicity

LD50 Oral - rat - > 2,000 mg/kg LD50 Oral - rat - > 2,000 mg/kg LD50 Dermal - rabbit - > 5,000 mg/kg LD50 Dermal - rabbit - > 5,000 mg/kg

# Cetyl Alcohol (36653-82-4)

Acute toxicity

LD50 Oral - rat - 5,000 mg/kg

Remarks: Cardiac:Other changes. Lungs, Thorax, or Respiration:Other changes.

LD50 Dermal - rabbit - > 2,600 mg/kg

DESCO INDUSTRIES INC. • 3651 Walnut Avenue, Chino, CA 91710 • (909) 627-8178 • Fax (909) 627-7449 • Web Site: DescoIndustries.com

#### **SECTION 12 — ECOLOGICAL INFORMATION**

No environmental hazards have been reported or known.

Mobility: The product is aqueous and will be separated in aqueous conditions

Degradability: N/A
Bioaccumulation: Not likely
Ecotoxicity: None known

Reference to BimSchV: N/A

Hazard Classification: None hazardous

# **SECTION 13 — DISPOSAL CONSIDERATIONS**

Product: Ensure the disposal is in accordance with local authorities.

Hazardous Waste Number: Nonregulated

#### **SECTION 14 — TRANSPORT INFORMATION**

This product is not classified for transport under ADR/IMDG regulations

#### **SECTION 15 — REGULATORY**

**INFORMATION** 

Physical/Chemical Indication: Non-flammable

Risk-Phrase: (R22): Harmful if swallowed,

(R36): Irritating to the eyes.

Safety-Phrase: (S2): Keep away from children, (S7): Keep containers well closed,

(S7). Reep containers well closel (S25): Avoid contact with eyes,

(S42): If swallowed, do not induce vomiting; seek medical advice immediately and

show this container or label.

EU Classification: This product does not have to be classified according to the EU Regulations.

(67/548/EEC-88/379/EEC)

TSCA: All ingredients of this product are listed or are excluded from the listing on the U.S.

Toxic Substance Control Act (TSCA) Chemical Substance inventory.

REACH: This product does not require REACH registration.

# **SECTION 16 — OTHER INFORMATION**

HMIS RATING: Health 1, Flammability 0, Physical Hazard 0, Personal Protection B

NFPA RATING: Special Hazard 0, Health 0, Flammability 0, Reactivity 0

#### Disclaimer

The information given in this publication has been worked up to the best of the knowledge of Desco Industries Inc, as well as taking into consideration the applicable laws and regulations. We cannot anticipate all conditions under which this information and our products or the products of the manufacturers in combination with our products may be used. We accept no responsibility for the results obtained by the application information or the safety and suitability of our product or product combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product or product combination for their own purposes. Unless otherwise agreed in writing, we sell the products without warranty, and buyers end users assume responsibility and liability for loss or damage arising from the handling and use of our products, whether used alone or in combination with other products.

N/A = Not Applicable; NE = None Established

DESCO INDUSTRIES INC. • 3651 Walnut Avenue, Chino, CA 91710 • (909) 627-8178 • Fax (909) 627-7449 • Web Site: DescoIndustries.com