WIRELESS SURVEILLANCE SYSTEM

USER'S MANUAL





PLEASE READ THIS MANUAL CAREFULLY BEFORE OPERATING EQUIPMENT. RETAIN IT FOR FUTURE REFERENCE.

CONTENTS

1	CAL	JTION			1	
	WAI	RNING			1	
2	PRODUCTS OVERVIEW					
	2.1	LCD DVR			2-4	
	2.2	DVR			. 4-5	
	2.3	Camera			5-6	
3	SPE		IS			
	3.1	LCD DVR			6-7	
	3.2	DVR			7-8	
	3.3	Camera			8-9	
4	INS	TALLATION				
	4.1	nstall the LC	D DVR		9	
	4.2	nstall the D√	/R		10	
	4.3	nstall the Ca	imera		10-11	
5	MEN	NU OPERAT	ION			
	5.1	Camera setti	ng		11-13	
	5.2	REC setting			13-16	
	5.3	System settir	ng		16-19	
	5.4 \$	System Info			19-20	
	5.5 I	Playback			20-21	
6	USA	GE OF SOF	TWAR	E IN IOS OPERATING SYSTEM		
	6.1	nstall client-e	end soff	ware	. 21-22	
	6.2	How to add E	DVR		. 22-24	
	6.3	Jser operatio	on		24-25	
	6.4	System settir	ngs		25-26	
	6.5 I	How to delete	e DVR		26-27	
7	USA	GE OF SOF	TWAR	E IN ANDROID OPERATING SYSTEM		
	7.1	nstall client-e	end soff	ware	27	
	7.2	How to add E	DVR		27-29	
8	STA	TEMENT			. 29	
9	TRC	UBLE SHO	OTING		30	

CAUTION

- * Please read the following manual details before using.
- * Keep DVR and indoor camera being used in damp-proof and water-proof environment.
- * Don't scratch LCD screen and clean the surface by soft cloth if the screen was dirty.
- * The equipment should be disassembled or repaired only by a qualified technician.



The lighting flash with arrowhead symbol within an equilateral triangle Is intended to alert the user to the presence of uninsulated. "dangerous voltage" within the products enclosure that may be of sufficient magnitude to constitute risk of electric shock to person.



The exclamation point within an equilateral triangle is intended to alert the user to the presence of important operating and maintenance (servicing) instructions in the literature accompanying the appliance.

WARNING

- * To avoid product damage, please install the equipment properly in accordance with the manual and guideline.
- * To avoid personal injury, please pay attention to personal safety during installation

Remarks:

- * Google Play Store, Android are the trademark of Google.Inc.
- * App Store, iOS are the trademarks of Apple.Inc.

2. PRODUCTS OVERVIEW

2.1 9 INCH LCD DVR WITH TOUCH CONTROLS



Icons Introduction

		A									
<u>*</u>											
••											
12 3		4 5 6 7 8 9 10 11 12 13									
1	:	Power indicator									
2	:	IR signal sensor									
3	:	Screen turn on / off									
4	•	Intercom with camera (only for camera with microphone & speaker)									
5	:	Switch single or quad screen									
6	:	Move to left options or volume down									
7	:	Confirm the settings or enter next step									
8	:	Move to next options or next channel									
9	:	Move to previous options or previous channel									
10	:	Move to right options or volume up									
11	:	Enter or Exit the menu									
12	:	Start or Stop manual recording									
13	:	Playback recording list									

Note:

For power-saving and avoidance of accidental touch purpose, the touch icon will switch to resting status (i.e. the lights of icon are off) if no operation for 8 seconds. Please touch any icon for 1 second (i.e. the lights of icon are on) to restart the touch operation function.

9 INCH LCD DVR WITH BUTTON CONTROLS



Button Introduction



7 INCH LCD DVR WITH BUTTON CONTROLS





Button Introduction



2.2 DVR





Button Introduction



2.3 CAMERA





3. SPECIFICATIONS

3.1 LCD DVR

ITEMS	DESCRIPTION
Display Screen	9 inch TFT LCD (16:9) LED back-light
Display Scieen	7 inch TFT LCD (16:9) LED back-light
Resolution	800(H)×RGB×480(V)
	9 inch: 198mm(H)×111.7mm(V)
Display Area	7 inch: 154.08 mm(H) x 85.92mm(V)
White Luminance	250cd/ m ²
Frequency Range	2.4G FHSS

Cameras Supported	4 channels
Transmission distance	200 ${\sim}300$ meters Line of sight
Fromo Doto	2-CH: 15fps@1280X720 HD
Frame Rate	2-CH: 25fps@ 640×480 VGA
Compression	MPEG-4
File Type	ASF
Record Mode	4-CH record separately
Start recording mode	Manual / Motion detect / Schedule
Scheduled Recording	1 Week
Automatic Overwrite	Optional
Maximum SD Card Size	CLASS 10 128GB
Network communication mode	P2P
Network Interface	RJ45 10M/ 100M Ethernet Auto Detect
Mobile Operating System	iOS of Apple, Android of Google
Video playback	Smart phone video playback
Power Supply	100-240V~50/60Hz 5V/2000mA
Power concumption	7 inch LCD DVR 5W max
Power consumption	9 inch LCD DVR 8W max
Operating Temperature	0°C∼+40°C
Operating Humidity	65%
Storage temperature	-10℃~+50℃

3.2 DVR

ITEMS	DESCRIPTION
Frequency Range	2.4G FHSS
Cameras Supported	4 channels
Transmission distance	200 ${\sim}300$ meters Line of sight
Erama Data	2-CH: 15fps@1280X720 HD
	2-CH: 25fps@ 640×480 VGA
Compression	MPEG-4
File Type	ASF
Record Mode	4-CH record separately
Start recording mode	Manual / Motion detect / Schedule
Scheduled Recording	1 Week
Automatic Overwrite	Optional
Maximum TF Card Size	CLASS 10 128GB
Video output	1ch cvbs 1.0Vp-p 75 Ω
Network communication mode	P2P
Network Interface	RJ45 10M/ 100M Ethernet Auto Detect
Mobile Operating System	iOS of Apple, Android of Google
Video playback	Smart phone video playback
Power Supply	100-240V~50/60Hz 5V/2000mA
Power consumption	5W max.
Operating Temperature	0°C∼+40°C
Operating Humidity	65%
Storage temperature	-10℃~+50℃

3.3 OUTDOOR CAMERA

ITEMS	DESCRIPTION
Image Sensor	1/4 inch color CMOS Sensor
Active pixels	1280(H)×720(V)
Horizontal Resolution	1.0 Megapixel
Min illumination	0.1Lux/F=1.2 (0Lux LED On)
Lens	3.6 mm (6mm optional) fixed lens
Night Vision	Yes
IR LED control	Automatic (CDS Sensor)
Quantity of IR LED	24 pcs
Night vision range	12-15 Meters
Frequency Range	2.4G FHSS
Transmission distance	200 ${\sim}300$ meters Line of sight
User ID	Random ID
Outdoor use	Yes
Waterproof	IP55
Operating Temperature	-10℃ ~+40 ℃
Operating Humidity	85%
Storage temperature	-20℃~+50℃
Power Supply	100-240V~50/60Hz 12V/500mA
Power consumption	5W max.

INDOOR BOX CAMERA

ITEMS	DESCRIPTION
Image Sensor	1/4 inch color CMOS Sensor
Active pixels	1280(H)×720(V)
Horizontal Resolution	1.0 Megapixel
Min illumination	0.1Lux/F=1.2 (0Lux LED On)
Lens	3.6 mm (6mm optional) fixed lens
Night Vision	Yes
IR LED control	Automatic (CDS Sensor)
Quantity of IR LED	12 pcs
Night vision range	6-8 Meters
Frequency Range	2.4G FHSS
Transmission distance	200 ${\sim}300$ meters Line of sight
User ID	Random ID
Usage Environment	Indoor
Operating Temperature	0°C∼+40°C
Operating Humidity	65%
Storage temperature	-10℃~+50℃
Power Supply	100-240V~50/60Hz 12V/500mA
Power consumption	5W max.

INDOOR DOME CAMERA

ITEMS	DESCRIPTION
Image Sensor	1/4 inch color CMOS Sensor
Active pixels	1280(H)×720(V)
Horizontal Resolution	1.0 Megapixel
Min illumination	0.1Lux/F=1.2 (0Lux LED On)
Lens	3.6 mm (6mm optional) fixed lens
Night Vision	Yes
IR LED control	Automatic (CDS Sensor)
Quantity of LED	1 pcs Array LED
Night vision range	12 -15 Meters
Frequency Range	2.4G FHSS
Transmission distance	200 \sim 300 meters Line of sight
User ID	Random ID
Usage Environment	Indoor
Operating Temperature	0°C∼+40°C
Operating Humidity	65%
Storage temperature	-10℃~+50℃
Power Supply	100-240V~50/60Hz 12V/500mA
Power consumption	5W max.

4. INSTALLATION

4.1 INSTALL THE LCD DVR



* Plug in the power adapter of the LCD DVR



- * Connect LCD DVR with Router by RJ45 cable
- * Install and lock the bracket of LCD DVR
- * Plug in the power adapter of LCD DVR

4.2 INSTALL THE DVR



- * Install the antenna to DVR
- * Connect DVR with Router by RJ45 cable
- * Connect DVR with TV/monitor by AV cable
- * Plug in the power adapter of DVR

Notes:

- Before using the equipment, please confirm the Router is open DHCP service (Generally, the router is open DHCP service automatically).

Note: This product is no PPPOE dial function, and can not connect with the Modem.

- DVR must be securely installed at the desktop / floor / wall.

4.3 INSTALL THE CAMERA



* Install the antenna to camera

- * Install and lock the bracket of camera
- * Fix camera after pairing
- * Plug in the power adapter of camera

Notes:

- Camera must be installed within the valid transmission range to ensure the DVR can receive the stable and clear image from the cameras.
- Camera must be securely installed at the desktop / floor / wall.

START SURVEILLANCE

After finishing above installation and connection, the monitor will display below interface when the power supply is turned on, then the system starts surveillance.



Description of Icons on the screen:





- (1) Wireless signal
- (2) Camera channel No#
- (3) Recording resolution
- (4) Recording in progress
- (5) Network connection status
- (6) Time and Date
- (7) Memory card inside

5. MENU OPERATION

5.1 CAMERA SETTING

- **5.1.1 Pairing –** To pair the camera with a selected DVR channel.
- 5.1.1.1 Plug and turn on the power adapters of DVR and cameras.
- 5.1.1.2 Press "**Menu**" to enter the main menu, and press "◀ ►" to select "**Camera setting**", then press "**Enter**" to enter next step. Press "▲ ▼" to select "**Pairing**".



5.1.1.3 At the "**Pairing**" screen, press the "**Enter**" to enter next step, and press "▲ ▼" to select "**Cam 1-2-3-4**", and press "**Enter**" to confirm, then press "**Pairing**" button at the back of camera within **30 seconds** to finish pairing.



Note:

- If no video displayed on the screen, it means the pairing is not successful, please repeat the above operation again.
- The system support up to 4 cameras.

5.1.2 Camera On/Off – To turn on / off the DVR recording channel.

At the "Camera setting" screen, press "▲ ▼" to select "Camera ON/OFF", and press "Enter" to enter next step. Press "▲ ▼" to select "Cam 1-2-3-4", and press "◄ ▶" to select "ON/OFF", then press "Enter" to confirm and press "Menu" to exit.



Note: Dual screen display if only set 2 cameras as "ON".

5.1.3 Resolution – To choose the recording resolution as VGA or HD

At the "Camera setting" screen, press "▲ ▼" to select "Resolution" and press "Enter" to enter next step. Press "▲ ▼" to select "Cam 1-2-3-4", and press "◀ ▶" to select "VGA/HD", then press "Enter" to confirm and press "Menu" to exit.



Note: maximum support 2 channel in HD resolution.

5.1.4 Brightness – To adjust the brightness of image displayed on the screen

At the "Camera setting" screen, press" ▲ ▼" to select "Brightness" and press "Enter" to enter next step. Press " ▲ ▼" to select "Cam 1-2-3-4", and press " ◀ ▶" to select "1-6", then press "Enter" to confirm and press "Menu" to exit.

Camera Setting	Brightness				
Pairing Anti-flicker	Cam1 ┥ 5 🕨				
Camera On/Off	Cam2 🖣 5 🕨				
Resolution	Cam3 ┥ 5 🕨				
Brightness	Cam4 ┥ 5 🕨				

5.1.5 Anti-flicker – To choose the frequency according to local video system

At the "**Camera setting**" screen, press "▲ ▼" to select "**Anti-flicker**" and press "**Enter**" to enter next step. Press "▲ ▼" to select "**60Hz/50Hz**", then press "**Enter**" to confirm and press "**Menu**" to exit.

Camera Setting	Anti-flicker					
Pairing Anti-flicker	60Hz					
Camera On/Off	50Hz					
Resolution						
Brightness						

5.2 REC SETTING

5.2.1 REC Mode - To choose the trigger ways of video recording

Press "**Menu**" to enter the main menu, and press "◀ ►" to select "**REC Setting**", then press "**Enter**" to enter next step. Press "▲ ▼" to select "**REC Mode**" column.



At the "**REC mode**" screen, press "▲ ▼" to select "**Cam 1-2-3-4**", and press "◀ ▶" to select "**Motion/Manual/Schedule**", then press "**Enter**" to confirm and press "**Menu**" to exit.



- **5.2.2 Scheduled Setting –** To set the recording schedule for each camera

Reco		024	Sun 68	iday 10 12	14 16	18 20	22 24	
REC Mode	File Overwrite	Cam1						
Scheduled Setting		Cam2						
		Cam3						
Motion Detection		Cam4						
Section							Moc	lify

5.2.2.2 At the "Scheduled Recording" screen, press " ◄ ▶" to select "Cam 1-2-3-4" and press "Enter" to confirm. Press " ◀ ▶" to enter time setting and press " ▲ ▼" to adjust the digit. Then press" ◀ ▶" to select the date at "Mon/Tue/Wed/Thu/Fri/Sat/Sun". Press" ◀ ▶" to select "Set", and press "Enter" to confirm.

Scheduled Recording	i Monday
Cam1 Cam2 Cam3 Cam4	0 2 4 6 8 10 12 14 16 18 20 22 24 Cam1
00:00 24:00	Cam2
00.00 ~ 24.00	Cam3
Mon Tue Wed Thu Fri Sat Sun	Cam4
Set Delete	Modify



5.2.2.3 Delete the scheduled setting, please do the same operations as above to select the date, time and channel, then press" < ►" to select "Delete", then press "Enter" to confirm and press "Menu" to exit.

Monday	Scheduled Recording
0 2 4 6 8 10 12 14 16 18 20 22 24 Cam1	Cam1 Cam2 Cam3 Cam4
Cam2	00:00 ~ 24:00
Cam3	00.00 ~ 24:00
Cam4	Mon Tue Wed Thu Fri Sat Sun
Modify	Set Delete
Sunday	
Cam1	
Cam2	
Cam3	
Cam4	

5.2.3 Motion Detection – To choose the detection sensitivity as per needs

At the "**Recording**" screen, press "▲ ▼" to select "**Motion Detection**", press "**Enter**" to enter next step, and press "**Enter**" at the Motion Detection screen to enter next step. Press "▲ ▼" to select "**Cam 1-2-3-4**", and press "◀ ▶" to select "**Low/Mid/High**", then press "**Enter**" to confirm and press "**Menu**" to exit.

Recording	Motion Detection
REC Mode File Overwrite	
Scheduled Setting	Sensitivity
Motion Detection	
Section	
Sensitivity	
Cam1 ┥ High 🕨	
Cam2 ┥ Mid 🕨	
Cam3 ┥ Low 🕨	
Cam4 ┥ Low 🕨	

5.2.4 Section – To set the recording time period of per folder.

At the "**Recording**" screen, press "▲ ▼" to select "**Section**", press "**Enter**" to enter next step. Press "▲ ▼" to select "**5 min / 10 min / 15 min**", then press "**Enter**" to

confirm and press "Menu" to exit.

Recording	Section
REC Mode File Overwrite	5 min
Scheduled Setting	10 min
Motion Detection	15 min
Section	

5.2.5 File Overwrite - To determine DVR continue recording or not when the memory card is full

At the "**Recording**" screen, press " $\blacktriangle \lor$ " to select "**File Overwrite**", press "**Enter**" to enter next step. Press " $\blacktriangle \lor$ " to select "**YES / NO**", then press "**Enter**" to confirm and press "**Menu**" to exit.

Recording	File Overwrite
REC Mode File Overwrite	YES
Scheduled Setting	NO
Motion Detection	
Section	

- "YES": the new video recording will automatically overwrite the old video recording in SD card, when the SD card is full.
- "NO": the DVR will show "Card Error Retry Please..", when the SD card is full.

5.3 SYSTEM SETTING

5.3.1 Date & Time – To set the date and time of the system

Press the "Menu" to enter the main menu, and press " \blacktriangleleft \blacktriangleright " to select "System Setting", then press "Enter" to enter next step. Press " \blacktriangle \checkmark " to select "Date & Time" column and press "Enter" to enter.



At the "**Date & Time**" screen, press "◀ ►" to select "**DATE**" and "**TIME**", then press "▲ ▼" to select digit "0 – 9 ","DATE" and "TIME", then press "**Enter**" to confirm and

press "Menu" to exit.



5.3.2 Video Out - To choose the video output to TV/monitor or LCD DVR

At the "Setting" screen, press " $\blacktriangle \lor$ " to select "Video Out", and press "Enter" to enter next step. Press " $\blacktriangle \lor$ " to select "NTSC / PAL/Panel ", then press "Enter" to confirm and press "Menu" to exit.



Note:

- NTSC video will output to TV / Monitor with NTSC video system
- PAL video will output to TV / Monitor with PAL video system
- Panel video will display at the monitor, which is only for LCD DVR.

5.3.3 Format – To delete all video and image stored in the SD card

At the "Setting" screen, press " \blacktriangle \checkmark " to select "Format", and press "Enter" to enter next step. Press " \blacktriangle \checkmark " to select "YES / NO ", then press "Enter" to confirm and press "Menu" to exit.



Note: DVR can discern the new SD card by this operation.

5.3.4 Default Setting – To restore to the factory default settings

At the "Setting" screen, press "▲ ▼" to select "Default Setting", and press "Enter"

to enter next step. Press "▲ ▼" to select "**YES / NO** ", then press "**Enter**" to confirm and press "**Menu**" to exit.



5.3.5 Alarm – To set audio alarm triggered or not when motion detected

At the "Setting" screen, press " $\blacktriangle \lor$ " to select "Alarm", and press "Enter" to enter next step. Press " $\blacktriangle \lor$ " to select "ON / OFF ", then press "Enter" to confirm and press "Menu" to exit.



"ON": DVR will sound "beep..." alarm when motion detected

5.3.6 Firmware Update – To update latest firmware if any.

At the "Setting" screen, press " $\blacktriangle \lor$ " to select "Firmware Update", and press "Enter" to enter next step. Press " $\blacktriangle \lor$ " to select "YES / NO ", then press "Enter" to confirm and press "Menu" to exit.



5.3.7 Language – To choose language as per user's needs

At the "Setting" screen, press " $\blacktriangle \lor$ " to select "Language", and press "Enter" to enter next step. Press " $\blacktriangle \lor$ " to select "English / Deutsch / Italiano", then press "Enter" to confirm and press "Menu" to exit.



- 5.3.8 Network To check or set the network connection
- 5.3.8.1 At the "**Setting**" screen, press "▲ ▼" to select "**Network**", and press "**Enter**" to enter next step. Press "◀ ▶" to select "**Dynamic IP**", then press "**Enter**" to confirm and press "**Menu**" to exit.

Set	ting	Netv	vork
Date & Time	Alarm	Static IP	Dynamic IP
Video Out	Firmware Update		
Format	Language	0	N
Default Setting	Network		

5.3.8.2 At the "Network" screen, press "< ▶" to select "Static IP" and press "▲ ▼" to select "Address /Mask/Gateway" and press "Enter" to confirm. Press "< ▶" to adjust the digit of "0 – 9", then press "Enter" to confirm and press "Menu" to exit.



System defaults Dynamic IP ON and will automatically obtain IP data

- Green mark n displayed at the monitor means the network connection is successfully
- Red mark
 displayed at the monitor means the network connection is unsuccessfully

5.4 SYSTEM INFO

5.4.1 Card Info – To check the SD card information

Press "**Menu**" to enter the main menu, and press "◀ ▶" to select "**System Info**", then press "**Enter**" to enter next step. Press "▲ ▼" to select "**Card Info**" at System Info screen and press "**Menu**" to exit.



5.4.2 Version – To check the version information of firmware

At the "**System Info**" screen, press "▲ ▼" to select " **Version** " and press "**Enter**" to check the machine software version, then press "**Menu**" to exit.



5.4.3 Network Info - To check the network information

At the "System Info" screen, press "▲ ▼" to select "Network Info " and press "Enter" to check the machine IP address and UID No#, then press "Menu" to exit.



5.5 **PLAYBACK** – To review the recording files stored in the SD card.

Press "**Menu**" to enter the main menu, and press "◀ ►" to select "**PLAYBACK**", then press "**Enter**" to enter next step.



At the "Folder Name" screen, press " \blacktriangle \checkmark " to select the file (e.g. "00000040") and press "Enter" to enter next step. Press " \blacktriangle \checkmark " to select camera channel/date/time concrete file (e.g. 153147-3 / 2014/02019 / 15:31:46), then press "Enter" to play or press "Menu" to exit.

Colder Name		File Name	Date	Start Time
Folder Name	1	153147-3	2014/02/19	15:31:46
00000040 00000039 00000038 00000037	1	153029-3 152901-4	2014/02/19 2014/02/19	15:30:28 15:29:00
Page 0001/0001			Pag	e 0001/0001

Note:

- Folders are sorted by recording time, and daily recording files are packed in same folder.
- Files are named by the recording time and channel. For example: 153147-3 means channel 3 begins recording at 15:31:47 (which is little later than the starting time).

6. USAGE OF SOFTWARE IN IOS OPERATING SYSTEM

Apple mobile phones and iPad tablet PC hereafter refer as "Apple phone". Before using the software, please open the phone Wi-Fi function or 3G data services, and ensure the Apple phone can connect to the internet properly.

6.1 INSTALL CLIENT-END SOFTWARE





APP iHomeCam

Use Apple phone to search "**iHomeCam**" APP (as below picture) in the Apple App Store, and install the software.



6.2 HOW TO ADD DVR

6.2.1 After software installation is completed, please search icon "**iHomeCam**"(as below picture) at your Apple phone desktop.



6.2.2 Click the icon "iHomeCam" to display the following interface







21:06	❷ 100% ⊑⊉	No SIM 🔶	20:43	10
amera	Save		Camera List	
		Q		
KEU	Z9N9		Camera Online	
	\otimes	н	FZ61LW7FKEUZ9N9Y8MF	1
678	B 9 0			
) \$ 8	. @ "			
ļ				
	' 🛛			
	return	(et et	(
		Camera	Event Add Camera	Ap



Equipment real-time viewing shortcut interface

Name UID Passwo

2 3



Equipment event lists



Add camera

Mobile phone Software version

THREE METHODS TO ADD DVR

6.2.2.1 Add DVR by searching local network DVR

Click and Click to begin searching for Local area network DVR. Select the DVR,

enter the password. Click the "Save" to add DVR to the list.

6.2.2.2 Add DVR by scanning QR Code

Click code to obtain UID automatically, then enter password and click the **"Save"** to finish adding DVR.

6.2.2.3 Add DVR by manually operation

Click and device adding interface will appear. Enter "**Name**", "**UID**", "**Password**" accordingly, and click "**Save**" to finish adding DVR.

[Name] : User-defined name

(UID): DVR unique identification No#, which can be found at the label on the DVR or DVR's **MENU** - **System Info** – **Network Info** - **UID**.

[Password] : Default password is 000000

Note: Please change the password for safety purpose.

Camera Online

FZ61LW7FKEUZ9N9Y8MF1

[Save] : Click **Save** after finishing above.

Channel

6.3 USER OPERATION

6.3.1After adding DVR successfully, click

viewed.





No SIM 😚	20:43	9 100% 🗲
_	Camera - CH1	_
Back	Live View	Channel
CH1		~
CH2		
СНЗ		
CH4		

image on DVR can be

6.3.2 Click the icon phone.





CH1-CH2-CH3-CH4, then images can be viewed on Apple

6.3.3 Full-screen display function: Start Apple phone to horizontal screen and put it horizontally to get full-screen display, then click the screen and the status bar is hidden.

6.3.4 Introduction of Icons:



Select camera channel (CH1/CH2/CH3/CH4)

Back to previous step.



6.4 SYSTEM SETTINGS

6.4.1Enter into system settings

Press	for 2 seconds, the	e below windows appear.
No SIM 🗢 9:32 🔮 98% 🖙	No SIM 🗢 20:47 🔮 100% 🖬	
Back Edit Camera	Back Advanced Setting	
FZ61LW7FKEUZ9N9Y8MF1	Security Code	
Name Camera	Video Quality High >	
Password •••••	Time Zone GMT +8:00 Taiwan	
Advanced Setting	About Device >	
Reconnect Online		

[Name] The initial device name

[Password] Default password 000000

[Advanced Setting] Access to the system parameter modification

[Reconnect] Refresh network signal coupling

6.4.2 Security Code settings

No SIM 🗢 20:4 Back Advanced	.7 ● 100% ⊑≱ I Setting	No SIM 중 20:47 ● 100% С Cancel Security Code ОК	No SIM 🗢 9:56 ● 100% 🗳 Cancel Security Code OK
Security Code	>	Old Old Password	Old •••••
Video Quality	High	New New Password	New •••••
video quality	nigit 🖌	Confirm Confirm Password	Confirm •••••
Time Zone	GMT +8:00 Taiwan		
About Device	>		1 2 3 4 5 6 7 8 9 0
			- / : ; () \$ & @ "
			#+= . , ? ! ' 🗙
			ABC space return

Fill the old password firstly, then fill the new password and confirm password, then click "OK".

Note: Please change the password for safety purpose.

6.4.3 Video Quality

According to the customer's internet conditions (e.g. Internet signal, speed) to adjust the parameter (Max/High/Medium/Low/Min) of the real time play back results. High

wean selected High.

Back Click

to go back the previous step.

Security Code	>	Max		
/ideo Quality	High >	High		
naco quanty	riigii 🖌	Mediu	n	
Time Zone	GMT +8:00 Taiwan	Low		
		Min		
About Device	>			

6.4.4 About Device

It shows the software version and SD/TF card information.

sim रू 20:47 ack Advanced S	● 100% ⊑ etting
Security Code	>
ida o Ouslitu	Link A
	High ¥
Time Zone	GMT +8:00
	Tawan
About Device	>

6.5 HOW TO DELETE DVR





7. USAGE OF SOFTWARE IN ANDROID OPERATING SYSTEM

Android mobile phones and Android tablet PC hereafter refer as "Android phone". Before using the software, open the phone Wi-Fi function or 3G data services, and ensure the Android phone can connect to the Internet properly.

7.1 INSTALL CLIENT-END SOFTWARE



APP iHomeCam

Use Android phone to search "**iHomeCam**" APP (as below picture) in the Google Play Store, and install the software.



7.2 HOW TO ADD DVR

7.2.1 After software installation is completed, please search icon "**iHomeCam**"(as below picture) at your Android phone desktop.



7.2.2 Click the icon "iHomeCam" to display the following interface.

		10日本 10日本 10日本 10日本 10日本 10日本 10日本 10日本	Add Camera
■4 请按此新增摄(象机	设备设置	Device Setting
		UID:	UID:
		扫描条码 搜索	Scan Search
		· · · · · · · · · · · · · · · · · · ·	Security Code:
		5种 Camera	Name Camera
			Search camera from LAN
			192 168 1.143
			Hetresh
		确定 取消	OK Cancel
	! 🖂 💠 4) 9:08 호스마	← ① □ □ ◇ ◇ ◇ ※ シ ☞ 9:13 ♥/■	← 合 □ □ ◇ 小 № ?■● 9:22 🕏
Add Camera		P22CamUre E Home ©	PSPCamLive Dire View Henre CH
,	E7611 W7EKE1/20N9V8ME1	Crite	
	Scan Search		
nitu Coder			
le:	Home		

THREE METHODS TO ADD DVR

7.2.2.1 Add DVR by searching local network DVR

Click Search to begin to search Local area network DVR. Select the DVR and enter the password, then click the "**OK**" to finish adding new DVR.

7.2.2.2 Add DVR by scanning QR Code

Click ^{Scan} to scan QR code to obtain UID automatically, then enter password and click the **"OK**" to finish adding DVR.

7.2.2.3 Add DVR by manually operation

Click[®] and device adding interface will appear. Enter "**Name**", "**UID**", "**Password**" accordingly, and click "**OK**" to finish adding DVR.

[Name] : User-defined name

[UID]: DVR unique identification No#, which can be found at the label on the DVR or DVR's **MENU** - **System Info** – **Network Info** - **UID**.

[Password] : Default password is 000000

Note: Please change the password for safety purpose.

[OK] : Click **OK** after finishing above.

The rest usage of software in Android phone is same as above Apple's, please refer the contents of above 6.3 --6.4.

8. Statement

The specification and information in this manual is only for reference. Any content maybe be updated (if any) without prior notice, unless there are special conventions. All statements, information in this manual does not constitute any warranty or guarantee. The version of the firmware and the software used for iOS and Android operating system maybe be upgraded without prior notice, some features maybe be different from this manual.

9. Trouble Shooting

9.1 Devices are not pairing

- 1. Check the camera and DVR are correctly connected with power adapters and the power supply is turned on.
- 2. Check the camera and DVR are pairing within 10 meters.

9.2 No images on the monitor

- 1. Check the camera and DVR are correctly connected with the power adapter and the power supply is turned on.
- 2. Confirm LCD DVR status indicator is in green or red, green indicator means screen is turned on; red indicator means screen is turned off.
- 3. Make sure there is nothing obstructing the view of the camera.
- 4. Make sure the camera is within the limited transmission distance.
- 5. Try re-pair the camera and DVR

9.3 Network can not connect or "failed"

- 1. Confirm DVR network indicator light is on.
- 2. Check DVR is connected properly. (Note: This product is no PPPOE dial function, can not connect directly to the modem)
- 3. Make sure the router is turned on DHCP service.
- 4. Make sure ID number or password is filled correctly.
- 5. Make sure the router work normally.

9.4 Network connect successfully, but without images

- 1. Make sure the camera under this channel of DVR has image
- 2. Make sure the pairing between DVR and camera is successful.
- 3. Make sure the camera is within the limited transmission distance.
- 4. Make sure the network is ok, the network speed is not less than 128kbps.
- 5. Confirm the intelligent terminal CPU speed is not less than 1GHz, the early Android devices can not reach this speed.

9.5 Wrong password can not be accessed

- 1. Check password is correct or not.
- 2. Select Restore factory settings in the network DVR menu, the system will be restored to the factory default status.