

Wave LED

### WAL025969

Old item no.: 18945LG



#### Wave LED T45 Lg 800 840 5D CLA NA

Wave LED is an illuminated magnifier for industrial applications. No knobs to tighten, nothing to adjust - a flexible, self-balancing shade and hands-free neck assembly combined with 45" heavy-duty internal-spring parallel, three-pivot K-arm, allows the lamp head to be secured in any position. The fully-enclosed neck design is ideal for environments where FOD is a concern. An automatic shut-off feature and step dimming further ensures energy savings. WAVE LED offers shadow-free 5-diopter (2.25X) magnification with light coming from both sides, as well as three-dimensional magnification lighting from the left or right. The 3D-feature is especially welcome when working with circuit board and similar delicate objects. Edge clamp mount. Color: light grey.

Lightsource	
Number of lamps	2
Lightsource	LED
CRI and/or Color Temperature	80 CRI, 4000K
Lamp power (W)	1 2
Lumen/Watt	5 9
LLMF LED 50000h Ta25	0.80
Average useful life (IEC 62717) Ta25	50000
Lumen Out	764
Optic	
Primary Lens (D)	5
Working distance (mm)	200
Magnification (X)	2.25
Technical data	
Maximum ambient temperature (°C)	2 5
IP classification	20









Electrical data	
Maximum voltage (V)	2 4 0
Maximum frequency (Hz)	6 0
Minimum frequency (Hz)	5 0
Voltage from (V)	110
Total consumption (W)	1 3
Termination	
Plug type	NΑ
Cord length (ft)	5
Mounting	Edge clamp
Dimensions	
Net weight (kg)	4,5
Arm length (in.)	4 5
Body	
Body color	Grey



# Wave LED WAL025969



### Wave LED T45 Lg 800 840 5D CLA NA

Wave LED is an illuminated magnifier for industrial applications. No knobs to tighten, nothing to adjust - a flexible, self-balancing shade and hands-free neck assembly combined with 45" heavy-duty internal-spring parallel, three-pivot K-arm, allows the lamp head to be secured in any position. The fully-enclosed neck design is ideal for environments





## Drawings

