Thin Wall PTFE Insulating Tubing





RoHS Compliant

Description

TTI (AWG) series is a thin wall, chemically inert tubing which offers superior insulating properties. It features excellent flex life, heat resistance and is self extinguishing.

Applications

- · Electrical Insulation
- · Protective Cover
- Circuit Board
- · Wire Insulation
- · Strain Relief
- · Introducer
- · Stent Delivery

Features

- · Virgin Polytetrafluoroethylene resin
- · Chemically inert
- · Lowest coefficient of friction
- · Superior dielectric strength
- · Exceptional heat resistance
- Self extinguishing
- Non-wetting
- · Excellent flexlife
- Laser markable

Specifications

Material : PTFE Colour : Natural

Working Temperature : 260°C (500°F) Flammability : UL83 (natural)

Certifications/Compliance

- ASTM D3295 Class 2
- AMS 3653E
- AMS 3655B
- UL-224 300V 200°C
- CSA 9032-01 300V
- VW1, UL-83 (natural)
- FDA Compliant
- USP Class VI Compliant


www.element14.com www.farnell.com www.newark.com www.cpc.co.uk



Thin Wall PTFE Insulating Tubing



Diagram



PTFE TTI Thin Wall (AWG) Series

	AWG Size	Inside Diameter						Wall Thickness	
Part Number		Nominal I.D.		Minimum I.D.		Maximum I.D.		Nominal Wall	
		Inch	mm	Inch	mm	Inch	mm	Inch	mm
TTI-S28-1100-NAT	28	0.015	0.38	0.013	0.33	0.018	0.46	0.009 ± 0.002	0.23 ± 0.05
TTI-S26-1100-NAT	26	0.018	0.46	0.016	0.41	0.022	0.56	0.009 ± 0.002	0.23 ± 0.05
TTI-S24-1100-NAT	24	0.022	0.56	0.02	0.51	0.026	0.66	0.010 ± 0.003	0.25 ± 0.08
TTI-S22-1100-NAT	22	0.028	0.71	0.025	0.64	0.032	0.81	0.010 ± 0.003	0.25 ± 0.08
TTI-S20-1100-NAT	20	0.034	0.86	0.032	0.81	0.04	1.02	0.012 ± 0.003	0.31 ± 0.08
TTI-S18-1100-NAT	18	0.042	1.07	0.04	1.02	0.049	1.25	0.012 ± 0.003	0.31 ± 0.08
TTI-S16-1100-NAT	16	0.053	1.35	0.051	1.3	0.061	1.55	0.012 ± 0.003	0.31 ± 0.08
TTI-S14-1100-NAT	14	0.066	1.68	0.064	1.63	0.074	1.88	0.012 ± 0.003	0.31 ± 0.08
TTI-S12-1100-NAT	12	0.085	2.16	0.081	2.06	0.091	2.31	0.012 ± 0.003	0.31 ± 0.08
TTI-S10-1100-NAT	10	0.106	2.69	0.102	2.59	0.112	2.84	0.012 ± 0.003	0.31 ± 0.08
TTI-S08-1100-NAT	8	0.133	3.38	0.129	3.28	0.141	3.58	0.015 ± 0.003	0.38 ± 0.08
TTI-S06-1100-NAT	6	0.166	4.22	0.162	4.11	0.178	4.52	0.015 ± 0.003	0.38 ± 0.08
TTI-S00-1100-NAT	0	0.33	8.38	0.325	8.25	0.347	8.81	0.015 ± 0.003	0.38 ± 0.08

Part Number Table

Description	Packaging	Part Number	
		TTI-S28-1100-NAT	
		TTI-S26-1100-NAT	
T.: W. !! DTEE		TTI-S24-1100-NAT	
Thin Wall PTFE Insulating Tubing	100ft 30.5m	TTI-S22-1100-NAT	
inicalating rabing	00.011	TTI-S20-1100-NAT	
		TTI-S18-1100-NAT	
		TTI-S16-1100-NAT	

Description	Packaging	Part Number		
Thin Wall PTFE		TTI-S14-1100-NAT		
		TTI-S12-1100-NAT		
	100ft	TTI-S10-1100-NAT		
Insulating Tubing	30.5m	TTI-S08-1100-NAT		
		TTI-S06-1100-NAT		
		TTI-S00-1100-NAT		

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

