# Product data sheet Characteristics

# XPSAF5130

# module XPSAF - Emergency stop - 24 V AC DC



Preventa Safety automation Preventa safety module XPSAF
·
XPSAF
For emergency stop and switch monitoring
Monitoring of a movable guard Emergency stop monitoring 1-channel wiring Emergency stop monitoring 2-channel wiring
Can reach PL e/category 4 conforming to EN/ISO 13849-1 Can reach SILCL 3 conforming to EN/IEC 62061
DC > 99 % conforming to EN/ISO 13849-1 MTTFd = 243 years conforming to EN/ISO 13849-1 PFHd = 4.62E-9 1/h conforming to EN/IEC 62061
Configurable
Captive screw clamp terminals, clamping capacity: 2 x 0.52 x 1.5 mm² flexible cable with cable end with double bezel  Captive screw clamp terminals, clamping capacity: 1 x 0.141 x 2.5 mm² flexible cable with cable end, with double bezel  Captive screw clamp terminals, clamping capacity: 1 x 0.141 x 2.5 mm² solid cable with cable end, with double bezel  Captive screw clamp terminals, clamping capacity: 1 x 0.251 x 1.5 mm² flexible cable with cable end, with double bezel  Captive screw clamp terminals, clamping capacity: 1 x 0.251 x 2.5 mm² flexible cable with cable end, with double bezel  Captive screw clamp terminals, clamping capacity: 2 x 0.142 x 0.75 mm² flexible cable with cable end, with double bezel  Captive screw clamp terminals, clamping capacity: 2 x 0.142 x 0.75 mm² solid cable with cable end with double bezel  Captive screw clamp terminals, clamping capacity: 2 x 0.252 x 1 mm² flexible cable with cable end, with double bezel
Relay instantaneous opening 3 NO, volt-free
0
24 V AC (- 1510 %) 24 V DC (- 1510 %)

#### Complementary

Complementary		
Synchronisation time between inputs	Unlimited	
Supply frequency	50/60 Hz	imer:
Power consumption in VA	<= 5 VA AC	

Internal, electronic
24 V
90 Ohm
C300 : 180 VA, AC-15 (holding) for relay output C300 : 1800 VA, AC-15 (inrush) for relay output
1.5 A at 24 V (DC-13) time constant: 50 ms for relay output
6 A per relay for relay output
18 A
4 A fuse type gG or gL for relay output conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200 6 A fuse type fast blow for relay output conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200
10 mA for relay output
17 V for relay output
<= 40 ms
300 V (degree of pollution: 2) conforming to DIN VDE 0110 part 1 300 V (degree of pollution: 2) conforming to IEC 60947-5-1
4 kV overvoltage category III conforming to IEC 60947-5-1 4 kV overvoltage category III conforming to DIN VDE 0110 part 1
3 LEDs
30 mA at 24 V AC (on power supply)
35 mm symmetrical DIN rail
0.25 kg

## Environment

Standards	EN 1088/ISO 14119 EN 60204-1 EN/IEC 60947-5-1 EN/ISO 13850
Product certifications	CSA TÜV UL
IP degree of protection	IP20 (terminals) conforming to EN/IEC 60529 IP40 (enclosure) conforming to EN/IEC 60529
Ambient air temperature for operation	-2560 °C
Ambient air temperature for storage	-4085 °C


## Contractual warranty

<b></b>	
Warranty period	18 months

# Product data sheet Dimensions Drawings

# XPSAF5130

## **Dimensions**



## XPSAF5130

### Wiring Diagrams

#### Refer to the Instruction Sheet

To download the instruction sheet, follow below procedure:



- Click on Download & Documents.
- Click on Instruction sheet.