

# Label - MM-EML (EX12)R C1 WH/BK - 0803971

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Label, continuous, cassette, white with black imprint, mounting type: adhesive, can be marked with THERMOFOX

## Product Description

The MM-EML... polyamide self-adhesive labels are available as continuous media for equipment marking.



## Key Commercial Data

Packing unit	1 STK
GTIN	
GTIN	4055626212470
Weight per Piece (excluding packing)	58.100 g
Custom tariff number	39199080
Country of origin	China

## Technical data

### Dimensions

Length (b)	8000 mm
Width (a)	12 mm

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 149 °C
---------------------------------	-------------------

### General

Color	white
Components	free from silicone, halogen, and cadmium
Material	Polyester
RoHS compliant	Yes
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Adhesive	Acrylic
Printability	Thermal transfer

## Label - MM-EML (EX12)R C1 WH/BK - 0803971

### Technical data

#### General

Device	0803984 THERMOFOX
Marking mounting type	adhesive

#### Standards and Regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

### Classifications

#### eCl@ss

eCl@ss 4.1	24190219
eCl@ss 5.1	27141137
eCl@ss 6.0	27141137
eCl@ss 8.0	27149129
eCl@ss 9.0	27400629

#### ETIM

ETIM 5.0	EC001288
ETIM 6.0	EC001288

#### UNSPSC

UNSPSC 13.2	39131504
-------------	----------