


Clamp Meter



**RoHS
Compliant**



Specifications

Clamp size	Opening 1.2" (30mm) approx
Diode Test	Test current of 0.3mA typical; Open circuit voltage 1.5V DC typical.
Continuity Check	Threshold <150Ω; Test current < 0.5mA
Low Battery Indication	"  " is displayed
Overrange Indication	"OL" is displayed
Measurements Rate	2 per second, nominal
Input Impedance	10MΩ (V DC and V AC)
Display	4000 counts LCD
AC Current	50-60Hz (A AC)
AC Voltage Bandwidth	50-400Hz (V AC)
Non-contact Voltage Detection	-
Operating Temperature	41°F to 104°F (5°C to 40°C)
Storage Temperature	-4°F to 140°F (-20°C to 60°C)
Operating Humidity	Max. 80% up to 87°F (31°C) decreasing linearly to 50% at 104°F (40°C)
Storage Humidity	<80%
Operating Altitude	7000ft. (2000m) maximum.
Over Voltage	Category III 600V
Battery	One 9V Battery
Auto OFF	Approx. 30 minutes

Electrical Specifications

Function	Range & Resolution	Accuracy (% of reading)
AC Current (50/60Hz)	40.00A AC	±(2.5 % + 8 digits)
	400.0A AC	±(2.8 % + 5 digits)
DC Current	40.00 A DC	±(2.5 % + 5 digits)
	400.0A DC	±(2.8 % + 5 digits)
DC Voltage	400.0mV DC	±(0.8% + 2 digits)
	4.000V DC	± (1.5% + 2digits)
	40.00V DC	
	400.0V DC	
	600.0V DC	±(2 % + 2 digits)
AC Voltage (50-400Hz)	400.0mV AC	±(1.5% + 30 digits)
	4.000V AC	±(1.5% + 5 digits)
	40.00V AC	



Clamp Meter



Function	Range & Resolution	Accuracy (% of reading)
AC Voltage (50-400Hz)	400.0V AC	±(1.5% + 5 digits)
	600.0V AC	±(2.0% + 5 digits)
Resistance	400.0Ω	±(1.0% + 4 digits)
	4.000kΩ	±(1.5% + 2 digits)
	40.00kΩ	
	400.0kΩ	
	4.000MΩ	±(2.5% + 3 digits)
	40.00MΩ	±(3.5% + 5 digits)
Capacitance	40.00nF	±(4.0% reading + 20 digits)
	400.0nF	±(3% reading + 5 digits)
	4.000μF	
	40.00μF	
	100.0μF	±(4.0% reading + 10 digits)
Frequency	10-10kHz Sensitivity: 100V(<50Hz); 50V(50 to 400Hz; 15V(401Hz to 10kHz)	±(1.5% reading + 2 digits)
Temp (type-K) (probe accuracy not included)	-20°C to 760°C	±(3% rdg +5°C)
	-4°F to 1400°F	±(3% rdg +9°F)

Part Number Table

Description	Part Number
Clamp Meter, AC/DC, 30mm Jaw	72-14400

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell Limited 2016.

