

**Cable glands  
VG M32 - MS 68**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Screwed joints that comply with the high demands of class of protection IP 68

**General ordering data**

Type	VG M32 - MS 68
Order No.	<a href="#">1772240000</a>
Version	Cable glands, Cable gland, M 32, 9 mm, OD min. 13.00 - OD max. 18.00 mm, IP54, IP66, IP67, IP68 - 5 bar (30 min.), IP69K, Brass, nickel-plated
GTIN (EAN)	4032248129898
Qty.	10 pc(s).

**Cable glands  
VG M32 - MS 68**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

Length	42 mm	Length (inches)	1.654 inch
Net weight	87.44 g		

**General information**

AF size 1	30 mm	AF size 2	34 mm
Cable gland	metric	Clamp insert	Polyamide
External thread	M 32	Length of thread	9 mm
Material	Brass, nickel-plated	O-Ring	NBR
Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
Outer cable diameter, max.	18 mm	Outer cable diameter, min.	13 mm
Pitch of thread	1.5 mm	Protection degree	IP54, IP66, IP67, IP68 - 5 bar (30 min.), IP69K
Protection degree with GWDR	IP54, IP66, IP67, IP68 - 5 bar (30 min.), IP69K	Seal insert	CR
Sealing	NBR	Torque for cap nut, max.	18 Nm
Torque for cap nut, min.	16 Nm	Torque for connecting adapter, max.	7 Nm
Torque for connecting adapter, min.	5 Nm		

**Classifications**

ETIM 3.0	EC000441	ETIM 4.0	EC000441
ETIM 5.0	EC000441	ETIM 6.0	EC000441
UNSPSC	30-21-18-01	eClass 5.1	27-14-91-09
eClass 6.2	27-14-91-09	eClass 7.1	27-14-91-09
eClass 8.1	27-14-91-09	eClass 9.0	27-14-44-32
eClass 9.1	27-14-44-32		

**Product information**

Descriptive text ordering data	Long-thread version on request VDE for metric version
Descriptive text technical data	Length "L" varies depending on the cable diameter used; IP69K applies to all metric cable glands; the following thread sizes PG29, PG36, PG42 and PG48 are excluded from IP69K.

**Approvals**

Approvals



ROHS Conform

**Downloads**

Brochure/Catalogue	<a href="#">CAT 3 HDC 17/18 EN</a> <a href="#">CAT 5 ENCL 17/18 EN</a>
Engineering Data	<a href="#">EPLAN, WSCAD</a>