02/05/18 V1.0

BNC Straight Plug, Crimp multicomp

Specifications

Electrical

Frequency Range Nominal Impedance Voltage Rating VSWR

Material

Shell Crimp Ferrule Center Contact Insulation Body Washer Spring Washer Gasket

Mechanical


Interface in Accordance with Cable Type Cable Attachment

Crimp Size Required

Environmental

Operating Temperature Range : -20°C to +80°C

Diagram





: DC - 4GHz

: 500V Max.

: Zinc, Nickel Plated

: Brass, Nickel Plated

: Brass, Gold Plated

: SK-5, Nickel Plated

: RG-58U or Equivalent

: Contact: 1.8(0.071) Hex Crimp Tool Ferrule: 5.5(0.216) Hex Crimp Tool

: Rubber, Red

: MIL-STD-348A


: Outer: Crimp Inner: Solder/Crimp


: Brass, 100µ" Nickel Plated : Brass, Nickel Plated

: 1.5 Max.

: PTFE

: 500





Dimensions : Millimetres (Inches)

Part Number Table

Description	Part Number
BNC Straight Plug, Crimp, 50Ω, RG-58U	13-10-1 58U

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage resulting from any reliance on the Information or use of it (including liability resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com www.farnell.com www.newark.com





RoHS Compliant