

Stacking 4mm Banana Plug to Plug Safety Patchcord - 1mm² PVC



Specifications

Lead Length	: 500mm/19.7" 1m / 3.3ft 2m / 6.6ft
Connector Type A	: Stacking 4mm Shrouded Banana Plug
Connector Type B	: Stacking 4mm Shrouded Banana Plug
Voltage Rating	: CAT II 1000V
Current Rating	: 20A
Resistance	: 500mm: 15mΩ 1m: 25mΩ 2m: 45mΩ
Cable	: 1mm ² , PVC
Contact Material	: Brass and Beryllium Copper, Nickel Plated
Insulator Material	: Polypropylene
Insulator Colour	: Blue, Yellow, Black, Red and Green
Temperature	: -20°C to 80°C

Applications

General purpose electric and electronic testing, controlling and measuring.

Part Number Table

Description	Insulator Colour	Lead Length	Part Number
Test Lead, Stacking 4mm Shrouded Banana Plug to Plug, 1mm ² PVC, 1000V, 20A	Blue	500mm	72-14068
	Yellow		72-14070
	Black		72-14072
	Red		72-14074
	Green		72-14076
	Blue	1m	72-14048
	Yellow		72-14050

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk



Stacking 4mm Banana Plug to Plug Safety Patchcord - 1mm² PVC



Description	Insulator Colour	Lead Length	Part Number
Test Lead, Stacking 4mm Shrouded Banana Plug to Plug, 1mm ² PVC, 1000V, 20A	Black	1m	72-14052
	Red		72-14054
	Green		72-14056
	Blue	2m	72-14058
	Yellow		72-14060
	Black		72-14062
	Red		72-14064
	Green		72-14066

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell Limited 2016.

