

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1. Product Identifier

Product name	MC002955
Synonyms	SDS Code: 415-1L
Proper shipping name	FERRIC CHLORIDE SOLUTION
Other means of identification	Ferric Chloride

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	For etching printed circuits boards
Uses advised against	Not Applicable

1.3. Details of the supplier of the safety data sheet

Registered company name	Premier Farnell plc
Address	150 Armley Road, Leeds,
Address	LS12 2QQ
Telephone	+44 (0) 870 129 8608
Fax	-
Email	-

1.4. Emergency telephone number

Association / Organisation	Premier Farnell plc
Emergency telephone numbers	+44 1865 407333
Other emergency telephone	NA
numbers	

SECTION 2 HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008	H315 - Skin Corrosion/Irritation Category 2, H318 - Serious Eye Damage Category 1, H302 - Acute Toxicity (Oral) Category 4, H290 - Metal Corrosion
[CLP] ^[1]	Category 1
Legend:	1. Classified by Chemwatch; 2. Classification drawn from EC Directive 67/548/EEC - Annex I ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

2.2. Label elements

Hazard pictogram(s)	
SIGNAL WORD	DANGER

Hazard statement(s)

. ,	
H315	Causes skin irritation.
H318	Causes serious eye damage.
H302	Harmful if swallowed.
H290	May be corrosive to metals.





Supplementary statement(s)

Not Applicable

Precautionary statement(s) Prevention

P280	P280 Wear protective gloves/protective clothing/eye protection/face protection.	
P234	Keep only in original container.	
P270	Do not eat, drink or smoke when using this product.	

Precautionary statement(s) Response

···· · · · · · · · · · · · · · · · · ·		
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310	Immediately call a POISON CENTER/doctor/physician/first aider.	
P390	Absorb spillage to prevent material damage.	
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.	
P302+P352	IF ON SKIN: Wash with plenty of water and soap.	
P330	Rinse mouth.	
P332+P313	If skin irritation occurs: Get medical advice/attention.	
P362+P364	Take off contaminated clothing and wash it before reuse.	

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501

P501 Dispose of contents/container in accordance with local regulations.

2.3. Other hazards

Cumulative effects may result following exposure*.

May produce discomfort of the respiratory system*.

REACh - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.1.Substances

See 'Composition on ingredients' in Section 3.2

3.2.Mixtures

1.CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP]
1.7705-08-0 2.231-729-4 3.Not Available 4.01-2119497998-05-XXXX	38-40	ferric chloride	Metal Corrosion Category 1, Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 1B, Serious Eye Damage Category 1; H290, H302, H314 ^[1]
1.7758-94-3 2.231-843-4 3.Not Available 4.01-2119498060-41-XXXX	<1.5	ferrous chloride	Metal Corrosion Category 1, Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 1B, Serious Eye Damage Category 1; H290, H302, H314 ^[1]
1.7647-01-0 2.231-595-7 3.017-002-00-2 017-002-01-X 4.01-2119484862-27- XXXX 01-2120066883-46-XXXX	<0.8	<u>hydrochloric</u> <u>acid</u>	Skin Corrosion/Irritation Category 1B, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation); H314, H335 ^[3]
Legend:	1. Classified by Chemwatch; 2. Classification drawn from EC Directive 67/548/EEC - Annex I ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI 4. Classification drawn from C&L		





SECTION 4 FIRST AID MEASURES

4.1. Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested. Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to iron and its derivatives:

- Always treat symptoms rather than history.
- F In general, however, toxic doses exceed 20 mg/kg of ingested material (as elemental iron) with lethal doses exceeding 180 mg/kg.
- Control of iron stores depend on variation in absorption rather than excretion. Absorption occurs through aspiration, ingestion and burned skin.
- ▶ Hepatic damage may progress to failure with hypoprothrombinaemia and hypoglycaemia. Hepatorenal syndrome may occur.
- F Iron intoxication may also result in decreased cardiac output and increased cardiac pooling which subsequently produces hypotension.
- Serum iron should be analysed in symptomatic patients. Serum iron levels (2-4 hrs post-ingestion) greater that 100 ug/dL indicate poisoning with levels, in excess of 350 ug/dL, being potentially serious. Emesis or lavage (for obtunded patients with no gag reflex) are the usual means of decontamination.
- Activated charcoal does not effectively bind iron.
- Catharsis (using sodium sulfate or magnesium sulfate) may only be used if the patient already has diarrhoea.
 Deferoxamine is a specific chelator of ferric (3+) iron and is currently the antidote of choice. It should be administered parenterally. [Ellenhorn and Barceloux: Medical Toxicology]
- For acute or short term repeated exposures to strong acids:
- Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
- Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
- Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues.
- INGESTION:
- Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.
- Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- Charcoal has no place in acid management.
- Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN:

- Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.
- ► Deep second-degree burns may benefit from topical silver sulfadiazine.





EYE:

- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjuctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required.
- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
- Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 FIREFIGHTING MEASURES

5.1. Extinguishing media

- Water spray or fog.
- Foam.
- Dry chemical powder.BCF (where regulations permit).
- BCF (where regulations
 Carbon dioxide.
- Carbon die

5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility	None known,
File incompatibility	NOTE NIOWIL
5.3. Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use fire fighting procedures suitable for surrounding area. Do not approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	 Non combustible. Not considered to be a significant fire risk. Acids may react with metals to produce hydrogen, a highly flammable and explosive gas. Heating may cause expansion or decomposition leading to violent rupture of containers. May emit corrosive, poisonous fumes. May emit acrid smoke. Decomposition may produce toxic fumes of: hydrogen chloride

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

Minor Spills	 Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material. Check regularly for spills and leaks. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal. 						
	Chemical Class:acidic compounds, inorganic For release onto land: recommended sorbents listed in order of priority.						
	SORBENT TYPE	RANK	APPLICATION			COLLECTION	LIMITATIONS
	LAND SPILL - SMALL						
	foamed glass - pillows			1	throw	pitchfork	R, P, DGC, RT
	expanded mineral - part	ticulate		2	shove	l shovel	R, I, W, P, DGC
	foamed glass - particula	ato		2	shove	l shovel	R, W, P, DGC





LAND SPILL - MEDIUM expanded mineral -particulate 1 blower skiploader R, I, W, P, DGC foamed glass- particulate 2 blower skiploader R.W.P.DGC foamed glass - particulate З throw skiploader R, W, P, DGC Leaend Major Spills DGC: Not effective where ground cover is dense R; Not reusable I: Not incinerable P: Effectiveness reduced when rainy RT:Not effective where terrain is rugged SS: Not for use within environmentally sensitive sites W: Effectiveness reduced when windy Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control; R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. ۶ Consider evacuation (or protect in place). Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Neutralise/decontaminate residue (see Section 13 for specific agent). Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. If contamination of drains or waterways occurs, advise emergency services

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material. Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke.
	 Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Fire and explosion protection	See section 5
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

7.2. Conditions for safe storage, including any incompatibilities

DO NOT use aluminium or galvanised containers Check regularly for spills and leaks
 Lined metal can, lined metal pail/ can.
 Plastic pail.
 Polyliner drum.
 Packing as recommended by manufacturer.
 Check all containers are clearly labelled and free from leaks.
For low viscosity materials
Drums and jerricans must be of the non-removable head type.

Suitable container • Where a can is to be used as an inner package, the can must have a screwed enclosure.





	For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): Removable head packaging; Cans with friction closures and I low pressure tubes and cartridges may be used. Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.
Storage incompatibility	 Inorganic acids are generally soluble in water with the release of hydrogen ions. The resulting solutions have pH's of less than 7.0. Inorganic acids neutralise chemical bases (for example: amines and inorganic hydroxides) to form salts - neutralisation can generate dangerously large amounts of heat in small spaces. The dissolution of inorganic acids in water or the dilution of their concentrated solutions with additional water may generate significant heat. The addition of water to inorganic acids often generates sufficient heat in the small region of mixing to cause some of the water to boil explosively. The resulting "bumping" can spatter the acid. Inorganic acids react with active metals, including such structural metals as aluminum and iron, to release hydrogen, a flammable gas. Inorganic acids react with active metals, including such structural metals as aluminum and iron, to release hydrogen, a flammable gas. Inorganic acids react with active metals, and compounds to release gaseous hydrogen cyanide. Inorganic acids react at the polymerisation of certain classes of organic compounds. Inorganic acids generate flammable and/or toxic gases in contract with difficorahamates, isocyanates, mercaptans, nitrides, nitriles, sulfides, and strong reducing agents. Additional gas-generating reactions occur with sulfites, nitrites, thiosulfates (to give H2S and SO3), dithionites (SO2), and even carbonates. Acids often catalyse (increase the rate of) chemical reactions. Hydrogen chloride: reacts strongly with strong oxidisers (releasing chlorine gas), acetic anhydride, caesium cyanotridecahydrodecaborate(2-), ethylidene difluoride, hexalithium dislicide, sodium, silicon dioxide, tetraselenium tetranitride, and many organic materials is incompatible with alkaline materials, acetic anhydride, acetylides, aliphatic amines, alkylone oxides, duminium, alumin

7.3. Specific end use(s)

See section 1.2

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

DERIVED NO EFFECT LEVEL (DNEL)

Not Available

PREDICTED NO EFFECT LEVEL (PNEC)

Not Available

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA						
Source	Ingredient	Material name	TWA	STEL	Peak	Notes
UK Workplace Exposure Limits (WELs)	ferric chloride	Iron salts (as Fe)	1 mg/m3	2 mg/m3	Not Available	Not Available
UK Workplace Exposure Limits (WELs)	ferrous chloride	Iron salts (as Fe)	1 mg/m3	2 mg/m3	Not Available	Not Available
European Union (EU) First List of Indicative Occupational Exposure Limit Values (IOELVs) (English)	hydrochloric acid	Hydrogen chloride	8 mg/m3 / 5 ppm	15 mg/m3 / 10 ppm	Not Available	Not Available
UK Workplace Exposure Limits (WELs)	hydrochloric acid	Hydrogen chloride (gas and aerosol mists)	2 mg/m3 / 1 ppm	8 mg/m3 / 5 ppm	Not Available	Not Available
EU Consolidated List of Indicative Occupational Exposure Limit Values (IOELVs)	hydrochloric acid	Hydrogen Chloride	8 mg/m3 / 5 ppm	15 mg/m3 / 10 ppm	Not Available	Not Available





EMERGENCY LIMITS

Ingredient	Material name	т	EEL-1	TEEL-2	TEEL-3
ferric chloride	Ferric chloride	8.	7 mg/m3	30 mg/m3	180 mg/m3
ferrous chloride	Iron(II) chloride tetrahydrate	Iron(II) chloride tetrahydrate 11		120 mg/m3	710 mg/m3
ferrous chloride	Ferrous chloride	Ferrous chloride 6.		76 mg/m3	460 mg/m3
hydrochloric acid	Hydrogen chloride; (Hydrochloric acid)	N	ot Available	Not Available	Not Available
hydrochloric acid	Deuterochloric acid; (Deuterium chloride)	1.3	8 ppm	22 ppm	100 ppm
Ingredient	Original IDLH		Revised IDLH		
ferric chloride	Not Available		Not Available		
ferrous chloride	Not Available		Not Available		
hydrochloric acid	50 ppm		Not Available		

MATERIAL DATA

The recommended TLV is thought to reduce the likelihood of respiratory irritation and skin irritation from exposure to aerosols and mists of soluble iron salts.

for hydrogen chloride:

Odour Threshold Value: 0.262 ppm (detection), 10.06 ppm (recognition)

NOTE: Detector tubes for hydrochloric acid, measuring in excess of 1 ppm, are available commercially.

Hydrogen chloride is a strong irritant to the eyes, mucous membranes and skin. Chronic exposure produces a corrosive action on the teeth. Reports of respiratory irritation following short-term exposure at 5 ppm have lead to the recommended TLV-C. There is no indication that skin contact with hydrogen chloride elicits systemic poisoning and a skin designation has not been applied. Exposure of humans to hydrogen chloride at 50 to 100 ppm for 1 hour is reported to be barely tolerable; 35 ppm caused irritation of the throat on short exposure and 10 ppm was the maximal concentration for prolonged exposure. It has been stated that hydrogen chloride at concentrations of 5 ppm is immediately irritating.

Odour Safety Factor(OSF)

OSF=1.3 (HYDROGEN CHLORIDE)

Exposed individuals are NOT reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class C, D or E.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class OSF Description

A 550 Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV-TWA for example) is being reached, even when distracted by working activities

- B 26-550 As "A" for 50-90% of persons being distracted
- C 1-26 As "A" for less than 50% of persons being distracted
- D 0.18-1 10-50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
- E <0.18 As "D" for less than 10% of persons aware of being tested

8.2. Exposure controls

	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineerin highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a vent match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.	strategically "adds" and		
8.2.1. Appropriate engineering controls	Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.			
	Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank (in still air).	Air Speed: 0.25-0.5 m/s (50-100 f/min.)		
	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)		
	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)		





	Lower end of the range	Upper end of the range		
	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents		
	2: Contaminants of low toxicity or of nuisance value only. 2: Contaminants of high toxicity			
	3: Intermittent, low production.	3: High production, heavy use		
	4: Large hood or large air mass in motion 4: Small hood-local control only Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.			
8.2.2. Personal protection				
Eye and face protection	 where complete eye protection is needed such as when handling bulk pressure. Chemical goggles.whenever there is a danger of the material coming Full face shield (20 cm, 8 in minimum) may be required for supplement Alternatively a gas mask may replace splash goggles and face shield Contact lenses may pose a special hazard; soft contact lenses may al of lenses or restrictions on use, should be created for each workplace class of chemicals in use and an account of injury experience. Medica should be readily available. In the event of chemical exposure, begin e 	tary but never for primary protection of eyes; these afford face protection. s. bsorb and concentrate irritants. A written policy document, describing the wear or task. This should include a review of lens absorption and adsorption for the al and first-aid personnel should be trained in their removal and suitable equipm ye irrigation immediately and remove contact lens as soon as practicable. Lens hould be removed in a clean environment only after workers have washed hanc		
Skin protection	See Hand protection below			
Hands/feet protection	 Elbow length PVC gloves When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. 			
Body protection	See Other protection below			
Other protection	 Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Eyewash unit. Ensure there is ready access to a safety shower. 			
	F LINUIE INTERED TEAUY ACCESS TO A SAFETY SHOWER.			

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computergenerated selection: Ferric Chloride

Material	CPI
BUTYL	А
BUTYL/NEOPRENE	А
HYPALON	А
NEOPRENE	А
NEOPRENE/NATURAL	А
NITRILE	А
NITRILE+PVC	А
PE/EVAL/PE	А
PVC	А
SARANEX-23	А
VITON/NEOPRENE	А
NATURAL RUBBER	В

Respiratory protection

Type B-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	B-AUS P2	-	B-PAPR-AUS / Class 1 P2
up to 50 x ES	-	B-AUS / Class 1 P2	-
up to 100 x ES	-	B-2 P2	B-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

76b-p()

www.element14.com www.farnell.com www.newark.com



27/10/18 V1.0

multicomp

NATURAL+NEOPRENE

NAT+NEOPR+NITRILE

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion **NOTE**: As a series of factors will influence the actual performance of the glove, a final

selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as

"feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

в

С

8.2.3. Environmental exposure controls

See section 12

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties Appearance ORANGE-BROWN

Appearance	ORANGE-BROWN		
Physical state	Liquid	Relative density (Water = 1)	1.4
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	<1	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	106	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	1	VOC g/L	Not Available

9.2. Other information

Not Available

SECTION 10 STABILITY AND REACTIVITY

10.1.Reactivity	See section 7.2
10.2. Chemical stability	 Contact with alkaline material liberates heat Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3



multicomp

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

	Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.
Inhaled	Acidic corrosives produce respiratory tract irritation with coughing, choking and mucous membrane damage. Symptoms of exposure may include dizziness, headache, nausea and weakness. In more severe exposures, pulmonary oedema may be evident either immediately or after a latent period of 5-72 hours. Symptoms of pulmonary oedema include a tightness in the chest, dyspnoea, frothy sputum and cyanosis. Examination may reveal hypotension, a weak and rapid pulse and moist rates. Death, due to anoxia, may occur several hours after onset of the pulmonary oedema.
	Hydrogen chloride (HCI) vapour or fumes present a hazard from a single acute exposure. Exposures of 1300 to 2000 ppm have been lethal to humans in a few minutes. Inhalation of HCI may cause choking, coughing, burning sensation and may cause ulceration of the nose, throat and larynx. Fluid on the lungs followed by
	generalised lung damage may follow. Breathing of HCl vapour may aggravate asthma and inflammatory or fibrotic pulmonary disease. High concentrations cause necrosis of the tracheal and bronchial epithelium, pulmonary oedema, atelectasis and emphysema and damage to the pulmonary blood vessels and liver.
	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
Ingestion	Ingestion of acidic corrosives may produce circumoral burns with a distinct discolouration of the mucous membranes of the mouth, throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident. Oedema of the epiglottis may produce respiratory distress and possibly, asphyxia. Nausea, vomiting, diarrhoea and a pronounced thirst may occur. More severe exposures may produce a vomitus containing fresh or dark blood and large shreds of mucosa. Shock, with marked hypotension, weak and rapid pulse, shallow respiration and clammy skin may be symptomatic of the exposure. Circulatory collapse may, if left untreated, result in renal failure. Severe cases may show gastric and oesophageal perforation with peritonitis, fever and abdominal rigidity. Stricture of the oesophageal, gastric and pyloric sphincter may occur as within several weeks or may be delayed for years. Death may be rapid and often results from asphyxia, circulatory collapse or aspiration of even minute amounts. Delayed deaths may be due to peritonitis, severe nephritis or pneumonia. Coma and convulsions may be terminal.
	Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue.
Skin Contact	Skin contact is not thought to produce harmful health effects (as classified under EC Directives using animal models). Systemic harm, however, has been identified following exposure of animals by at least one other route and the material may still produce health damage following entry through wounds, lesions or abrasions. Good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation. Direct eye contact with acid corrosives may produce pain, lachrymation, photophobia and burns. Mild burns of the epithelia generally recover rapidly and completely. Severe burns produce long-lasting and possible irreversible damage. The appearance of the burn may not be apparent for several weeks after the initial contact. The cornea may ultimately become deeply vascularised and opaque resulting in blindness.
	Repeated or prolonged exposure to acids may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Gastrointestinal disturbances may also occur. Chronic exposures may result in dermatitis and/or conjunctivitis. The impact of inhaled acidic agents on the respiratory tract depends upon a number of interrelated factors. These include physicochemical characteristics, e.g., gas versus aerosol; particle size (small particles can penetrate deeper into the lung); water solubility (more soluble agents are more likely to be removed in the nose and mouth). Given the general lack of information on the particle size of aerosols involved in occupational exposures to acids, it is difficult to identify their principal deposition site within the respiratory tract. Acid mists containing particles with a diameter of up to a few micrometers will be deposited in both the upper and lower airways. They are irritating to muccus epithelia, they cause dental erosion, and they produce acute effects in the lungs (symptoms and changes in pulmonary function). Asthmatics appear to be at particular risk for pulmonary effects.
	Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems. Chronic minor exposure to hydrogen chloride (HCI) vapour or fume may cause discolouration or erosion of the teeth, bleeding of the nose and gums; and ulceration of the nasal mucous membranes. Repeated exposures of animals to concentrations of about 34 ppm HCI produced no immediate toxic effects.
	Workers exposed to hydrochloric acid suffered from gastritis and a number of cases of chronic bronchitis have also been reported. Repeated or prolonged exposure to dilute solutions of HCI may cause dermatitis. Chronic excessive iron exposure has been associated with haemosiderosis and consequent possible damage to the liver and pancreas. Haemosiderin is a golden-brown insoluble protein produced by phagocytic digestion of haematin (an iron-based pigment). Haemosiderin is found in most tissues, especially in the liver, in the form of granules. Other sites of haemosiderin deposition include the pancreas and skin. A related condition, haemochromatosis, which involves a disorder of metabolism of these deposits, may produce cirrhosis of the liver, diabetes, and bronze pigmentation of the skin - heart failure may eventually occur.
Chronic	Such exposure may also produce conjunctivitis, choroiditis, retinitis (both inflammatory conditions involving the eye) and siderosis of tissues if iron remains in these tissues. Siderosis is a form of pneumoconiosis produced by iron dusts. Siderosis also includes discoloration of organs, excess circulating iron and degeneration of the retina, lens and uvea as a result of the deposition of intraocular iron. Siderosis might also involve the lungs - involvement rarely develops before ten years of regular exposure. Often there is an accompanying inflammatory reaction of the bronchi. Permanent scarring of the lungs does not normally occur.





	High levels of iron may raise the risk of cancer. This concern stems from the highly reactive chemicals, called free radicals, which subsequently react with I genetic disposition prevents them from keeping tight control over iron (e.g. the Iron overload in men may lead to diabetes, arthritis, liver cancer, heart irregul [K. Schmidt, New Scientist, No. 1919 pp.11-12, 2nd April, 1994] Overexposure to respirable dust may cause coughing, wheezing, difficulty in t decreased vital lung capacity, chest infections Repeated exposures, in an occupational setting, to high levels of fine- divided lodgement of any inhaled dusts in the lung irrespective of the effect. This is pr (1/50,000 inch), are present. Lung shadows are seen in the X-ray. Symptoms on exertion (exertional dyspnea), increased chest expansion, weakness and v vital capacity decreases further and shortness of breath becomes more sever capacity, diminished oxygen uptake during exercise, emphysema and pneumo. Removing workers from possibility of further exposure to dust generally leads potential is high, periodic examinations with emphasis on lung dysfunctions sh Dust inhalation over an extended number of years may produce pneumoconic reaction in its presence. It is further classified as being of noncollagenous or	DNA. Cells may use with the inhe arities and proble- preathing and inr dusts may produ articularly true w of pneumoconic veight loss. As ti e. Other signs o thorax (air in lur to halting the pi bould be underta sis Pneumocol collagenous typ	be disrupted an prited disorder, h herms with other use a condition l hen a significar usis may include ne disease prog r symptoms incl ng cavity) as a ra rogress of the lu- ken nicosis is the acc es. Noncollager	ad may be become cancerous. People whose naemochromatosis) may be at increased risk. organs as iron builds up. ction. Chronic symptoms may include known as pneumoconiosis which is the th number of particles less than 0.5 microns a progressive dry cough, shortness of breath presses the cough produces a stringy mucous, lude altered breath sounds, diminished lung are complication. Ing abnormalities. Where worker-exposure umulation of dusts in the lungs and the tissue nous pneumoconiosis, the benign form, is			
	ΤΟΧΙCΙΤΥ	IRRITATION					
Ferric Chloride	Not Available	Not Available					
ferrous chloride	TOXICITY dermal (rat) LD50: >2000 mg/kg ^[1] Oral (rat) LD50: 29.74 mg/kg ^[1]	IRRITATION Not Available					
hydrochloric acid	TOXICITY Inhalation (rat) LC50: 780.108879 mg/l/1h ^[2] Oral (rat) LD50: 900 mg/kg ^[2]	N 5mg/30s - mild					
Legend:	 Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances 						
FERRIC CHLORIDE	The material may produce respiratory tract irritation. Symptoms of pulmonary irritation may include coughing, wheezing, laryngitis, shortness of breath, headache, nausea, and a burning sensation. Unlike most organs, the lung can respond to a chemical insult or a chemical agent, by first removing or neutralising the irritant and then repairing the damage (inflammation of the lungs may be a consequence). The repair process (which initially developed to protect mammalian lungs from foreign matter and antigens) may, however, cause further damage to the lungs (fibrosis for example) when activated by hazardous chemicals. Often, this results in an impairment of gas exchange, the primary function of the lungs. Therefore prolonged exposure to respiratory irritants may cause sustained breathing difficulties. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.						
HYDROCHLORIC ACID	No significant acute toxicological data identified in literature search. The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.						
Ferric Chloride & FERRIC CHLORIDE & FERROUS CHLORIDE & HYDROCHLORIC ACID	Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and outration of exposure to the irritating substance. Industrial bronchis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.						





Ferric Chloride & FERRIC CHLORIDE & FERROUS CHLORIDE & HYDROCHLORIC ACID	for acid mists, aerosols, vapours Data from assays for genotoxic activity in vitro suggest the the respiratory tract have not been examined in this respe- mists, just as mucous plays an important role in protectin induces genotoxic events in vivo in the respiratory system, under fasting or nocturnal conditions, and with the human Furthermore, exposures to low pH in vivo differ from expos conditions, so that perturbation of intracellular homeostasi	ct. Mucous secretion may protect the cell g the gastric epithelium from its auto-sec comparison should be made with the hu urinary bladder, in which the pH of urine sures <i>in vitro</i> in that, <i>in vivo</i> , only a portic	Is of the airways from direct exposure to inhaled acidic creted hydrochloric acid. In considering whether pH itself iman stomach, in which gastric juice may be at pH 1-2 can range from -5 to > 7 and normally averages 6.2. on of the cell surface is subjected to the adverse			
FERRIC CHLORIDE & HYDROCHLORIC ACID	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.					
Acute Toxicity	¥	Carcinogenicity	0			
Skin Irritation/Corrosion	×	Reproductivity	0			
Serious Eye Damage/Irritation	×	STOT - Single Exposure	0			
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0			
Mutagenicity	0	Aspiration Hazard	0			
		Legend: 🗙 – D	Data available but does not fill the criteria for classification			

Data available to make classification

🚫 – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity

Ferric Chloride	ENDPOINT		TEST DURATION (HR)		SPEC	CIES	VAL	UE	SO	URCE
r ente onionae	Not Available		Not Available		Not A	vailable	Not	Available	Not	Available
	ENDPOINT		TEST DURATION (HR)			SPECIES		VALUE	s	OURCE
	LC50		96			Fish		>=10mg/L	1	
ferric chloride	EC50		48			Crustacea		9.6mg/L	4	
	EC84		48			Crustacea		8.8mg/L	4	
	NOEC		504			Fish		0.32mg/L	4	
	ENDPOINT	TES	T DURATION (HR)	SPECIES		VALUE		SOURCE		
	LC50	96		Fish		4mg/L	4mg/L			
ferrous chloride	EC50	48		Crustacea		0.017mg/l	L	4		
	EC10	216		Algae or other aquatic plants		0.0009mg	/L	4		
	NOEC	71		Algae or other aquatic plants 0.0000			0.00005m	ıg/L	4	
	ENDPOINT		TEST DURATION (HR)			SPECIES		VALUE	S	OURCE
hydrochloric acid	LC50		96			Fish		282mg/L	4	
	NOEC		0.08		Fish			10mg/L	4	
Legend:			oxicity Data 2. Europe ECHA							
	. , ,		Data (Estimated) 4. US EPA, E Data 7. METI (Japan) - Biocor		'	,	5. ECETO	C Aquatic Haza	ard Assess	sment Data 6.

Harmful to aquatic organisms.

Ecotoxicity:

The tolerance of water organisms towards pH margin and variation is diverse. Recommended pH values for test species listed in OECD guidelines are between 6.0 and almost 9. Acute testing with fish showed 96h-LC50 at about pH 3.5

Although inorganic chloride ions are not normally considered toxic they can exist in effluents at acutely toxic levels (chloride >3000 mg/l). The resulting salinity can exceed the tolerances of most freshwater organisms.

Inorganic chlorine eventually finds its way into the aqueous compartment and as such is bioavailable. Incidental exposure to inorganic chloride may occur in occupational settings where chemicals management policies are improperly applied. The toxicity of chloride salts depends on the counter-ion (cation) present; that of chloride itself is unknown. Chloride toxicity has not been observed in humans except in the special case of impaired sodium chloride metabolism, e.g. in congestive heart failure. Healthy individuals can tolerate the intake of large quantities of chloride provided that there is a concomitant intake of fresh water.

Although excessive intake of drinking-water containing sodium chloride at concentrations above 2.5 g/litre has been reported to produce hypertension, this effect is believed to be related to the sodium ion concentration.





	ENDPOINT		TEST DURATION (HR)		SPECIES	VAL	UE	SC	URCE
	LC50		96		Fish	>=10mg/L		1	
ferric chloride	EC50		48		Crustacea	9.6m	ng/L	4	
	EC84		48		Crustacea	8.8m	ıg/L	4	
	NOEC		504		Fish	0.32	mg/L	4	
	ENDPOINT	TES	T DURATION (HR)	SPECIES			VALUE		SOURCE
	LC50	96		Fish			4mg/L		4
ferrous chloride	EC50	48 Crustacea		Crustacea			0.017mg/L		4
	EC10	216	P16 Algae or other aquatic plan		aquatic plants		0.0009mg/L		4
	NOEC	71	Algae or other aquatic plants		0.00005mg/L		4		
	ENDPOINT		TEST DURATION (HR)		SPECIES	VA	LUE	SO	URCE
hydrochloric acid	LC50		96		Fish	28	2mg/L	4	
	NOEC		0.08		Fish	10	mg/L	4	

(Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Harmful to aquatic organisms.

Ecotoxicity:

The tolerance of water organisms towards pH margin and variation is diverse. Recommended pH values for test species listed in OECD guidelines are between 6.0 and almost 9. Acute testing with fish showed 96h-LC50 at about pH 3.5

Although inorganic chloride ions are not normally considered toxic they can exist in effluents at acutely toxic levels (chloride >3000 mg/l). The resulting salinity can exceed the tolerances of most freshwater organisms.

Inorganic chlorine eventually finds its way into the aqueous compartment and as such is bioavailable. Incidental exposure to inorganic chloride may occur in occupational settings where chemicals management policies are improperly applied. The toxicity of chloride salts depends on the counter-ion (cation) present; that of chloride itself is unknown. Chloride toxicity has not been observed in humans except in the special case of impaired sodium chloride metabolism, e.g. in congestive heart failure. Healthy individuals can tolerate the intake of large quantities of chloride provided that there is a concomitant intake of fresh water.

Although excessive intake of drinking-water containing sodium chloride at concentrations above 2.5 g/litre has been reported to produce hypertension, this effect is believed to be related to the sodium ion concentration.

Chloride concentrations in excess of about 250 mg/litre can give rise to detectable taste in water, but the threshold depends upon the associated cations. Consumers can, however, become accustomed to concentrations in excess of 250 mg/litre. No health-based guideline value is proposed for chloride in drinking-water.

In humans, 88% of chloride is extracellular and contributes to the osmotic activity of body fluids. The electrolyte balance in the body is maintained by adjusting total dietary intake and by excretion via the kidneys and gastrointestinal tract. Chloride is almost completely absorbed in normal individuals, mostly from the proximal half of the small intestine. Normal fluid loss amounts to about 1.5-2 liters/day, together with about 4 g of chloride per day. Most (90 - 95%) is excreted in the urine, with minor amounts in faeces (4-8%) and sweat (2%).

Chloride increases the electrical conductivity of water and thus increases its corrosivity. In metal pipes, chloride reacts with metal ions to form soluble salts thus increasing levels of metals in drinking-water. In lead pipes, a protective oxide layer is built up, but chloride enhances galvanic corrosion. It can also increase the rate of pitting corrosion of metal pipes Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways

12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ferric chloride	HIGH	HIGH
hydrochloric acid	LOW	LOW

12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
ferric chloride	HIGH (BCF = 9622)
hydrochloric acid	LOW (LogKOW = 0.5392)

12.4. Mobility in soil

Ingredient	Mobility
ferric chloride	LOW (KOC = 35.04)
hydrochloric acid	LOW (KOC = 14.3)





12.5.Results of PBT and vPvB assessment

	Р	В	т
Relevant available data	Not Available	Not Available	Not Available
PBT Criteria fulfilled?	Not Available	Not Available	Not Available

12.6. Other adverse effects

No data available

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product / Packaging disposal	 Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sever may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material). Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed.
Waste treatment options	Not Available
Sewage disposal options	Not Available

SECTION 14 TRANSPORT INFORMATION

Labels Required



Land transport (ADR)

14.1.UN number	2582					
14.2.UN proper shipping name	FERRIC CHLORIDE SOLUTION					
14.3. Transport hazard class(es)	Class8SubriskNot Applicable					
14.4.Packing group	II					
14.5.Environmental hazard	Not Applicable					
14.6. Special precautions for user	Hazard identification (Kemler)80Classification codeC1Hazard Label8Special provisionsNot ApplicableLimited quantity5 L					





Air transport (ICAO-IATA / DGF	R)					
14.1. UN number	2582					
14.2. UN proper shipping name	Ferric chloride solution					
14.3. Transport hazard class(es)	ICAO/IATA Class8ICAO / IATA SubriskNot ApplicableERG Code8L					
14.4. Packing group	II					
14.5. Environmental hazard	Not Applicable					
14.6. Special precautions for user	Special provisions Cargo Only Packing Instructions Cargo Only Maximum Qty / Pack Passenger and Cargo Packing Instructions Passenger and Cargo Maximum Qty / Pack	A3 A803 856 60 L 852 5 L				
	Passenger and Cargo Limited Quantity Packing Instructions Passenger and Cargo Limited Maximum Qty / Pack					

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	2582
14.2. UN proper shipping name	FERRIC CHLORIDE SOLUTION
14.3. Transport hazard class(es)	IMDG Class8IMDG SubriskNot Applicable
14.4. Packing group	11
14.5. Environmental hazard	Not Applicable
14.6. Special precautions for user	EMS NumberF-A, S-BSpecial provisions223Limited Quantities5 L

Inland waterways transport (ADN)

14.1. UN number	2582
14.2. UN proper shipping name	FERRIC CHLORIDE SOLUTION
14.3. Transport hazard class(es)	8 Not Applicable
14.4. Packing group	Ш
14.5. Environmental hazard	Not Applicable
14.6. Special precautions for user	Classification code C1 Special provisions Not Applicab Limited quantity 5 L Equipment required PP, EP Fire cones number 0

14.7. Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable





SECTION 15 REGULATORY INFORMATION

FERRIC CHLORIDE(7705-08-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
European Customs Inventory of Chemical Substances ECICS (English)	UK Workplace Exposure Limits (WELs)
European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)	
FERROUS CHLORIDE(7758-94-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
European Customs Inventory of Chemical Substances ECICS (English)	UK Workplace Exposure Limits (WELs)
European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)	
HYDROCHLORIC ACID(7647-01-0) IS FOUND ON THE FOLLOWING REGULATORY LIST	S
EU Consolidated List of Indicative Occupational Exposure Limit Values (IOELVs)	European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and
European Customs Inventory of Chemical Substances ECICS (English)	Packaging of Substances and Mixtures - Annex VI
	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC
European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)	Monographs

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : 98/24/EC, 92/85/EC, 94/33/EC, 91/689/EEC, 1999/13/EC, Commission Regulation (EU) 2015/830, Regulation (EC) No 1272/2008 and their amendments

15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

ECHA SUMMARY

Ingredient	CAS number	Index No		ECHA Dossier	
ferric chloride	7705-08-0	Not Available		Not Available	
Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)		•	rams Signal Code(s)	Hazard Statement Code(s)
1	Acute Tox. 4; Skin Corr. 1B		GHS05	5; Dgr	H302; H314; H412
2	Met. Corr. 1; Acute Tox. 4; Skin Irrit. 2; Eye Darn. 1; Skin Sens. 1; Skin Corr. 1B; STOT SE 3; Acute Tox. 3; Aquatic Chronic 3; Eye Irrit. 2; Skin Corr. 1C		GHS08	5; Dgr; GHS09	H318; H317; H314; H412; H290; H335; H301

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

Ingredient	CAS number	Index No ECH		ECHA Dos	ECHA Dossier	
ferrous chloride	7758-94-3	Not Available		Not Availat	ble	
Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)		Pictograms Sig Code(s)	nal Word	Hazard Statement Code(s)	
1	Acute Tox. 4; Skin Corr. 1B		GHS05; Dgr		H302; H314	
2	Acute Tox. 4; Skin Corr. 1B; Skin Irrit. 2; Eye Dam. 1		GHS05; Dgr		H302; H314; H318; H312; H332	
1	Acute Tox. 4; Skin Irrit. 2; Eye Dam. 1; Acute Tox. 4; Eye Dam. 1; Aquatic Chronic 3		GHS05; Dgr		H302; H315; H318; H412	
2	Met. Corr. 1; Acute Tox. 4; Eye Dam. 1; Skin Sens. 1; Skin Irrit. 2; Aquatic Chronic 3; Eye Irrit. 2; Aquatic Chronic 2; Skin Corr. 1B		GHS05; Dgr; GH GHS08; GHS06	IS09;	H318; H317; H314; H335; H411; H312; H332; H301; H341	

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

Ingredient	CAS number	Index No			ECHA Dossier	
hydrochloric acid	7647-01-0	017-002-00-2 017-002-01-X	017-002-00-2 017-002-01-X No		ot Available	
Harmonisation (C&L Inventory)	Hazard Class and Category Code(s))	Pictograms Sigr Word Code(s)	nal	Hazard Statement Code(s)	
2	Gas (Liq.); Acute Tox. 4; Press. Gas (C	Skin Corr. 1A; Acute Tox. 3; Met. Corr. 1; STOT SE 3; Skin Corr. 1B; Eye Dam. 1; Press. Gas (Liq.); Acute Tox. 4; Press. Gas (Comp.); Acute Tox. 2; Eye Irrit. 2; Skin Irrit. 2; Skin Corr. 1C; Flam. Liq. 2; Resp. Sens. 1; Repr. 1B; STOT SE 1; STOT RE 1; Aquatic Acute 1; Repr. 1A; STOT RE 2		S08;	H314; H290; H335; H318; H280; H311; H330; H225; H334; H360; H370; H372; H301	
2	Skin Corr. 1A; Acute Tox. 3; Met. Corr. 1; STOT SE 3; Skin Corr. 1B; Eye Dam. 1; Press. Gas (Liq.); Acute Tox. 4; Press. Gas (Comp.); Acute Tox. 2; Eye Irrit. 2; Skin Irrit. 2; Skin Corr. 1C; Flam. Liq. 2; Resp. Sens. 1; Repr. 1B; STOT SE 1; STOT RE 1; Aquatic Acute 1; Repr. 1A; STOT RE 2		GHS05; GHS06; GHS04; Dgr; GH GHS02	S08;	H314; H290; H335; H318; H280; H311; H330; H225; H334; H360; H370; H372; H301	





1	Skin Corr. 1B; STOT SE 3	GHS05; Dgr	H314; H335
2	Skin Corr. 1B; STOT SE 3	GHS05; Dgr	H314; H335
	Met. Corr. 1; Skin Corr. 1B; STOT SE 3	GHS05; Dgr	H290; H314; H335
2	Met. Corr. 1; Skin Corr. 1B; STOT SE 3	GHS05; Dgr	H290; H314; H335
	Press. Gas (Comp.); Skin Corr. 1A; Acute Tox. 3	GHS05; GHS04; GHS06; Dgr	H280; H314; H331
	Press. Gas (Comp.); Skin Corr. 1A; Acute Tox. 3; Skin Corr. 1B; Eye Dam. 1; STOT SE 3	GHS05; GHS04; GHS06; Dgr	H280; H314; H331; H335

National Inventory	Status
Australia - AICS	Υ
Canada - DSL	Υ
Canada - NDSL	N (ferric chloride; hydrochloric acid; ferrous chloride)
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	Υ
Japan - ENCS	Υ
Korea - KECI	Υ
New Zealand - NZIoC	Υ
Philippines - PICCS	Υ
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Full text Risk and Hazard codes

H225	Highly flammable liquid and vapour.	
H280	Contains gas under pressure; may explode if heated.	
H301	Toxic if swallowed.	
H311	Toxic in contact with skin.	
H312	Harmful in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H317	May cause an allergic skin reaction.	
H330	Fatal if inhaled.	
H331	Toxic if inhaled.	
H332	Harmful if inhaled.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H335	May cause respiratory irritation.	
H341	Suspected of causing genetic defects.	
H360	May damage fertility or the unborn child.	
H370	Causes damage to organs.	
H372	Causes damage to organs through prolonged or repeated exposure.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	

Other information

Ingredients with multiple cas numbers		
Name	CAS No	
ferric chloride	7705-08-0, 58694-80-7, 121714-78-1	
ferrous chloride	7758-94-3, 13478-10-9, 16399-77-2	





Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chernwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered. For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average PC – STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit, IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL: No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LODE Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

> Part Number MC002955

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility of rits accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell Limited 2016.

