

DAC101

Digital Audio Converter

This 2-way Digital SPDIF (Coaxial/ Toslink) Audio Converter can let the users connect SPDIF audio signal input through either Coaxial cable or Toslink cable. It passes the signal (as is) to both its coaxial and Toslink output ports. With its built-in amplification feature, it can also serve as a repeater extending the signal transferring distance.

KEY FEATURES

Supports two-way conversion: Coaxial to Toslink or Toslink to Coaxial.

Audio format support: LPCM2.0/DTS/Dolby-AC3

Supports amplification of SPDIF audio and extends the transferring distance, through coaxial or Toslink cables.

Select one input from Coaxial or Toslink input ports, and send SPDIF audio signal to both Coaxial and Toslink output ports simultaneously.

Compact size and easy to install.



SPECIFICATIONS

Support audio format	LPCM2.0/DTS/Dolby-AC3
Input ports	1 x Coaxial RCA Jack and 1 x Toslink port
Output ports	1 x Coaxial RCA Jack and 1 x Toslink port
Power Supply	USB Power Cable
Operating Temperature range	0 to +40
Operating Humidity range	5% to 90 % RH(No condensation)
Operating Temperature range	(0 to 40)
Inputs	1 Toslink Optical Audio 1 Coaxial Audio
Outputs	1 Toslink Optical Audio 1 Coaxial Audio
Support	LPCM2.0/DTS/Dolby-AC3
Dimensions	49 x 50 x 20 (mm)

