

Waterproof Voltage Tester



**RoHS
Compliant**

Features

- AC / DC Voltage Measurement (Including Three-Phase AC)
- Phase Position Indication of Three-phase AC
- Continuity Test & Single Probe Measurement (Checks Neutral or Live Wire)
- Waterproof (IP65)
- Auto Ranging
- Low Battery Indication

General Characteristics

Power : 1.5V Batteries (R03) × 2
 Colour : Orange and Grey
 Weight : 210g
 Dimension : 275mm × 51mm × 30mm
 Standard Accessories : Batteries & User Manual

Electrical Specifications

Parameters	Range	Best Accuracy
LED AC/DC Voltage Indication	12V	0 ~ 10V
	24V	17V ±2V
	50V	35V ±6V
	120V	80V ±20V
	230V	165V ±20V
	400V	300V ±30V
	690V	510V ±40V
Phase Rotation Test	Operating Voltage: 0V ~ 690V	
	Frequency: 50Hz ~ 60Hz	
Single Lead (L2) Voltage Detection	Operating Voltage: 100V ~ 690V	
	Frequency: 50Hz ~ 400Hz	
Continuity Test	Resistance: 0 ~ 400kΩ	
	Beeper and LED Light Indicator	
Polarity Detection	Positive & Negative	



Part Number Table

Description	Part Number
Waterproof Voltage Tester, AC/DC	72-9395

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell Limited 2016.

