

BS4737 Type 3 Alarm Cable-TC Unscreened PVC



Product Type:

Alarm Cable

Application:

Manufactured to BS4737, this cable is designed as an internal cable used for the inter-connection of alarm equipment. It can also be used for other low voltage inter-connecting wiring

Standards:

BS4737-3.30: 2015 Type 3 RoHS2.0 Compliant

Construction:

Conductor	Stranded Tinned copper
	Nominal 7/0.17mm.
Insulation	PVC
Core colours	4 Core: Red, Blue, Yellow, Black
	6 Core: Green, White, Red, Blue, Yellow, Black
	8 Core: Brown, Green, White, Red, Blue, Yellow, Black, Orange
Rip cord	Colour: Yellow
Sheath:	PVC
Colour:	White, other colours available
Outer Diameter:	4 Core: 3.5± 0.2mm
	6 Core: 4.0± 0.2mm
	8 Core: 4.2± 0.2mm

Electrical Characteristics:

Rated Voltage: 50V

Rated Conductor Temperature: 70 °C

Max. Conductor DC Resistance: ≤155Ω/km @ 20°C

Datasheet Ref: BS4737 Type 3 Alarm Cable TC Unscreened

Issue: 1

Page 1 of 1

This data sheet remains the property and copyright of C & C Cables Limited and the information contained within this document must not be copied or reproduced without the permission, in writing, from C & C Cables Limited. All information contained within this data sheet was correct at time of creation but may be subject to change without prior notice.