

Surface-Mount Dual-Band Metal Antenna 2400-2500 MHz / 5150-5875 MHz



Laird's D-Puck antenna is a cost-effective, small-scale metal antenna designed for maximum durability. This vertically polarized antenna has a gain of >3 dBi at 2.4-2.5 GHz and >4 dBi at 5.15-5.875 GHz. The D-Puck is specifically designed to be embedded inside devices for aesthetically pleasing integration with high durability.

FEATURES AND BENEFITS

- Tape and reel packaging for high volume pick-and-place manufacturing
- RoHS Compliant (2011/65/EU)
- Planar Inverted F Antenna (PIFA) requires ground plane to radiate efficiently

ELECTRICAL SPECIFICATIONS				
Operating Frequency (MHz)	2400-2500	5150-5875		
Gain (dBi)	>3	>4		
Impedance (ohms)	50			
VSWR	<2.5:1			
Polarization	Vertical			

MECHANICAL SPECIFICATIONS		
Dimensions (diameter x height) – mm (in.)	16.0 x 16.0 x 6.0 (0.63 x 0.63 x 0.24)	
Weight – g (oz.)	2 (0.07)	
Carrier Material	Black color, resins	


ENVIRONMENTAL SPECIFICATIONS		
Hazardous Materials Compliance	RoHS compliant (2011/65/EU)	

CONFIGURATION

PART NUMBER	DESCRIPTION	CONNECTOR	PACKAGING
MAF94192	D-Puck Antenna	Surface Mount	Tape and Reel
CAF94377	D-Puck Antenna on Evaluation Board	SMA-Female Panel	Single




MECHANICAL DRAWING




RADIATION PATTERNS

Azimuth (Total Gain)



Elevation (Total Gain)



Americas: +1.847 839.6925 IAS-AmericasSales@lairdtech.com Europe: +44.1628.858941 IAS-EUSales@lairdtech.com Asia: IAS-AsiaSales@lairdtech.com Middle East and Africa: +44.1628.858941 IAS-MEAUSales@lairdtech.com www.lairdtech.com



Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.



© Copyright 2018 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.