

Solder Sleeve Wire Splices Heat Shrink Tube White, 50 pcs




Features

- Shrinkage ratio:2:1
- Waterproof for wiring splices
- Easy control soldering process
- Transparent sleeve provides precise inspection


Specifications

Operating Temperature	: -55°C to +105°C
Min. Shrink Temperature	: 60°C
Min. Fully Recovery Temperature	: 110°C
Starting Temperature of Solder Melt	: 115°C


Diagram



Colour	Cable Size		As Supplied (mm)		Solder Sleeve (mm)			Length (L) mm
	AWG	mm ²	I.D. (a)	Average W.T. (b)	I.D. (c)	Average W.T. (d)	Height (e)	
White	26-24	0.25-0.34	3 ±0.1	0.25 ±0.05	1.8 ±0.1	0.35 ±0.05	1.7 ±0.1	25 ±0.5



1. Heat shrinkable tubing
2. Low temperature solder sleeve
3. Waterproof hot melt adhesive



Material: Tin
Waterproof for wiring splices;
Material: Adhesive
Material: PE

Part Number Table

Description	Part Number
Solder Sleeve Wire Splices Heat Shrink Tube (1.8 × 25mm), White, 50 pcs	21-19560

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. DURATOOL is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands
Farnell.com/exclusive-brands
Element14.com/exclusive-brands

