

Cisco SFP-GE-S Compatible SFP Fiber Module - 1000BASE-SX

Product ID: SFPGESST



The SFPGESST is a Cisco SFP-GE-S compatible fiber transceiver module that has been designed, programmed and tested to work with Cisco® brand switches and routers. It delivers dependable 1 GbE connectivity over fiber cable, for 1000BASE-SX compliant networks, with a maximum distance of up to 550 m (1804 ft).

Technical Specifications:

• Wavelength: 850nm

• Maximum Data Transfer Rate: 1.25 Gbps

Type: Multi Mode Fiber

• Connection Type: LC Connector

• Maximum Transfer Distance: 550 m (1804 ft)

MTBF: 3,381,761 hours

• Power Consumption: Less than 1 Watt

Digital Diagnostics Monitoring (DDM): Yes



Data Sheet

This SFP fiber module is hot-swappable, making upgrades and replacements seamless by minimizing network disruptions.

StarTech.com SFPs

All StarTech.com SFP & SFP+ transceiver modules are backed by a lifetime warranty and free lifetime multilingual technical support. StarTech.com offers a wide variety of SFP modules and direct-attach SFP cables, providing the convenience and reliability you need to ensure dependable network performance.



Data Sheet

Certifications, Reports and Compatibility













Applications

- Replacing defective or damaged SFP modules in Cisco switches and routers
- Expand your network to remote segments

Features

- 100% compatibility with Cisco SFP-GE-S guaranteed
- StarTech.com SFP modules are backed by a lifetime warranty
- Meets or exceeds OEM specifications and Multi-Source Agreement (MSA) industry standards
- Low power consumption of less than 1 W
- Hot-swappable with fiber-optic modules



Data Sheet

	Warranty	Lifetime
Hardware	Compatible Brand	Cisco
	Industry Standards	IEEE 802.3z 1000BASE-SX
	WDM	No
Performance	Compatible Networks	1000 Mbps (1 Gbps)
	DDM	Yes
	Fiber Operating Mode	Half/Full-Duplex
	Max Transfer Distance	550 m (1804 ft)
	Maximum Data Transfer Rate	1.25 Gbps
	MTBF	3,381,761 hours
	Туре	Multi Mode
	Wavelength	850nm
Connector(s)	Local Unit Connectors	1 - Fiber Optic LC Duplex Female
Special Notes / Requirements	Note	For use in Gigabit fiber networking equipment and media converters
	System and Cable Requirements	MSA or Cisco compliant SFP port
Power	Power Consumption (In Watts)	< 1 W
Environmental	Humidity	30~70% RH
	Operating Temperature	0°C to 70°C (32°F to 158°F)
	Storage Temperature	-40°C to 85°C (-40°F to 85°F)
Physical Characteristics	Product Height	10 mm [0.4 in]
	Product Length	60 mm [2.4 in]
	Product Weight	17 g [0.6 oz]
	Product Width	12 mm [0.5 in]
Packaging Information	Shipping (Package) Weight	95 g [3.4 oz]
What's in the Box	Included in Package	1 - 1.25 Gbps Multimode LC SFP

Product appearance and specifications are subject to change without notice.