

Section 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product name: MC001838 HARDENER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Premier Farnell

150 Armley Road

Leeds

LS12 2QQ

Tel: +44 (0) 870 129 8608

Email: information@premierfarnell.com**1.4. Emergency telephone number**

Emergency tel: +44 (0) 870 202530

Section 2: Hazards identification**2.1. Classification of the substance or mixture**

Classification under CLP: Skin Corr. 1B: H314; Skin Sens. 1A: H317; Aquatic Chronic 2: H411

Most important adverse effects: Causes severe skin burns and eye damage. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS05: Corrosion

GHS07: Exclamation mark

GHS09: Environmental



Signal words: Danger

Precautionary statements: P260: Do not breathe mist.

P264: Wash hands, forearms and face thoroughly after handling.

SAFETY DATA SHEET

MC001838 HARDENER

Page: 2

- P272: Contaminated work clothing should not be allowed out of the workplace.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
- P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
- P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P310: Immediately call doctor.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P302+P352: IF ON SKIN: Wash with plenty of water.
- P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
- P362+P364: Take off contaminated clothing and wash it before reuse.
- P405: Store locked up.
- P501: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Haz. ingredients (label): STYRENATED PHENOL; REACTION MASS OF TRIENTINE AND TRIENTINE, MONO- AND DI-PROPOXYLATED; N-(BETA-AMINOETHYL)PIPERAZINE

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

STYRENATED PHENOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
262-975-0	61788-44-1	-	Skin Irrit. 2: H315; Skin Sens. 1A: H317; Aquatic Chronic 1: H410	10-30%

REACTION MASS OF TRIENTINE AND TRIENTINE, MONO- AND DI-PROPOXYLATED

942-835-1	-	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1B: H317; Aquatic Chronic 2: H411	10-30%
-----------	---	---	---	--------

N-(BETA-AMINOETHYL)PIPERAZINE - REACH registered number(s): 01-2119471486-30-XXXX

205-411-0	140-31-8	-	Skin Corr. 1B: H314; Acute Tox. 3: H311; Acute Tox. 4: H302; Skin Sens. 1: H317; Aquatic Chronic 3: H412	10-30%
-----------	----------	---	--	--------

[cont...]

SAFETY DATA SHEET

MC001838 HARDENER

Page: 3

FUMED SILICA

614-122-2	67762-90-7	Substance with a Community workplace exposure limit.	-	1-10%
-----------	------------	--	---	-------

Section 4: First aid measures

4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.
- Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
- Ingestion:** Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** Severe burns may occur. Blistering may occur. Progressive ulceration will occur if treatment is not immediate. May cause sensitisation in susceptible individuals.
- Eye contact:** Corneal burns may occur. May cause permanent damage. There may be severe pain. The eyes may water profusely.
- Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
- Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Show this safety data sheet to the doctor in attendance. A decontamination shower should be available on the premises. Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

[cont...]

SAFETY DATA SHEET

MC001838 HARDENER

Page: 4

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS.
Mark out the contaminated area with signs and prevent access to unauthorised personnel. If outside keep bystanders upwind and away from danger point.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is exhaust ventilation of the area. Avoid direct contact with the substance.
Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): PC1: Adhesives, sealants.

Section 8: Exposure controls/personal protection

8.1. Control parameters

[cont...]

SAFETY DATA SHEET

MC001838 HARDENER

Page: 5

Hazardous ingredients:

FUMED SILICA

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	6 mg/m ³	2.4 mg/m ³	-	-

DNEL/PNEC Values

Hazardous ingredients:

STYRENATED PHENOL

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	4.11 mg/m ³	Workers	Systemic
DNEL	Dermal	2.92 mg/kg	Workers	Systemic
PNEC	Fresh water	11.5 ug/L	-	-
PNEC	Marine water	1.15 ug/L	-	-
PNEC	Microorganisms in sewage treatment	10 mg/L	-	-
PNEC	Fresh water sediments	1.564 mg/kg	-	-
PNEC	Marine sediments	156.4 ug/kg	-	-
PNEC	Soil (agricultural)	305.2 ug/kg	-	-

N-(BETA-AMINOETHYL)PIPERAZINE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation (repeated dose)	3.6 mg/m ³	Workers	Systemic
DNEL	Inhalation	21.4 mg/m ³	Workers	Systemic
DNEL	Dermal (repeated dose)	3.3 mg/kg	Workers	Systemic
DNEL	Dermal	20 mg/kg	Workers	Systemic
DNEL	Dermal	6 ug/cm ²	Workers	Local
PNEC	Fresh water	58 ug/L	-	-
PNEC	Marine water	6 ug/L	-	-
PNEC	Microorganisms in sewage treatment	250 mg/L	-	-
PNEC	Fresh water sediments	215 mg/kg	-	-
PNEC	Marine sediments	21.5 mg/kg	-	-
PNEC	Soil (agricultural)	42.9 mg/kg	-	-

8.2. Exposure controls

Engineering measures: Ensure there is exhaust ventilation of the area.

Respiratory protection: When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection: Impermeable gloves.

[cont...]

SAFETY DATA SHEET

MC001838 HARDENER

Page: 6

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Black

Odour: Characteristic odour

Viscosity: Non-viscous

Relative density: 1.73

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

STYRENATED PHENOL

ORAL	RAT	LD50	>2000	mg/kg
------	-----	------	-------	-------

[cont...]

SAFETY DATA SHEET

MC001838 HARDENER

Page: 7

REACTION MASS OF TRIENTINE AND TRIENTINE, MONO- AND DI-PROPOXYLATED

DERMAL	RAT	LD50	2,150	mg/kg
ORAL	RAT	LD50	4,500	mg/kg

N-(BETA-AMINOETHYL)PIPERAZINE

DERMAL	RBT	LD50	886	mg/kg
ORAL	RAT	LD50	1000	mg/kg

FUMED SILICA

DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Severe burns may occur. Blistering may occur. Progressive ulceration will occur if treatment is not immediate. May cause sensitisation in susceptible individuals.

Eye contact: Corneal burns may occur. May cause permanent damage. There may be severe pain. The eyes may water profusely.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

STYRENATED PHENOL

ALGAE	72H ErC50	>10	mg/l
DAPHNIA	48H EC50	4.6	mg/l
FISH	96H LC50	5.6	mg/l

[cont...]

SAFETY DATA SHEET

MC001838 HARDENER

Page: 8

REACTION MASS OF TRIENTINE AND TRIENTINE, MONO- AND DI-PROPOXYLATED

ALGAE	72H ErC50	4.1	mg/l
Daphnia magna	48H EC50	48	mg/l
RAINBOW TROUT (<i>Oncorhynchus mykiss</i>)	96H LC50	4.1	mg/l

N-(BETA-AMINOETHYL)PIPERAZINE

Daphnia magna	48H EC50	58	mg/l
FISH	96H LC50	2190	mg/l
GREEN ALGA (<i>Selenastrum capricornutum</i>)	72H ErC50	>1000	mg/l

FUMED SILICA

ZEBRAFISH (<i>Brachydanio rerio</i>)	96H LC50	>10000	mg/l
--	----------	--------	------

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 08 04 09

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN2735

[cont...]

SAFETY DATA SHEET

MC001838 HARDENER

Page: 9

14.2. UN proper shipping name

Shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.
(N-(BETA-AMINOETHYL)PIPERAZINE)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: Marine pollutant(s) - STYRENATED PHENOL ; REACTION MASS OF TRIENTINE AND TRIENTINE,
MONO- AND DI-PROPOXYLATED ;

Tunnel code: E

Transport category: 2

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk: Not applicable.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture
by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No
2015/830.

This safety data sheet is prepared in accordance with Commission Regulation (EC) No
1272/2008.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.
H311: Toxic in contact with skin.
H314: Causes severe skin burns and eye damage.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.

[cont...]

SAFETY DATA SHEET

MC001838 HARDENER

Page: 10

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

Section 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product name: MC001838 RESIN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Premier Farnell

150 Armley Road

Leeds

LS12 2QQ

Tel: +44 (0) 870 129 8608

Email: information@premierfarnell.com**1.4. Emergency telephone number**

Emergency tel: +44 (0) 870 202530

Section 2: Hazards identification**2.1. Classification of the substance or mixture**

Classification under CLP: Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411

Most important adverse effects: Causes serious eye damage. Causes skin irritation. May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H318: Causes serious eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS05: Corrosion

GHS07: Exclamation mark

GHS09: Environmental



Signal words: Danger

Precautionary statements: P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

P273: Avoid release to the environment.

SAFETY DATA SHEET

MC001838 RESIN

Page: 2

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call POISON CENTER/doctor.

P302+P352: IF ON SKIN: Wash with plenty of water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BISPHENOL A EPOXY RESIN (MW <700) - REACH registered number(s): 01-2119456619-26-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-033-5	25068-38-6	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1: H317; Aquatic Chronic 2: H411	30-50%

1,4-BUTANEDIOL DIGLYCIDYL ETHER - REACH registered number(s): 01-2119494060-45-XXXX

219-371-7	2425-79-8	-	Acute Tox. 4: H302+H312+H332; Skin Sens. 1: H317; Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Irrit. 2: H315	1-10%
-----------	-----------	---	--	-------

AMORPHOUS SILICA - REACH registered number(s): 01-2119379499-16-XXXX

231-545-4	7631-86-9	Substance with a Community workplace exposure limit.	-	1-10%
-----------	-----------	---	---	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. If irritation occurs or persists, seek medical attention. Transfer to hospital if necessary.

Eye contact: Bathe the eye with running water for 15 minutes. Immediately remove contact lenses if present. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact. May cause sensitisation in susceptible individuals.

[cont...]

SAFETY DATA SHEET

MC001838 RESIN

Page: 3

Eye contact: There may be severe pain. The eyes may water profusely. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises. Show this safety data sheet to the doctor in attendance.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Ensure adequate ventilation.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is exhaust ventilation of the area. Avoid the formation or spread of mists in the air.

[cont...]

SAFETY DATA SHEET

MC001838 RESIN

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): PC1: Adhesives, sealants.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

AMORPHOUS SILICA

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	6 mg/m ³	-	2.4 mg/m ³	-

DNEL/PNEC Values

Hazardous ingredients:

BISPHENOL A EPOXY RESIN (MW <700)

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	12.25 mg/m ³	Workers	Systemic
DNEL	Dermal	8.33 mg/kg	Workers	Systemic
PNEC	Fresh water	6 ug/L	-	-
PNEC	Marine water	600 ng/L	-	-
PNEC	Microorganisms in sewage treatment	10 mg/L	-	-
PNEC	Fresh water sediments	996 ug/kg	-	-
PNEC	Marine sediments	99.6 ug/kg	-	-
PNEC	Soil (agricultural)	196 ug/kg	-	-
PNEC	Food chain	11 mg/kg	-	-

1,4-BUTANEDIOL DIGLYCIDYL ETHER

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	4.7 mg/m ³	Workers	Systemic
DNEL	Dermal	6.66 mg/kg	Workers	Systemic
PNEC	Fresh water	24 ug/L	-	-
PNEC	Marine water	2.4 ug/L	-	-

[cont...]

SAFETY DATA SHEET

MC001838 RESIN

Page: 5

PNEC	Microorganisms in sewage treatment	100 mg/L	-	-
PNEC	Fresh water sediments	84 ug/kg	-	-
PNEC	Marine sediments	8.4 ug/kg	-	-
PNEC	Soil (agricultural)	2.7 ug/kg	-	-
PNEC	Food chain	28 ug/kg	-	-

8.2. Exposure controls

Engineering measures: Ensure there is exhaust ventilation of the area.

Respiratory protection: When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Suitable respiratory protection should be worn when there is inadequate ventilation.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Beige

Odour: Perceptible odour

Relative density: 1.690

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong acids. Strong bases. Strong oxidising agents.

[cont...]

SAFETY DATA SHEET

MC001838 RESIN

Page: 6

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BISPHENOL A EPOXY RESIN (MW <700)

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

1,4-BUTANEDIOL DIGLYCIDYL ETHER

DERMAL	RAT	LD50	>2150	mg/kg
ORAL	RAT	LD50	1118	mg/kg
VAPOURS	RAT	4H LC50	>11.3	mg/l

AMORPHOUS SILICA

DERMAL	RBT	LD50	>5000	mg/kg
DUST/MIST	RAT	4H LC50	>2.08	mg/l
ORAL	RAT	LD50	>3300	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact. May cause sensitisation in susceptible individuals.

Eye contact: There may be severe pain. The eyes may water profusely. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Section 12: Ecological information

12.1. Toxicity

[cont...]

SAFETY DATA SHEET

MC001838 RESIN

Page: 7

Hazardous ingredients:

BISPHENOL A EPOXY RESIN (MW <700)

Daphnia magna	48H EC50	1.7	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H ErC50	2.4	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	1.2	mg/l

1,4-BUTANEDIOL DIGLYCIDYL ETHER

Scenedesmus Subspicatus	72H ErC50	110	mg/l
ZEBRAFISH (Brachydanio rerio)	96H LC50	24	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 08 04 09

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN (MW <700))

[cont...]

SAFETY DATA SHEET

MC001838 RESIN

Page: 8

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302+H312+H332: Harmful if swallowed, in contact with skin or if inhaled

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.