# **SAFETY DATA SHEET**



Circuitworks® Rubber Keypad Repair Part A

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Circuitworks® Rubber Keypad Repair Part A

Product code : CW2605 (PartA)

Product description : Adhesive.

Product type : Paste.

Other means of : CW2605 Part A

identification

1.2 Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

# 1.3 Details of the supplier of the safety data sheet

Manufacturer Chemtronics 8125 Cobb Center Drive Kennesaw, GA 30152

Tel. 770-424-4888 or toll free 800-645-5244

Distributor

Importer
ITW Contamination Control BV
Saffierlaan 5
VZ-2132 Hoofddorp
The Netherlands

Email: info@itw-cc.com

Tel: +31 88 1307 400 FAX: +31 88 1307 499

e-mail address of person : info@itw-cc.com

responsible for this SDS

# **National contact**

ITW Contamination Control BV Saffierlaan 5 VZ-2132 Hoofddorp The Netherlands

Email: info@itw-cc.com

Tel: +31 88 1307 400 FAX: +31 88 1307 499

# 1.4 Emergency telephone number

**National advisory body/Poison Centre** 

**Telephone number**: EMERGENCY HEALTH INFORMATION:

Chemtrec - 1-800-424-9300 or collect 703-527-3887

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Supplier** 

Telephone number : Chemtronics Product Information: 800-TECH-401 (800-832-4401)

Chemtronics Customer Service: 800-645-5244

Chemtrec 800-424-9300

Hours of operation : Chemtrec - 1-800-424-9300 or collect 703-527-3887

For emergency responders

24/7

Information limitations : EMERGENCY HEALTH INFORMATION:

**EMERGENCY SPILL INFORMATION:** 

Transport information

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

**Product definition**: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown

toxicity

: 70 percent of the mixture consists of component(s) of unknown toxicity

Ingredients of unknown

ecotoxicity

: Contains 33 % of components with unknown hazards to the aquatic environment

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

# 2.2 Label elements

Hazard pictograms





Signal word : Warning

**Hazard statements**: Causes serious eye irritation.

Very toxic to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention**: Wear eye or face protection. Avoid release to the environment. Wash hands

thoroughly after handling.

Response : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.FOR INDUSTRIAL USE ONLY

Supplemental label

elements

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Circuitworks® Rubber Keypad Repair Part A

# **SECTION 2: Hazards identification**

Special packaging requirements

Containers to be fitted with child-resistant

: Not applicable.

fastenings

Tactile warning of danger : Not applicable.

2.3 Other hazards

Other hazards which do not result in classification

: None known.

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
silver	EC: 231-131-3 CAS: 7440-22-4	≥50 - ≤75	Aquatic Acute 1, H400 (M=1000) Aquatic Chronic 1, H410 (M=1000)	[1] [2]
2-butoxyethyl acetate	EC: 203-933-3 CAS: 112-07-2 Index: 607-038-00-2	≥10 - ≤21	Acute Tox. 4, H312 Acute Tox. 4, H332 Eye Irrit. 2, H319	[1] [2]
2-(2-ethoxyethoxy)ethyl acetate	EC: 203-940-1 CAS: 112-15-2	≥10 - ≤25	Eye Irrit. 2, H319	[1]
Carbon black	EC: 215-609-9 CAS: 1333-86-4	≤10	Aquatic Chronic 3, H412	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Circuitworks® Rubber Keypad Repair Part A

# **SECTION 4: First aid measures**

#### Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### **Protection of first-aiders**

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

# 4.2 Most important symptoms and effects, both acute and delayed

# **Over-exposure signs/symptoms**

**Eye contact** : Adverse symptoms may include the following:

irritation

**Inhalation** : Adverse symptoms may include the following:

headache dizziness/vertigo nausea or vomiting

**Skin contact**: Adverse symptoms may include the following:

irritation

**Ingestion**: Adverse symptoms may include the following:

nausea or vomiting stomach pains

# 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

: None known.

# 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: Combustible liquid.

**Hazardous combustion** 

products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide metal oxide/oxides

# 5.3 Advice for firefighters

**Special protective actions** 

for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

# SECTION 5: Firefighting measures

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**6.2 Environmental** precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

# 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

# 6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

# SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

# 7.1 Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Circuitworks® Rubber Keypad Repair Part A

# **SECTION 7: Handling and storage**

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

# Seveso Directive - Reporting thresholds (in tonnes)

#### **Danger criteria**

	Notification and MAPP threshold	Safety report threshold
E1: Hazardous to the aquatic environment - Acute 1 or Chronic 1	100	200

# 7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

# **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

# 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
silver	EU OEL (Europe, 12/2009). Notes: list of indicative
	occupational exposure limit values
	TWA: 0.1 mg/m³ 8 hours.
2-butoxyethyl acetate	EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list
, ,	of indicative occupational exposure limit values
	STEL: 333 mg/m³ 15 minutes.
	STEL: 50 ppm 15 minutes.
	TWA: 133 mg/m³ 8 hours.
	TWA: 20 ppm 8 hours.

# Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

No DNELs/DMELs available.

#### **PNECs**

No PNECs available

#### 8.2 Exposure controls

# **SECTION 8: Exposure controls/personal protection**

Appropriate engineering

: Use only with adequate ventilation.

controls

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash

**Skin protection** 

**Hand protection** 

: Use chemical-resistant, impervious gloves.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection Environmental exposure** 

controls

: A respirator is not needed under normal and intended conditions of product use.

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process

equipment will be necessary to reduce emissions to acceptable levels.

# SECTION 9: Physical and chemical properties

# 9.1 Information on basic physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Colour : Grey. [Dark] **Odour** : Fruity.

: Not available. **Odour threshold** : Not available. pН **Melting point/freezing point** : Not available.

Initial boiling point and

boiling range

: 204°C

: Closed cup: 61 to 93.3°C Flash point **Evaporation rate** : <1 (butyl acetate = 1)

Flammability (solid, gas) Not available. Upper/lower flammability or Lower: 0.5% explosive limits Upper: 19.4%

: 0.13 kPa [room temperature] Vapour pressure

Vapour density : >1 [Air = 1] **Relative density** 2.6

: Not available. Solubility(ies)

Partition coefficient: n-octanol/ : Not available.

water

**Auto-ignition temperature** : Not available. **Decomposition temperature** : Not available. **Viscosity** : Not available.

Circuitworks® Rubber Keypad Repair Part A

# **SECTION 9: Physical and chemical properties**

**Explosive properties**: Not considered to be a product presenting a risk of explosion.

Oxidising properties : Not available.

9.2 Other information

Solubility in water : Not available.

No additional information.

# **SECTION 10: Stability and reactivity**

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Avoid release to the

environment.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

# **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
2-butoxyethyl acetate	LD50 Dermal LD50 Oral	Rabbit Rat	1500 mg/kg 2400 mg/kg	-
2-(2-ethoxyethoxy)ethyl acetate	LD50 Oral	Rat	11 g/kg	-
Carbon black	LD50 Oral	Rat	>15400 mg/kg	-

Conclusion/Summary : Not available.

#### **Acute toxicity estimates**

Route	ATE value
	3950 mg/kg 28.97 mg/l

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-butoxyethyl acetate	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				milligrams	
	Skin - Mild irritant	Rabbit	-	500	-
				milligrams	
2-(2-ethoxyethoxy)ethyl	Eyes - Moderate irritant	Rabbit	-	500	-
acetate				milligrams	
	Skin - Mild irritant	Rabbit	-	500	-
				milligrams	

**Conclusion/Summary** 

: Not available.

**Sensitisation** 

**Conclusion/Summary**: Not available.

**Mutagenicity** 

Circuitworks® Rubber Keypad Repair Part A

# SECTION 11: Toxicological information

: Not available. **Conclusion/Summary** 

Carcinogenicity

**Conclusion/Summary** : Not available.

Reproductive toxicity

**Conclusion/Summary** : Not available.

**Teratogenicity** 

**Conclusion/Summary** : Not available. Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

**Aspiration hazard** 

Not available.

Information on likely routes : Not available.

of exposure

Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : Harmful by inhalation. MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN

IRRITATION. Danger of very serious irreversible effects.

Skin contact : May cause skin irritation. May be harmful if absorbed through skin or if swallowed.

Ingestion : Harmful if swallowed. Possible risk of irreversible effects. May cause damage to

organs following a single exposure if swallowed. Do not ingest. If swallowed then

seek immediate medical assistance.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

irritation

Inhalation Adverse symptoms may include the following:

> headache dizziness/vertigo nausea or vomiting

Skin contact : Adverse symptoms may include the following:

irritation

Ingestion : Adverse symptoms may include the following:

> nausea or vomiting stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

**Potential immediate** : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

Circuitworks® Rubber Keypad Repair Part A

# **SECTION 11: Toxicological information**

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Other information : Not available.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
silver	Acute EC50 1.4 μg/l Marine water Acute EC50 0.24 μg/l Fresh water	Algae - Chroomonas sp. Daphnia - Daphnia magna	4 days 48 hours
	Acute LC50 4500 ppb Fresh water	Crustaceans - Gammarus pseudolimnaeus	48 hours
	Acute LC50 2.13 to 2.93 μg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 5 mg/l Marine water	Algae - Glenodinium halli	72 hours
Carbon black	Acute EC50 37.563 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours

**Conclusion/Summary**: Not available.

#### 12.2 Persistence and degradability

**Conclusion/Summary**: Not available.

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
silver	-	70	low
2-butoxyethyl acetate	1.51	-	low
2-(2-ethoxyethoxy)ethyl acetate	0.76	3.2	low

# 12.4 Mobility in soil

Soil/water partition

coefficient (Koc)

: Not available.

**Mobility** : Not available.

# 12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

# 13.1 Waste treatment methods

**Product** 

# SECTION 13: Disposal considerations

**Methods of disposal** 

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** 

**Methods of disposal** 

: The classification of the product may meet the criteria for a hazardous waste.

**Packaging** 

: The generation of waste should be avoided or minimised wherever possible. Waste

packaging should be recycled. Incineration or landfill should only be considered

when recycling is not feasible.

**Special precautions** 

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	Adhesives Sealants	Adhesives Sealants	Adhesives Sealants	Adhesives Sealants
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No
Additional information	-	-	-	-

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code : Not available.

# SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

Circuitworks® Rubber Keypad Repair Part A

# **SECTION 15: Regulatory information**

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

**Europe inventory**: Not determined.

Industrial emissions : Listed

(integrated pollution prevention and control) -

**Air** 

Industrial emissions : Listed

(integrated pollution prevention and control) -

Water

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

**Seveso Directive** 

This product is controlled under the Seveso Directive.

#### **Danger criteria**

# **Category**

E1: Hazardous to the aquatic environment - Acute 1 or Chronic 1

#### **International regulations**

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

# **International lists**

**National inventory** 

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

China : All components are listed or exempted.

Japan : Japan inventory (ENCS): Not determined.

Japan inventory (ISHL): Not determined.

Malaysia : Not determined.

New Zealand : All components are listed or exempted.

Philippines : All components are listed or exempted.

Republic of Korea : All components are listed or exempted.

Taiwan : All components are listed or exempted.

Circuitworks® Rubber Keypad Repair Part A

# SECTION 15: Regulatory information

: Not determined. **Turkey** 

**United States** : All components are listed or exempted.

15.2 Chemical safety

This product contains substances for which Chemical Safety Assessments are still assessment

required.

# **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

**Abbreviations and** 

: ATE = Acute Toxicity Estimate

acronyms

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

# Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Eye Irrit. 2, H319	Calculation method
Aquatic Acute 1, H400	Calculation method
Aquatic Chronic 1, H410	Calculation method

#### Full text of abbreviated H statements

H312 H319	Harmful in contact with skin. Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

# Full text of classifications [CLP/GHS]

Acute Tox. 4, H312	ACUTE TOXICITY (dermal) - Category 4
Acute Tox. 4, H332	ACUTE TOXICITY (inhalation) - Category 4
Aquatic Acute 1, H400	ACUTE AQUATIC HAZARD - Category 1
Aquatic Chronic 1, H410	LONG-TERM AQUATIC HAZARD - Category 1
Aquatic Chronic 3, H412	LONG-TERM AQUATIC HAZARD - Category 3
Eye Irrit. 2, H319	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2

**Date of printing** 5/30/2017 Date of issue/ Date of : 5/30/2017

revision

: No previous validation

**Version** 

# Notice to reader

Date of previous issue

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

# **SAFETY DATA SHEET**



Circuitworks® Rubber Keypad Repair Part B

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Circuitworks® Rubber Keypad Repair Part B

Product code : CW2605 (Part B)

Product description : Adhesive.
Product type : Liquid.

Other means of : CW2605 Part B

identification

1.2 Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

# 1.3 Details of the supplier of the safety data sheet

Manufacturer Chemtronics 8125 Cobb Center Drive Kennesaw, GA 30152

Tel. 770-424-4888 or toll free 800-645-5244

Distributor

Importer
ITW Contamination Control BV
Saffierlaan 5
VZ-2132 Hoofddorp
The Netherlands

Email: info@itw-cc.com

Tel: +31 88 1307 400 FAX: +31 88 1307 499

e-mail address of person : info@itw-cc.com

responsible for this SDS

#### **National contact**

ITW Contamination Control BV Saffierlaan 5 VZ-2132 Hoofddorp The Netherlands

Email: info@itw-cc.com

Tel: +31 88 1307 400 FAX: +31 88 1307 499

# 1.4 Emergency telephone number

**National advisory body/Poison Centre** 

**Telephone number**: EMERGENCY HEALTH INFORMATION:

Chemtrec - 1-800-424-9300 or collect 703-527-3887

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Supplier** 

Telephone number : Chemtronics Product Information: 800-TECH-401 (800-832-4401)

Chemtronics Customer Service: 800-645-5244

Chemtrec 800-424-9300

Hours of operation : Chemtrec - 1-800-424-9300 or collect 703-527-3887

For emergency responders

24/7

Information limitations : EMERGENCY HEALTH INFORMATION:

**EMERGENCY SPILL INFORMATION:** 

Transport information

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

**Product definition**: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Irrit. 2, H319

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown :

ecotoxicity

: Contains 67.5 % of components with unknown hazards to the aquatic environment

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms



Signal word : Warning

**Hazard statements**: Causes serious eye irritation.

**Precautionary statements** 

**Prevention**: Wear eye or face protection. Wash hands thoroughly after handling.

Response : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Storage : Not applicable.

Disposal : Not applicable.

Supplemental label

elements

: FOR INDUSTRIAL USE ONLY

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

I

# **Special packaging requirements**

Containers to be fitted

with child-resistant

: Not applicable.

: Not applicable.

fastenings

Tactile warning of danger : Not applicable.

# **SECTION 2: Hazards identification**

#### 2.3 Other hazards

Other hazards which do not result in classification

: None known.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
2-(2-ethoxyethoxy)ethyl acetate	EC: 203-940-1 CAS: 112-15-2	≥50 - ≤75	Eye Irrit. 2, H319	[1]
methanol	EC: 200-659-6 CAS: 67-56-1 Index: 603-001-00-X	<3	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 1, H370	[1] [2]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

**Eye contact** 

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

# SECTION 4: First aid measures

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### 4.2 Most important symptoms and effects, both acute and delayed

**Over-exposure signs/symptoms** 

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : Adverse symptoms may include the following:

> dizziness/vertigo drowsiness/fatigue nausea or vomiting muscle weakness headache

unconsciousness respiratory tract irritation

Skin contact : Adverse symptoms may include the following:

irritation

Ingestion : Adverse symptoms may include the following:

> nausea or vomiting stomach pains

#### 4.3 Indication of any immediate medical attention and special treatment needed

: Treat symptomatically. Contact poison treatment specialist immediately if large Notes to physician

quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

# SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

: Decomposition products may include the following materials:

**Unsuitable extinguishing** 

media

: None known.

#### 5.2 Special hazards arising from the substance or mixture

**Hazards from the** substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous combustion** 

carbon dioxide

products carbon monoxide

# 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# SECTION 6: Accidental release measures

# 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

# 6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

# 7.1 Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers.

Seveso Directive - Reporting thresholds (in tonnes)

Named substances

Circuitworks® Rubber Keypad Repair Part B

# SECTION 7: Handling and storage

	Notification and MAPP threshold	Safety report threshold
Methanol	500	5000

# 7.3 Specific end use(s)

Recommendations : Not available. **Industrial sector specific** : Not available. solutions

# **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

# 8.1 Control parameters

# **Occupational exposure limits**

Product/ingredient name	Exposure limit values
	EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values  TWA: 260 mg/m³ 8 hours.  TWA: 200 ppm 8 hours.

# procedures

**Recommended monitoring**: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

No DNELs/DMELs available.

## **PNECs**

No PNECs available

# 8.2 Exposure controls

**Appropriate engineering** controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

# Individual protection measures

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

# **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

# **Skin protection**

Circuitworks® Rubber Keypad Repair Part B

# **SECTION 8: Exposure controls/personal protection**

**Hand protection** 

: Use chemical-resistant, impervious gloves.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

**Appearance** 

Physical state : Liquid.

Colour : Amber.

Odour : Ethereal.

Odour threshold : Not available.

PH : Not available.

Melting point/freezing point : Not available.

Initial boiling point and

boiling range

: 64°C

Flash point : Closed cup: 100°C Evaporation rate : <1 (butyl acetate = 1)

Flammability (solid, gas)
Upper/lower flammability or

**explosive limits** 

Not available.Not available.

Vapour pressure : 12.8 kPa [room temperature]

Vapour density : Not available.

Relative density : 1

Solubility(ies) : Not available.

Partition coefficient: n-octanol/ : Not available.

water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.Viscosity: Not available.

**Explosive properties**: Not considered to be a product presenting a risk of explosion.

Oxidising properties : Not available.

9.2 Other information

Solubility in water : Not available.

No additional information.

# **SECTION 10: Stability and reactivity**

10.1 Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

: The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

: Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. open flames, sparks and static discharge Avoid all possible sources of ignition (spark or flame).

10.5 Incompatible materials

: Reactive or incompatible with the following materials: Strong oxidizing materials acids alkalis amines water

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

# **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
2-(2-ethoxyethoxy)ethyl acetate	LD50 Oral	Rat	11 g/kg	-
methanol	LC50 Inhalation Gas. LC50 Inhalation Gas.	Rat Rat		1 hours 4 hours
	LD50 Dermal LD50 Oral	Rabbit Rat	15800 mg/kg 5600 mg/kg	-

**Conclusion/Summary** 

: Not available.

# **Acute toxicity estimates**

Route	ATE value
	5000 mg/kg 15000 mg/kg 150 mg/l

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-(2-ethoxyethoxy)ethyl acetate	Eyes - Moderate irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
methanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	40 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-

**Conclusion/Summary** 

**Sensitisation** 

: Not available.

**Conclusion/Summary** 

: Not available.

**Mutagenicity** 

**Conclusion/Summary** 

: Not available.

**Carcinogenicity** 

**Conclusion/Summary**: Not available.

Circuitworks® Rubber Keypad Repair Part B

# SECTION 11: Toxicological information

**Reproductive toxicity** 

**Conclusion/Summary** 

: Not available.

**Teratogenicity** 

**Conclusion/Summary** : Not available. Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
methanol	Category 1	Not determined	Not determined

# Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

**Information on likely routes**: Not available.

of exposure

# Potential acute health effects

Eye contact : Irritating to eyes. Risk of serious damage to eyes. Causes burns.

: Harmful by inhalation. MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN Inhalation

IRRITATION.

Skin contact : MAY CAUSE EYE AND SKIN IRRITATION.

Ingestion : Harmful if swallowed. May be fatal if swallowed. Do not ingest. If swallowed then

seek immediate medical assistance.

# Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

> pain or irritation watering redness

Inhalation : Adverse symptoms may include the following:

dizziness/vertigo drowsiness/fatigue nausea or vomiting muscle weakness headache

unconsciousness

respiratory tract irritation

Skin contact : Adverse symptoms may include the following:

irritation

Ingestion : Adverse symptoms may include the following:

nausea or vomiting stomach pains

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

**Potential immediate** 

effects

: Not available.

Potential delayed effects

: Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Circuitworks® Rubber Keypad Repair Part B

# **SECTION 11: Toxicological information**

# Potential chronic health effects

Not available.

**Conclusion/Summary**: Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Other information : Not available.

# **SECTION 12: Ecological information**

# 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
methanol	Acute LC50 2500000 µg/l Marine water	Algae - Ulva pertusa Crustaceans - Crangon crangon - Adult	96 hours 48 hours
	water Acute LC50 290 mg/l Fresh water	Daphnia - Daphnia magna - Neonate Fish - Danio rerio - Egg Algae - Ulva pertusa	48 hours 96 hours 96 hours

**Conclusion/Summary**: Not available.

# 12.2 Persistence and degradability

**Conclusion/Summary**: Not available.

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-(2-ethoxyethoxy)ethyl acetate	0.76	3.2	low
methanol	-0.77	<10	low

# 12.4 Mobility in soil

Soil/water partition

coefficient (Koc)

: Not available.

Mobility : Not available.

#### 12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

# **Product**

Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste Packaging** 

.The classification of the product may meet the criteria for a hazardous waste.

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** 

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	Adhesives Sealants	Adhesives Sealants	Adhesives Sealants	Adhesives Sealants
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code : Not available.

Circuitworks® Rubber Keypad Repair Part B

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

# EU Regulation (EC) No. 1907/2006 (REACH)

# **Annex XIV - List of substances subject to authorisation**

#### **Annex XIV**

None of the components are listed.

# Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

**Europe inventory** : All components are listed or exempted.

Ozone depleting substances (1005/2009/EU)

Not listed.

# Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

# **Seveso Directive**

This product is controlled under the Seveso Directive.

#### **Named substances**

#### **Name**

Methanol

# **International regulations**

# Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

# Montreal Protocol (Annexes A, B, C, E)

Not listed.

# **Stockholm Convention on Persistent Organic Pollutants**

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

# **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

# **International lists**

#### **National inventory**

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

China : All components are listed or exempted.

Japan : Japan inventory (ENCS): All components are listed or exempted.

Japan inventory (ISHL): Not determined.

Malaysia : Not determined.

New Zealand : All components are listed or exempted.
Philippines : All components are listed or exempted.
Republic of Korea : All components are listed or exempted.

Circuitworks® Rubber Keypad Repair Part B

# **SECTION 15: Regulatory information**

**Taiwan** : All components are listed or exempted.

Turkey : Not determined.

**United States** : All components are listed or exempted.

15.2 Chemical safety

assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

# **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate

acronyms

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

# Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Eye Irrit. 2, H319	Calculation method

# Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H370	Causes damage to organs.

# Full text of classifications [CLP/GHS]

Acute Tox. 3, H301	ACUTE TOXICITY (oral) - Category 3
Acute Tox. 3, H311	ACUTE TOXICITY (dermal) - Category 3
Acute Tox. 3, H331	ACUTE TOXICITY (inhalation) - Category 3
Eye Irrit. 2, H319	SERIOUS EYE DAMAGE/EYÉ IRRITATION - Category 2
Flam. Liq. 2, H225	FLAMMABLE LIQUIDS - Category 2
Skin Irrit. 2, H315	SKIN CORROSION/IRRITATION - Category 2
STOT SE 1, H370	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE -
	Category 1

Date of printing : 5/30/2017

Date of issue/ Date of : 5/30/2017

revision

Date of previous issue : No previous validation

Version : 1

# **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.