

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: MP000426 HARDENER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Premier Farnell

150 Armley Road

Leeds

LS12 2QQ

United Kingdom

Tel: + 44 (0) 870 129 8608

Fax: + 44 (0) 870 129 8611

Email: information@premierfarnell.com

1.4. Emergency telephone number

Emergency tel: + 44 (0) 870 120 2530

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314; Acute Tox. 3: H311+H331; Acute Tox. 4: H302; Skin Sens. 1: H317; Aquatic Chronic 2: H411

Most important adverse effects: Causes severe skin burns and eye damage. Toxic in contact with skin or if inhaled
Harmful if swallowed. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

H311+H331: Toxic in contact with skin or if inhaled

H302: Harmful if swallowed.

H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS05: Corrosion

GHS06: Skull and crossbones

Safety Data Sheet

multicomp^{PRO}

GHS07: Exclamation mark

GHS09: Environmental



Signal words: Danger

Precautionary statements: P260: Do not breathe mist.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.
Rinse skin with water .

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call doctor.

P273: Avoid release to the environment.

Haz. ingredients (label): 2,2'-DIMETHYL-4,4'-METHYLENEBIS(CYCLOHEXYLAMINE); ISOPHORONE DIAMINE

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

2,2'-DIMETHYL-4,4'-METHYLENEBIS(CYCLOHEXYLAMINE) - REACH registered number(s): 01-2119497829-12-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
229-962-1	6864-37-5	-	Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 4: H302; Skin Corr. 1A: H314; Aquatic Chronic 2: H411	30-50%

ISOPHORONE DIAMINE - REACH registered number(s): 01-2119514687-32-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
220-666-8	2855-13-2	-	Skin Corr. 1B: H314; Acute Tox. 4: H302+H312; Skin Sens. 1: H317; Aquatic Chronic 3: H412	30-50%

Section 4: First aid measures

4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.
Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.
- Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Severe burns may occur. Blistering may occur. Progressive ulceration will occur if treatment is not immediate. May cause sensitisation in susceptible individuals.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Show this safety data sheet to the doctor in attendance. A decontamination shower should be available on the premises. Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is exhaust ventilation of the area. Avoid direct contact with the substance. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): PC1: Adhesives, sealants.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

Hazardous ingredients:

2,2'-DIMETHYL-4,4'-METHYLENEBIS(CYCLOHEXYLAMINE)

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	600 ug/m3	Workers	Systemic
DNEL	Inhalation	960 ug/m3	Workers	Local
DNEL	Dermal	60 ug/kg	Workers	Systemic
PNEC	Fresh water	400 ug/L	-	-
PNEC	Marine water	40 ug/L	-	-
PNEC	Microorganisms in sewage treatment	1.6 mg/L	-	-
PNEC	Fresh water sediments	17.4 mg/kg	-	-

PNEC	Marine sediments	1.74 mg/kg	-	-
PNEC	Soil (agricultural)	4.56 mg/kg	-	-
PNEC	Food chain	556 ug/kg	-	-

ISOPHORONE DIAMINE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	0.073 mg/m3	Workers	Local
PNEC	Fresh water	60 ug/L	-	-
PNEC	Marine water	6 ug/L	-	-
PNEC	Microorganisms in sewage treatment	3.18 mg/L	-	-
PNEC	Fresh water sediments	5.784 mg/kg	-	-
PNEC	Marine sediments	578 ug/kg	-	-
PNEC	Soil (agricultural)	1.121 mg/kg	-	-

8.2. Exposure controls

Engineering measures: Ensure there is exhaust ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be used in handling.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Pale yellow

Odour: Irritating odour

Solubility in water: Partially soluble

Viscosity: Non-viscous

Flash point°C: 122

Relative density: 0.96

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2,2'-DIMETHYL-4,4'-METHYLENEBIS(CYCLOHEXYLAMINE)

DERMAL	RBT	LD50	>200	mg/kg
DUST/MIST	RAT	4H LC50	0.4	mg/l
ORAL	RAT	LD50	>320	mg/kg

ISOPHORONE DIAMINE

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	1030	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	ING	Hazardous: calculated
Acute toxicity (ac. tox. 3)	INH DRM	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Severe burns may occur. Blistering may occur. Progressive ulceration will occur if treatment is not immediate. May cause sensitisation in susceptible individuals.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

2,2'-DIMETHYL-4,4'-METHYLENEBIS(CYCLOHEXYLAMINE)

Daphnia magna	48H EC50	4.57	mg/l
FISH	96H LC50	22.4	mg/l
Scenedesmus Subspicatus	72H ErC50	>5	mg/l

ISOPHORONE DIAMINE

Daphnia magna	48H EC50	23	mg/l
FISH	96H LC50	110	mg/l
Scenedesmus Subspicatus	72H ErC50	>50	mg/l

12.2. Persistence and degradability

Persistence and degradability: Not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Partially soluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN2922

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, TOXIC, N.O.S.
(2,2'-DIMETHYL-4,4'-METHYLENEBIS(CYCLOHEXYLAMINE); ISOPHORONE DIAMINE)

14.3. Transport hazard class(es)

Transport class: 8 (6.1)

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: Marine pollutant(s) - 2,2'-DIMETHYL-4,4'-METHYLENEBIS(CYCLOHEXYLAMINE) ; ;
ISOPHORONE DIAMINE ;

Tunnel code: E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H302+H312: Harmful if swallowed or in contact with skin

H311: Toxic in contact with skin.

H311+H331: Toxic in contact with skin or if inhaled

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H331: Toxic if inhaled.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: MP000426 RESIN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Premier Farnell

150 Armley Road

Leeds

LS12 2QQ

United Kingdom

Tel: + 44 (0) 870 129 8608

Fax: + 44 (0) 870 129 8611

Email: information@premierfarnell.com

1.4. Emergency telephone number

Emergency tel: + 44 (0) 870 120 2530

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Sens. 1: H317; Aquatic Chronic 2: H411; Eye Dam. 1: H318; Skin Irrit. 2: H315; -: EUH205

Most important adverse effects: Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects. Contains epoxy constituents. May produce an allergic reaction.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H318: Causes serious eye damage.

H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

EUH205: Contains epoxy constituents. May produce an allergic reaction.

Hazard pictograms: GHS05: Corrosion

GHS07: Exclamation mark

GHS09: Environmental

Safety Data Sheet



Signal words: Danger

- Precautionary statements:** P261: Avoid breathing mist.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310: Immediately call POISON CENTER/doctor.
P302+P352: IF ON SKIN: Wash with plenty of water.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

Haz. ingredients (label): EPOXY PHENOL NOVALAC; 1,4-BUTANEDIOL DIGLYCIDYL ETHER; BISPHENOL A EPOXY RESIN (MW <700); C13-C15 ALKYL GLYCIDYL ETHERS

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

EPOXY PHENOL NOVALAC - REACH registered number(s): 01-2119454392-40-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
608-164-0	28064-14-4	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1: H317; Aquatic Chronic 2: H411	50-70%

1,4-BUTANEDIOL DIGLYCIDYL ETHER - REACH registered number(s): 01-2119494060-45-XXXX

219-371-7	2425-79-8	-	Acute Tox. 4: H302+H312+H332; Skin Sens. 1: H317; Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Irrit. 2: H315	10-30%
-----------	-----------	---	--	--------

BISPHENOL A EPOXY RESIN (MW <700) - REACH registered number(s): 01-2119456619-26-XXXX

500-033-5	25068-38-6	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1: H317; Aquatic Chronic 2: H411	<1%
-----------	------------	---	--	-----

C13-C15 ALKYL GLYCIDYL ETHERS

268-358-2	68081-84-5	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1: H317; Aquatic Chronic 2: H411	<1%
-----------	------------	---	--	-----

Section 4: First aid measures

4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. If irritation occurs or persists, seek medical attention. Transfer to hospital if necessary.
- Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
- Ingestion:** Wash out mouth with water. Do not induce vomiting. Consult a doctor.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** There may be irritation and redness at the site of contact. May cause sensitisation in susceptible individuals.
- Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.
- Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.
- Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.
- Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

- Immediate / special treatment:** Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

- Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

- Exposure hazards:** In combustion emits toxic fumes.

5.3. Advice for fire-fighters

- Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- Personal precautions:** Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): PC1: Adhesives, sealants.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

Hazardous ingredients:

1,4-BUTANEDIOL DIGLYCIDYL ETHER

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	4.7 mg/m ³	Workers	Systemic
DNEL	Dermal	6.66 mg/kg	Workers	Systemic
PNEC	Fresh water	24 ug/L	-	-
PNEC	Marine water	2.4 ug/L	-	-
PNEC	Microorganisms in sewage treatment	100 mg/L	-	-
PNEC	Fresh water sediments	84 ug/kg	-	-
PNEC	Marine sediments	8.4 ug/kg	-	-
PNEC	Soil (agricultural)	2.7 ug/kg	-	-
PNEC	Food chain	28 ug/kg	-	-

BISPHENOL A EPOXY RESIN (MW <700)

Type	Exposure	Value	Population	Effect
------	----------	-------	------------	--------

DNEL	Inhalation	12.25 mg/m ³	Workers	Systemic
DNEL	Dermal	8.33 mg/kg	Workers	Systemic
PNEC	Fresh water	6 ug/L	-	-
PNEC	Marine water	600 ng/L	-	-
PNEC	Microorganisms in sewage treatment	10 mg/L	-	-
PNEC	Fresh water sediments	996 ug/kg	-	-
PNEC	Marine sediments	99.6 ug/kg	-	-
PNEC	Soil (agricultural)	196 ug/kg	-	-
PNEC	Food chain	11 mg/kg	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Black

Odour: Aromatic

Viscosity: Viscous

Flash point°C: >93

Relative density: 1.17

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

EPOXY PHENOL NOVALAC

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

1,4-BUTANEDIOL DIGLYCIDYL ETHER

DERMAL	RAT	LD50	>2150	mg/kg
ORAL	RAT	LD50	1118	mg/kg
VAPOURS	RAT	4H LC50	>11.3	mg/l

BISPHENOL A EPOXY RESIN (MW <700)

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact. May cause sensitisation in susceptible individuals.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

EPOXY PHENOL NOVALAC

ALGAE	72H ErC50	9.4	mg/l
Daphnia magna	48H EC50	1.7	mg/l
FISH	96H LC50	1.5	mg/l

1,4-BUTANEDIOL DIGLYCIDYL ETHER

Scenedesmus Subspicatus	72H ErC50	110	mg/l
ZEBRAFISH (Brachydanio rerio)	96H LC50	24	mg/l

BISPHENOL A EPOXY RESIN (MW <700)

Daphnia magna	48H EC50	1.7	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H ErC50	2.4	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	1.2	mg/l

12.2. Persistence and degradability

Persistence and degradability: Not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Non-volatile.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(ORTHO CRESOL NOVALAC EPOXY RESIN)

14.3. Transport hazard class(es)

Safety Data Sheet

multicomp PRO

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH205: Contains epoxy constituents. May produce an allergic reaction.
H302+H312+H332: Harmful if swallowed, in contact with skin or if inhaled
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H319: Causes serious eye irritation.
H411: Toxic to aquatic life with long lasting effects.
H412: Harmful to aquatic life with long lasting effects.

Part Number

MP000426

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO