Digital Soldering Stations ESD Safe

multicomp PRO



Specifications

Input Voltage	: 100V AC to 120V AC 60Hz
Heater voltage	: 26V AC
Temperature range	: 150°C to 450°C
Temperature offset range	: ±50°C
Temperature stability	: ±2°C (in still air, no load)
Temperature adjustment	: 5 digits (Default)/1 digit (Fine-tuning)
Automatic stand-by time	:1-120 minutes (Adjustable)
Automatic shutdown time	:1-120 minutes (Adjustable)
Heater	:60W High performance dual-core ceramic heater
Tip-to-ground impedance	:< 2Ω
Tip-to-ground voltage	:< 2mV

Includes

Main Unit	
Iron	1
Iron stand	
Cleaning Sponge	

Part Number Table

Description	Part Number
Digital Soldering Station, ESD, 60W, 120V AC, US Plug	MP740138
Digital Soldering Station, ESD, 80W, 120V AC, US Plug	MP740139
Digital Soldering Station, ESD, 100W, 120V AC, US Plug	MP740140

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

