multicomp PRO

RoHS Compliant



Specifications:

Electrical Characteristics (at 25°C)

1kHz 1V	L	470µH ±10%
at 25°C	DCR	1.48Ω (Max.)
1kHz 1V Irms = 0.42A	ΔΤ	Temperature Rise 40°C (Max.)

Operating temperature: -55°C to +130°C

Material List

No.	ltem	Material Description
1	Core	K22 DRM 9.5 × 5.5 RB-R B = 4.5 F = 3
2	Wire	Ø0.2mm × 1P 2UEF1/U 155°C
3	Solder (Lead Free)	Sn99.3%/Cu0.7%


Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



Inductor

multicomp PRO


Schematic Diagram



Note:

1. Wire Ø0.2mm × 2P 2UEF1/U 155°C 2. 101.5TS (Reference)


Electric Characteristics



Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



Configurations and Dimensions



А	9.8mm	(Maximum)
С	5.8mm	(Maximum)
D	2.9mm	(Reference)

Dimensions : Millimetres

Part Number Table

Description	Part Number
Inductor, 470µH, ±10%, SMD	MCSDC1006-471KU

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

