Pushbutton Switches Non-Illuminated, Square




Specifications

Contact Configuration
Actuator
Terminal
Rating
Contact Resistance
Insulation Resistance
Dielectric Strength
Electrical Life
Mechanical Life
Terminal Material
Push Force

SPST
Non-Illuminated, Square
Quick Connect Tab
1A, 125V AC/250V AC
30mΩ Max.
100MΩ Min. 500V DC
1000V AC/1 minute
5,000 Cycles Min.
10,000 Cycles Min.
Copper Alloy, Silver or Gold Plated
> 0.3kg

Dimension



Dimensions : Millimetres

Part Number Table

Description	Actuator Colour	Switch Operation	Part Number
Pushbutton Switch, Non-Illuminated, Square, SPST, Panel, QC	Black	On-Off	SW03218
	Red	On-Off	SW03217
	Green	On-Off	SW03220
	Black	(On)-Off	SW03222
	Red	(On)-Off	SW03221
	Yellow	(On)-Off	SW03223
	Green	(On)-Off	SW03224

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence. Multicomp is the registered trademark of the Group. © Premier Farnell Limited 2016.

www.element14.com www.farnell.com www.newark.com