2RO-20WER

TECHNICAL DATA SHEET

LAN Cable Model: CB19184

RoHS Compliant

Design of cable:					
Inner conductor	Single bare copper Ø0.483±0.005mm				
Insulation	HDPE				
Insulation Dia	Ø0.87±0.05mm				
Core colours	White-Blue/Blue White-Orange/Orange White-Green/Greer White-Brown/Brown				
Braiding	16X5/0.11 ±0.003mm Tinned copper				
Jacket	PVC				
Colour	Grey RAL7032				
Size	Ø4.8±0.2mm				
Wall thickness	≈0.5mm				
Printing	By request				
Electric data at 20°C					
Conductor resistance	≤110.0 Ohm/km				
Insulation resistance	≤5000M ohm*km				
Testing voltage	wire/wire 50Hz 1min=1.5KV				
Permissible temperature	-10°C~75°C				

Frequency	Impedance	RL	ATT	NEXT	ELFEXT	PSNEXT	PSELFEXT	SKW	NVP
Mhz	ohm	≥dB/100M	≤dB/100M	≤dB/100M	≥dB/100M	≥dB/100M	≥dB/100M	≤ns/100M	
1	100±15	20.0	2.04	65.3	63.8	62.3	60.8		66%
4		23.0	4.1	56. 3	51.7	53. 3	48.7		
10		25.0	6.5	50. 3	43.8	47. 3	40.8	≤ 45	
16		25.0	8.2	47. 3	39.7	44. 3	36.7		
20		25.0	9.3	44. 5	37.7	42. 8	34.7		
31.25		23.6	11 .6	42. 9	33.9	39. 9	30.9		
62.5		21.5	17.0	38.4	27.8	35.4	24.8		
100		20.1	22.0	35.3	23.8	32.3	20.8		

Important Notice: This data sheet and its contents (the "Information") belong to pro-POWER. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but pro-POWER assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where pro-POWER was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict pro-POWER's liability for death or personal injury resulting from its negligence.

