Trimmer Potentiometer

multicomp PRO

RoHS

Compliant

R

Features

- 6mm Square Multiturn
- · Cermet / Industrial / Sealed

: 10 to 1MΩ

: ±10% std.

: Infinite

: 1% or 2Ω max.

: 3% or 3Ω max.

: 12 turns nom

: (300 Volts max.)

: -55°C to +125°C

: ±100ppm/°C

: 200 Cycles

: Voltage= ±0.02% Resistance= ±0.05%

: 500V DC, 1,000 megohms min.

: 101.3kPa 600V AC, 8.5kPa 250V AC

0.25 Watt (70°C), 0 Watt (125°C)

: 98m/s² (1% ΔTR; 1% ΔVR)

: 390m/s² (1% ΔTR; 1% ΔVR)

: 1,000 Hrs, 0.25 Watt @ 70°C

Specifications

Electrical Characteristics

Standard Resistance Range Resistance Tolerance Absolute Minimum Resistance Contact Resistance Variation Adjustability

Resolution Insulation Resistance Dielectric Strength Effective Travel

Environmental Characteristic


Power Rating

Temperature Range Temperature Coefficient Vibration Shock Load Life Rotational Life

Physical Characteristics

Torque	: 25mN-m max.
Mechanical Stops	: Wiper Idles
Terminals	: Solderable pins
Standard Packaging	: 50pcs. per tube

Diagram



Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

multicomp PRO

2 WIPER

Part Number Table

Description	Resistance Ω	Part Number
Trimmer Potentiometer	1,000	MCWIW1015-W-102-LF
	10,000	MCWIW1015-W-103-LF
	20,000	MCWIW1015-W-203-LF
	500	MCWIW1015-W-501-LF
	5,000	MCWIW1015-W-502-LF
	50,000	MCWIW1015-W-503-LF

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

