

Socket - SD-D/SP - 2963323

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Control cabinet socket, for mounting on DIN rails and in the service interface, housing color: green, with spring-cage connection, national version: Germany, housing width 45 mm



Key Commercial Data

| | |
|--------------------------------------|--------------------------------|
| Packing unit | 5 pc |
| Minimum order quantity | 5 pc |
| GTIN | |
| GTIN | 4017918190682 |
| Weight per Piece (excluding packing) | 75.700 g |
| Custom tariff number | 85366990 |
| Country of origin | Greece |
| Note | Made to Order (non-returnable) |

Technical data

Dimensions

| | |
|--------|---------|
| Width | 45 mm |
| Height | 75 mm |
| Depth | 65.2 mm |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -20 °C ... 60 °C |
| Ambient temperature (storage/transport) | -20 °C ... 60 °C |

General

| | |
|-----------------------|----------|
| Nominal voltage U_N | 250 V AC |
| Nominal current I_N | 16 A |
| Status display | No |

Socket - SD-D/SP - 2963323

Technical data

General

| | |
|-----------------------------|-------------|
| Contact material | CuZn37 |
| For country-specific use in | D |
| Color | green |
| Insulating material | PA |
| Standards/regulations | IEC 83 |
| | DIN 49440-1 |

Connection data

| | |
|---------------------------------------|------------------------|
| Conductor cross section solid min. | 0.2 mm ² |
| Conductor cross section solid max. | 4 mm ² |
| Conductor cross section flexible min. | 0.2 mm ² |
| Conductor cross section flexible max. | 2.5 mm ² |
| Conductor cross section AWG min. | 24 |
| Conductor cross section AWG max. | 12 |
| Connection method | Spring-cage connection |
| Stripping length | 8 mm |
| Screw thread | M3 |

Standards and Regulations

| | |
|-----------------------|-------------|
| Standards/regulations | IEC 83 |
| | DIN 49440-1 |

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50 |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27142300 |
| eCl@ss 4.1 | 27142300 |
| eCl@ss 5.0 | 27142300 |
| eCl@ss 5.1 | 27142300 |
| eCl@ss 6.0 | 27142300 |
| eCl@ss 7.0 | 27142305 |
| eCl@ss 8.0 | 27142305 |
| eCl@ss 9.0 | 27142305 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001325 |
| ETIM 3.0 | EC001325 |
| ETIM 4.0 | EC001663 |

Socket - SD-D/SP - 2963323

Classifications

ETIM

| | |
|----------|----------|
| ETIM 5.0 | EC001663 |
| ETIM 6.0 | EC001663 |
| ETIM 7.0 | EC001663 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211806 |
| UNSPSC 7.0901 | 39121406 |
| UNSPSC 11 | 39121406 |
| UNSPSC 12.01 | 39121406 |
| UNSPSC 13.2 | 39121406 |
| UNSPSC 19.0 | 39121406 |