

Pressure Transmitter, 0-5psi, 0-5V out, 11-28V, NPT1/2 M, DIN 43650, Plug, Gauge



## PT989 Series IOT Pressure Sensors Technical Data Sheet

**PT989-5PV1J22B1C10G**

### Features

- Pressure range 0-5psi
- Gauge pressure transmitter
- Constant current / Constant Voltage power supply
- Isolated construction, enable to measure various media
- Stainless Steel
- Reverse polarity protection
- Short protection

### Applications

- Industrial process control
- Gas, liquid pressure measurement
- Gasoline, petroleum and chemical industries
- Water management

### Description

PT989-5PV1J22B1C10G is a highly stable and reliable pressure transmitter with span and zero correction. PT989-5PV1J22B1C10G pressure transmitter comes in a compact size, and is lightweight and stable. It can be used to measure pressure levels for many applications in metallurgy, mining, chemicals, water supply and waste management.

### Product Configuration

Application:	Pressure Transmitter
Pressure Type:	Gauge
Electrical Connector:	DIN 43650
Process Connector:	NPT1/2 Male

### General Specifications

Description	Minimum	Typical	Maximum	Unit
Pressure Range	0		5	psi
Accuracy		±0.5		%Full Scale
Zero Thermal Error			±0.05	% Full Scale/°C
Span Thermal Error			±0.05	% Full Scale/°C
Compensated Temp Range	0		50	°C
Long Term Stability			±0.3	%Full Scale/year
Overpressure		1.5		xFull Scale

### Electrical Specifications

Description	Minimum	Typical	Maximum	Unit
Output Signal		0-5V		
Power Supply/Excitation Level	11	24	28	VDC
Output Load			10,000	Ω



an INFINIT<sup>®</sup> brand

Pressure Transmitter, 0-5psi, 0-5V out, 11-28V, NPT1/2 M, DIN 43650, Plug, Gauge



## PT989 Series IOT Pressure Sensors Technical Data Sheet

**PT989-5PV1J22B1C10G**

### Material Specifications

Description	Material
Diaphragm	Stainless Steel 316L
Plug Housing	Plastic
Tubing	Stainless Steel 304
Pin	Kovar
O-Ring	Viton

### Mechanical Specifications

#### Electrical Connection

Transmitter connects with the outer circuit through DIN 43650 plug.

Pin	3-Wire
1	+V
2	GND
3	Signal: +OUT

### Environmental Specifications

Temperature (Operating)	-30°C to 80°C
Temperature (Storage)	-40°C to 120°C
Ingress Protection	IP65
Certifications	ROHS Compliant CE Compliant


The Infinite Electronics portfolio includes coaxial cable assemblies, connectors, adapters and custom products, as well as our wireless product line which includes antennas, RF amplifiers, lightning and surge protectors, and NEMA rated enclosures.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume any liability arising out of the use of any part or documentation.

# PT989-5PV1J22B1C10G CAD Drawing

Pressure Transmitter, 0-5psi, 0-5V out, 11-28V, NPT1/2 M, DIN 43650, Plug, Gauge

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	05/29/19	TOZA



UNLESS OTHERWISE SPECIFIED LENGTH DIMENSIONS ARE IN INCHES DIMENSIONS IN [ ] ARE IN MILLIMETERS		THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF L-COM. ALL RIGHTS RESERVED.	
TOLERANCES: .X±.2 [5.08]   FRACTIONS ± 1/32 .XX±.01 [25]   ANGLES ± 1° .XXX±.005 [13]		SHEET 1 OF 1	
ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.		SCALE N/A	
THIRD-ANGLE PROJECTION		REV A	
		PART NUMBER PT989-5PV1J22B1C10G	
SIZE A	CAGE 43321	DRAWN BY DZINN	REV A
WWW.L-com.com   e-mail: CustomerService@L-com.com		DRAWN BY DZINN	
an INFINITI brand		PART NUMBER PT989-5PV1J22B1C10G	
50 High Street, West Mill, 3rd Floor, Suite #30 North Andover, MA 01845 USA		REV A	
Phone: 1.800.341.5266   1.978.682.6936		SCALE N/A	
Fax: 1.978.689.9484		SHEET 1 OF 1	

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.