

Features

- Axial ferrite bead inductors
- Applications include suppression in digital equipment and clock circuits
- Supplied bandoliered on reels of 5000 suitable for automatic insertion


Specifications

Impedance	: 93Ω
DC Current Rating	: 3A
Ferrite Mounting	: Through Hole
SVHC	: No SVHC
Body Diameter	: 3.5mm
Core Material	: Ferrite
DC Current Max.	: 3A
External Length / Height	: 6mm
Impedance @ 100MHz Typ	: 65Ω
Impedance @ 10MHz Typ	: 25Ω
Inductor Case Style	: Axial Leaded
Inductor Type	: Ferrite Bead
No. of Pins	: 2
Package / Case	: Axial
Reel Quantity	: 5,000

Impedance


	Z
Minimum	60(Ω)
Test Frequency	100 (MHz)
Typical	93(Ω)

Diagram



A	B	C	E
3.5 ±0.2	6 ±0.3	52.4 ±1.5	5 ±0.5

Dimensions : Millimetres



Part Number Table

Description	Current Rating (A)	Bead Dimensions		Part Number
		Length	Diameter	
Inductor, Ferrite Bead, 65Z	3	6mm	3.5mm	MCAB 035060-33

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.