



Main

| | |
|--|---|
| Range | TeSys |
| Product name | TeSys GS |
| Device short name | GS2Q |
| Product or component type | Switch-disconnector-fuse |
| Poles description | 4P |
| Protected poles description | 4t |
| Contacts type and composition | 4 NO |
| [I _{th}] conventional free air thermal current | 400 A (at 40 °C) |
| [I _e] rated operational current | 200 A at 440 V 2 poles in series per phase and not juxtaposed DC-23A 315 A at 440 V 2 poles in series per phase and not juxtaposed DC-23B 250 A at 690 V AC-23A 315 A at 500 V AC-23A 315 A at 500 V AC-23B 400 A at 400 V AC-23A 400 A at 400 V AC-23B |
| Fuse type | BS |
| Fuse size | B4 B1 B2 B3 |
| Network type | DC AC |
| Network frequency | 50/60 Hz |

Complementary

| | |
|---|---|
| Type of operating handle | External frontal External right side |
| Mounting support | Plate |
| [U _i] rated insulation voltage | 800 V AC 50/60 Hz |
| [U _{imp}] rated impulse withstand voltage | 8 kV |
| Rated operational power in W | 220 kW at 690 V 220 kW at 500 V 220 kW at 400 V 95 kW at 690 V |
| Making capacity | 4000 A at 400 V AC-23B |

| | |
|---|--|
| [Icm] rated short-circuit making capacity | 50 kA at 400 V with protection by gG fuses |
| Breaking capacity | 3200 A at 400 V (AC-23B) |
| Short-circuit withstand | 40 kA |
| Mechanical durability | 10000 cycles |
| Electrical durability | 1000 cycles AC-23A 1000 cycles AC-23B 200 cycles DC-23A 200 cycles DC-23B |
| Connections - terminals | Power circuit: bars 45 mm ² Power circuit: lugs-ring terminals 185...240 mm ² |
| Tightening torque | Power circuit: 25 N.m |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 60947-3 |
| Product certifications | CE |
| IP degree of protection | IP20 conforming to IEC 60529 (with terminal cover) |
| Ambient air temperature for operation | -20...70 °C |
| Ambient air temperature for storage | -40...80 °C |
| Fire resistance | 850 °C fuse cover conforming to IEC 60695-2-1 960 °C body conforming to IEC 60695-2-1 |
| Height | 205 mm |
| Width | 318 mm |
| Depth | 149 mm |
| Net weight | 6.1 kg |

Offer Sustainability

| | |
|----------------------------|--|
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|