

Technical Data



SUPER 200



SUPER 200 is a multi purpose, high grade lubricant with PTFE for long lasting lubrication and protection on moving parts in office equipment, domestic appliances and similar machinery.

ADVANTAGES

- Reduces friction and wear
- Cleans, lubricates and protects
- Displaces moisture, prevents corrosion
- Broad operating temperature range (-10°C to $+180^{\circ}\text{C}$)

APPLICATIONS

Especially effective as a high-temperature lubricant on fuser units in photocopiers, where temperatures can reach $150 - 160^{\circ}\text{C}$. Also suitable for mechanisms such as:

- Locks
- Hinges
- Tracks
- Clutches
- Bearings
- Chains
- Gears
- Precision Tooling

Super 200 will clean away surface contamination, displace moisture, prevent squeaking and leave a durable, protective film on the treated part. Apply directly onto the components to be treated. Ensure the electrical equipment is switched off before applying Super 200. After spraying, always leave for at least 4/5 minutes to allow dispersal of solvent vapours, before operating the equipment.

TECHNICAL DATA

Appearance	:	Amber liquid
Odour	:	Butyl Acetate
SG @ 25°C	:	0.875
Pressure @ 25°C	:	3.5
Discharge rate	:	1.1 /sec
Temperature range	:	Operational from -10°C to $+180^{\circ}\text{C}$
Solubility	:	Soluble in most solvents, insoluble in water
Recommended Solvents	:	Aeroklene 50, Coldklene 110, Deflux 160

Flammability	:	Classified as extremely flammable under CHIP Regulations
Flashpoint	:	Not applicable in sealed aerosol
Packaging	:	200ml aerosol (12 per carton)

STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

Health and Safety sheet available separately.

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

CRC Industries UK Limited, Wylde Road, Bridgwater, Somerset, TA6 4DD

Tel: +44 (0) 1278 727200

Fax: +44 (0) 1278 425644

Web: www.ambersil.com

E-mail: sales.uk@crcind.com