R&S[®]InstrumentView Software Manual







Version 09.00

The software manual describes the following:

• R&S[®]InstrumentView

The R&S[®]InstrumentView supports the following product series:

- R&S[®]FPH
- R&S[®]ZPH
- R&S[®]FPC
- R&S[®]FSH4
- R&S[®]ZVH
- R&S[®]FSC
- R&S[®]RTA4000
- R&S[®]RTB2000
- R&S[®]RTC1000
- R&S®RTH1000
- R&S[®]RTM3000

The contents of this manual correspond to software version 2.10 or higher.

The software contained in this product uses several valuable open source software packages. For information, see the "Open Source Acknowledgment" document, which is available for download from the R&S InstrumentView product page at i.e. http:// www.rohde-schwarz.com/product/FPH > "Downloads" > "Software".

Rohde & Schwarz would like to thank the open source community for their valuable contribution to embedded computing.

© 2020 Rohde & Schwarz GmbH & Co. KG Mühldorfstr. 15, 81671 München, Germany Phone: +49 89 41 29 - 0 Fax: +49 89 41 29 12 164 Email: info@rohde-schwarz.com Internet: www.rohde-schwarz.com Subject to change – Data without tolerance limits is not binding. R&S[®] is a registered trademark of Rohde & Schwarz GmbH & Co. KG. Trade names are trademarks of the owners.

1321.1040.02 | Version 09.00 | R&S®InstrumentView

Throughout this manual, products from Rohde & Schwarz are indicated without the [®] symbol, e.g. R&S[®]InstrumentView is indicated as R&S InstrumentView.

Contents

1	Installing R&S InstrumentView	7
2	Connecting the Instrument	9
2.1	Connection Manager Menu	9
2.1.1	LAN Connection	10
2.1.2	USB Connection	11
2.1.3	List of Connections	12
2.1.4	Context Menu	13
3	R&S InstrumentView Screen Layout	14
3.1	Context Menu	16
4	General Settings	18
4.1	Printing Trace Windows	18
4.2	Report Generator	20
4.3	Save Instrument	23
4.4	Open Instrument	25
4.5	Options	25
4.5.1	Color Settings	26
4.5.2	Directory Settings	28
4.5.3	Application Settings	30
4.5.4	Keyboard Shortcuts	30
4.5.5	Command-Line Tool	31
4.5.6	About	31
5	Using R&S InstrumentView with a Spectrum and Network	Analyzer
	·····	
5.1	Working with Trace Windows	32
5.1.1	Get Trace	
5.1.2	Add Trace	
5.2	Working with Instrument	
5.2.1	Remote Display	40
5.2.1.1	Remote Display with Troubleshooting	41
5.2.2	Lab Display	43

5.2.3	File Transfer	
5.2.4	Synchronization	47
5.2.5	Multi-Transfer	
5.2.6	Screenshot	51
5.2.7	Date Time Synchronization	
5.2.8	Save Active Dataset	53
5.2.9	Activate Dataset to Instrument	53
5.2.10	Firmware Update	54
5.3	Working with Instrument Datasets	55
5.3.1	Using Transducers	
5.3.2	Using Cable Models	57
5.3.3	Using Calibration Kits	58
5.3.4	Using Limit Lines	59
5.3.5	Using Channel Table	61
5.3.6	Using Standards	62
5.3.6.1	Standards Table Editor	63
5.3.6.2	Measurement Type	63
5.3.7	Using Quick Name Table	66
5.3.8	Using Analog Modulation Analysis AM Limits	67
5.3.9	Using Analog Modulation Analysis FM Limits	
5.3.10	Wizard Set Editor	69
5.3.11	Map Creator	73
5.3.12	EMF Editor Tool	75
5.3.12.1	EMF Measurement Configuration Editor	76
5.3.12.2	EMF Measurement Set Editor	79
5.4	Analyze the Instrument Dataset	83
5.4.1	Spectrogram	84
5.4.2	Map Analysis	
5.4.3	GPX Conversion	
5.4.4	Dataset Image	91
5.4.5	EMF Measurement Result	
6	Using R&S InstrumentView with an Oscilloscope	101
6.1	Working in Offline Mode	

6.2	Working in Online Mode	
6.3	Scope Workspace Settings	
6.3.1	Scope Workspace Header Settings	104
6.3.2	Setup Dialog	
6.3.3	Context Menu	110
6.4	Get Trace	111
6.5	Add Trace	111
6.6	Screenshot	111
	Index	113

1 Installing R&S InstrumentView

Installing the R&S InstrumentView software

The R&S InstrumentView allows you to control the instrument remotely via LAN or USB interface. It is an application software which provides printing service, customize report generation and editorial functions on the different datasets used in the instrument. The R&S InstrumentView also provides post-processing features to edit the markers position on the trace measurements.

The R&S InstrumentView supports a range of:

- Spectrum analyzer, for example R&S FSH4, R&S FSC, R&S ZVH, R&S FPH, R&S ZPH and R&S FPC.
- Oscilloscopes: R&S RTA4000, R&S RTB2000, R&S RTC1000, R&S RTH1000, R&S RTM3000

The setup program installs the R&S InstrumentView software on PC's running Windows 7, 8 and 10.

To install the software, download the latest software installer from the individual instrument product homepage, i.e. www.rohde-schwarz.com/product/fph.

Running the R&S InstrumentView software



There are a few ways to start the R&S InstrumentView software:

- Double-click the R&S InstrumentView icon I on the desktop of the PC.

About the software information

To display the software information for R&S InstrumentView, select the "About" menu item in the "Options" menu. See Figure 1-1.

🖶 About InstrumentView 🛛 🗙				
R&S [®] Instr For use with RTC & RTM so What's New	umentView FSH4, ZVH, FSC, FPH, ZPH, FPC, RTI eries.	H, RTA, RTB,		
Legal Information				
InstrumentView V1.90.1-alpha+developerbuild (2019-11-13 07:19 UTC) InstrumentView Open Source Acknowledgement Copyright © 2018 by Rohde & Schwarz All Rights Reserved				
Active Reports V11.1.9726 Active Reports Open Source Acknowledgement Portions Copyright © GrapeCity, Inc. 2015 All Rights Reserved				
	Copy to Clipboard	Close		

Figure 1-1: About R&S InstrumentView

2 Connecting the Instrument

The InstrumentView software communicates with your instrument via USB or Ethernet (LAN).

You can select the type of connection using the connection manager menu at the top right-hand corner of the screen layout. See Figure 3-1.

The connection manager menu also displays the instrument connection status.

Table 2-1: Connection status

Connection status	Function	
Connected	One or more instruments are connected withe the PC	
Not Connected	No instrument is connected with the PC	

2.1 Connection Manager Menu

In the "Connection Manager" menu, you can configure the remote connection between the PC and the instrument.

Depending on the connection status icon \rightleftharpoons , you can connect or disconnect the instrument from the connection manager list.

믭	Conne	ction Mana	ager				×
6	र _{द्रद्र}		ວ ວ	8	Connections 3		
G		9	9		0		_
				-			
		Œ					
Г		Name		Serial Nr.	IP-Address		S
	×	Default			172.17.75.1		1
-						<i>P</i>	
	×	FPH			172.25.56.28	g	W
	+	ZPH	4	999991	172.25.56.170	Ø	Ŵ
							-
				ര	G		
		-	Add D	evices	e Disconnect		
	_			_	-		8
							Done

Figure 2-1: Connection manager menu

- 1 = LAN connection tab
- 2 = USB connection tab
- 3 = List of connections tab
- 4 = Connected instrument
- 5 = Connection manager list for LAN connection
- 6 = Select "Add Devices" button to configure a new instrument
- 7 = Select "Disconnect" / "Connect" button to connect or disconnect instruments from the connection manager list
- 8 = Select "Done" button to exit the "Connection Manager" dialog box

2.1.1 LAN Connection

During the initial startup, the "IP-Address" field is set to default "172.17.75.1". You can edit the IP address using the icons \mathscr{I} :

To add a new instrument (LAN connection)

1. In the "Connection Manager" dialog, select "Add Devices".

The "Add Single Device" dialog opens.

Add Si	ngle Device			
Name	Demo			
IP Address	172.25.56.61		Defau	ult
Discov	er Network Devices			
Network Adapter	Local Area Connection	•	Q	
	Wireless Network Connection 2			
	Bluetooth Network Connection			
	Wireless Network Connection			
	Local Area Connection			
	VirtualBox Host-Only Network			
			Ok	Cancel

- 2. In the "LAN" tab, you can automatically check the available network adapter connected on the PC. Use the *q* icon.
- 3. Set the "Name" and "IP address".
- 4. Press the "OK" button to add the new instrument to the connection manager list.

2.1.2 USB Connection

When the instrument is connected to the PC for the first time, Windows tries to install the new hardware automatically. The required drivers are installed along with the R&S InstrumentView software package.

When the drivers are found on your system and the hardware has been successfully installed, Windows shows a corresponding message.

There is only one USB instance in the connection manager list. See Figure 2-2.

Depending on the connection status icon \Rightarrow ×, you can connect or disconnect an instrument from the connection manager list.

🖶 Connection Manager			×
문 LAN 🥠	USB 😝 🤇	Connections	
Name	Serial Nr.	IP-Address	
	000000	172.16.10.10	
	😝 Disco	onnect	
			Done

Figure 2-2: USB connection

2.1.3 List of Connections

Only one USB connection instance is supported at any time.

To view a list of instruments connected to the PC, select the "Connections" tab in the "Connection Manager" dialog box.

The connection status is displayed according to the type of connection established between the PC and instrument, e.g. USB \sim , LAN \approx .

Depending on the connection status icon $rightarrow \infty$, you can connect or disconnect an instrument from the connection manager list.

		-	
	Name	Serial Nr.	IP-Address
움	ZPH	999991	172.25.56.170
물	FPC	101061	172.25.57.26
•	FPH	000000	172.16.10.10
		😝 Discol	nnect
			Done

Figure 2-3: List of connected devices

2.1.4 Context Menu

Right-click in the connection manager list to access the following menus:



3 R&S InstrumentView Screen Layout

The following illustrates the display of the R&S InstrumentView screen layout.

Instrument View	a	-	×
Connected 1	K 🔯 201704251221 X 🖺 Report Generator X +++, 201704251512 X 🖺 Report Generator X +++	++,ts\Am-mod.set 🗙 률 📲 201704251601 🗙 률 🕬 201704251602 🗙 률 🖓 201704251603	
\mu Print 🙎	Spectrum	Measurement Setup	-4
Report Generator	Ref Level -20 dBm 5 SWT 50 ms RF Attenuator 0 dB Trace Mode Clear / Write R8W 3 MHz Trigger Mode Free Run	Measurement Setup	
🔍 Open	VBW 3 MHz Irace Detector Auto Peak	Name Sweep (T1) Sweep (T1) Sw Date 4/25/2017 4/25/2017 4/2 Time 4/05/12/04 4/25/2017 4/2	Э
🖺 Save	d8m M5 D2 M6 M4 M3 M6	Instrument FPH - 101061 FPH - 1000 FPH	
🖳 Get Trace	74.35 Junite all not available all and a state in the part of the state of the stat	Instrument Mode Spectrum Analyzer Spectrum Analyzer Spe Meas Mode Spectrum Spectrum Spe Uplink Spe	m
👫 Add Trace	-eass 7 ** Reset Move 8	Downlink Scroll Up Channel Scroll Up Center Frequency 2.000000000 GHz 2.0	
🖶 Instrument 🔸	Corporation and a second secon	Frequency Offset 0.0 Hz 0.0 Hz 0.0 Scroll Dov Span 4.00 GHz 4.00 GHz 4.00 Ref Level - 22.00 dBm -22.00 dBm -20.00 dBm	m
🖉 Preparation 🔸	-10L4 Copy Active Sweep	Ref Offset 0.00 dB 0.00 dB 0.00 dB Range 100.00 dB 100.00 dB 100.00 dB RF Attenuation Scroll Here prtion Auto Low Distortion Auto Low Distortion	tion
ିନ୍ Analysis 🔸	and a start of a start of the s	RF Attenuator Pre-Amplifier RF Input Left Edge 10 50 Ω 50 Ω	
Ö _o Options →	-134.4 Delete Active Sweep	RBW Right Edge 3.00 MHz 3.00 MHz VBW SWT 50.00 ms 50.00 ms	
	164.4 View Display Line	Trigger Made Page Left Free Run Free Run Trigger Leve	
	assa	Trace Mode Page Right Clear / Write Clear / Write Trace Math Off Off Off Off	
		Primary Transducer Scroll Left	
	GHz GHz	Isotropic Antenna Scroll Right Off Off	

Figure 3-1: R&S InstrumentView screen layout

- 1 = Connection manager menu
- 2 = R&S InstrumentView menu
- 3 = Tab header bar
- 4 = Drop-down box to show hidden tabs in the Tab header bar
- 5 = Displays dialog box associated with the selected tab in the Tab header bar
- 6 = Trace measurement of the selected tab
- 7 = Mouse menu option. See details in Table 5-6.
- 8 = Context menu for trace measurement window
- 9 = Context menu for vertical scrollbar
- 10 = Context menu for horizontal scrollbar

Table 3-1: R&S InstrumentView menu

R&S InstrumentView menu	Function
🗳 Print	Prints and displays the print preview of the trace measurements. See Chapter 4.1, "Printing Trace Windows", on page 18.
Report Generator	Customizes the report generation for the trace measurement results. See Chapter 4.2, "Report Generator", on page 20.
<u>)</u> Open	Opens an existing trace measurement from the PC. See Chapter 4.4, "Open Instrument", on page 25.
Save	Saves the trace measurements and dataset. See Chapter 4.3, "Save Instrument", on page 23.
Get Trace	Retrieves a trace measurement from the connected instrument. See Chapter 5.1.1, "Get Trace", on page 33. See Chapter 6, "Using R&S InstrumentView with an Oscilloscope", on page 101.

R&S InstrumentView menu	Function
H Add Trace	Adds a trace measurement from the connected instrument to the existing trace measurement.
	See Chapter 5.1.2, "Add Trace", on page 38.
	See Chapter 6, "Using R&S InstrumentView with an Oscilloscope", on page 101.
🖬 Instrument 🕨	Remote display and control of the instrument from PC. See Chap- ter 5.2.1, "Remote Display", on page 40.
	Provides a snapshot of all connected devices. See Chapter 5.2.2, "Lab Display", on page 43.
	Files transfer between the instrument and PC. See Chapter 5.2.3, "File Transfer", on page 44.
	Synchronizing files between instrument and PC. See Chapter 5.2.4, "Synchronization", on page 47.
	Multiple transfers of trace measurements from the instrument to PC. See Chapter 5.2.5, "Multi-Transfer", on page 49.
	Captures a screenshot from the instrument. See Chapter 5.2.6, "Screenshot", on page 51
	Date time synchronization. See Chapter 5.2.7, "Date Time Synchro- nization", on page 52.
	Saves current active instrument dataset. See Chapter 5.2.8, "Save Active Dataset", on page 53.
	Activates dataset from PC to instrument. See Chapter 5.2.9, "Activate Dataset to Instrument", on page 53.
	Edits the different datasets supported by the instrument family.
🖋 Preparation 🔸	See Chapter 5.3, "Working with Instrument Datasets", on page 55.
	Provides post data analysis for spectrogram and map analysis.
¬🦓 Analysis 🔹 ►	Provides GPX conversion to KMZ and CSV file format.
	See Chapter 5.3.11, "Map Creator", on page 73.
	Provides color settings on the different elements in trace window.
🗘 Options 🕨	Configures the local directory settings for the different types of files used in the application.
	Provides setting to enable the retrieve of full dataset from instrument.
	Displays the keyboard shortcuts key.
	Displays the application software information.
	See Chapter 4.5, "Options", on page 25.

Tab header bar

After the PC is successfully connected to the instrument, new tabs appear in the "Tab header bar" when a menu item is selected from the R&S InstrumentView menu.

Tab selected for usage is highlighted with a horizontal blue line in the tab. See an example in Figure 3-2.



```
Figure 3-2: Selected tab
```

3.1 Context Menu

Right-click on the trace measurement window, horizontal scrollbar or vertical scrollbar to access the following menus:

Trace measurement window:

Reset Zoom	 "Reset Zoom", "Reset Move" - resets to original zoom level or moved position.
Reset Move	 "Copy Graphics": copies the selected trace from the trace window to the clipboard. This context menu is only available for R&S ZPH product series. "Copy Graphic with Label": copies the trace window and the
Copy Graphics	 "Measurement Setup" details to the clipboard. "Copy Data": copies the instrument setup and trace data from the trace window to the clipboard.
Copy Data	 "Copy Active Sweep": copies the selected trace from the trace window. When a trace is selected, the corresponding grid color on the Y-axis changed accordingly.
Copy Active Sweep	 "Paste Sweep": trace copied to the clipboard is pasted into the trace window. "Delete Active Sweep": deletes the selected trace from the trace
Paste Sweep	 Delete Active Sweep : deletes the selected trace non-the trace window. When a trace is selected, the corresponding grid color on the Y-axis changed accordingly. "View Display Line": a useful feature to visibly show the display.
Delete Active Sweep	 "View Grid": enables or disables the display of grid line on the trace window.
View Display Line	
🗸 View Grid	

Context Menu

Horizontal scrollbar:

Scroll Here
Left Edge
Right Edge
Page Left
Page Right
Scroll Left
Scroll Right

- "Scroll Here" : navigates to the cursor position.
- "Left Edge", "Right Edge": navigates to the extreme left or right of the scrollbar position.
- "Page Left", "Page Right": pages left or right on the scrollbar position.
- "Scroll Left", "Scroll Right": navigates left or right on the scrollbar position.

Vertical scrollbar:

Scroll Here	
Тор	
Bottom	
Page Up	
Page Down	
Scroll Up	
Scroll Down	

- "Scroll Here": navigates to the cursor position
- "Top", "Bottom": navigates to the top or bottom of the scrollbar position.
- "Page Up", "Page Down": pages up or down on the scrollbar position.
- "Scroll Up", "Scroll Down": navigates up or down on the scrollbar position.

4 General Settings

The following chapters give information about how to perform general settings like opening and saving files and setting up the report details.

4.1 Printing Trace Windows

The dual trace feature is supported in the R&S ZPH product series only. Each trace contains its own marker set values.

🖳 Print

The "Print" menu allows you to print the trace measurements currently loaded in the R&S InstrumentView. It also displays the print preview window on the printed output.

Arrangement of the printing sequence is possible by dragging the trace measurement window in the "Selection" section. See Figure 4-1.

Printing Trace Windows



Figure 4-1: Print dialog

- 1 = Arrangement of the number of trace measurement windows per page (1, 2, 4, 6, 16 per page)
- 2 = Print preview tool
- 3 = Orientation on the printed output
- 4 = Preview window
- 5 = "Color mode" defines the window background color as black or white
- 6 = "Selection" displays the printed order of the trace measurement windows

Report Generator

Print preview tools	Function
Print or (Ctrl+P)	Prints the preview output.
Copy (Ctrl+C)	This action is not available.
Zoom in (Ctrl+)	Zoom-in the preview details.
Zoom out (Ctrl-)	Zoom-out the preview details.
100% (Ctrl+1)	Previews the actual print size of the trace measure- ment window.
Page width (Ctrl+2)	Previews the whole width size of the trace measure- ment window.
Whole page (Ctrl+3)	Previews a single page of the trace measurement result in the preview window.
Two pages (Ctr+4)	Previews two pages of trace measurement results on the same row in the preview window.

Table 4-1: Print preview tools

Context menu

Right-click in the print preview window to access the following menus:

- "Increase Zoom": zoom-in on the print preview details
- "Decrease Zoom": zoom-out on the print preview details

4.2 Report Generator

Report Generator

The "Report Generator" menu allows you to select logo, report output format and language and selectively display measurements parameters to customize the test report. See Figure 4-2.

General Settings

Report Generator



Report Settings	s Measurement Settings
 Measureme 	ent
Dataset	Dataset2019050.set
Comments	1
	Add 🕅 Remove 🛠 Up 😵 Down 🕜
Pictures	 Dpen after Generation
Previe	w 13 Generate 14

Figure 4-2: Report generation dialog

- 1 = Displays report library directory path
- 2 = Selects, if the files in the subfolders are included in the display
- 3 = Selects "Refresh" button to refresh the files in the selected report library directory
- 4 = Homepage
- 5 = Opens the PC window explorer to set report library directory path
- 6 = List of dataset files extracted from the report library directory. See Chapter 4.3, "Save Instrument", on page 23
- 7 = Dataset/Screenshot tools
- 8 = List of dataset sequence to be generated in report
- 9 = Report parameters
- 10 = User customization for logo and report language and format (PDF, HTML, RTF)
- 11 = "Output Option" selects, if a report is generated into one single file or into separate files for each folder
- 12 = Activates"Open after Generation" checkbox to open the file after report generation
- 13 = Selects "Preview" button to preview the report format
- 14 = Activates "Generate" button to generate the report
- 15 = "Measurement Settings" to insert additional comment and screenshots at the end of the report

Report tools	Function
"View"	Views dataset/screenshot.
"Add"	Adds selected dataset/screensot.
"Remove"	Deletes the selected dataset/screenshot.
"Up"	Moves forward the selected dataset/screen- shot.sequence.
"Down"	Moves backward the selected dataset/screen- shot.sequence.

Table 4-2: Dataset/Screenshot tools

Report parameters

The following shows a snapshot of the report generated. See Figure 4-3.

It shows the details parameters in the "General Information", "Measurement Results" and "Measurement Settings" section. These details parameters are configurable for report generation. See index 8 of Figure 4-2.

Save Instrument

Date: 10/5/2018	Instrument: ZPH - 999991/002
User.	Site:
Comments:	

Measurement Results

DTF



Markers			
M 1 Position	19.68 m	M 2 Value	-46.81 dB
M 1 Value	-45.20 dB	M 3 Position	27.68 m
M2 Position	50 m	M 3 Value	-47.56 dB
Limit Line Results	Limit Line Results		
Threshold (Upper)		-36.00 dB PASS	
Measurement Setup			
Date	10/5/2018	Start Distance	9.000 m
Time	10:32:10 AM	Stop Distance	50.000 m
Instrument	ZPH - 999991/002	Start Frequency	1.270390417 GHz
Meas Mode	DTF	Stop Frequency	1.731609583 GHz
Calibration State	Default Calibration	Cable Model	<none></none>
Trace 1 Setup			
Trace Mode	Clear / Write	Format	Magnitude
Rance	50 dB	RefLevel	-12 dB

Figure 4-3: Test report generated

- 1 = General information
- 2 = Marker data
- 3 = Measurement results
- 4 = Measurement settings

4.3 Save Instrument

💾 Save

Depending on the types of dataset or trace windows (e.g. screenshot) that the R&S InstrumentView is working with, the "Save" function saves the files in their respective file format. See Table 4-3.

Table 4-3: File format

Description	File format
Primary transducer factor, secondary transducer factor and isotropic transducer factor	*.pritrd, *.sectrd, *.isotrd
See Chapter 5.3.1, "Using Transducers", on page 55.	
Cable models	*.cblmod
See Chapter 5.3.2, "Using Cable Models", on page 57.	
Calibration kit	*.ckit
See Chapter 5.3.3, "Using Calibration Kits", on page 58.	
Relative limit line and absolute limit line	*.relli, *.absli
See Chapter 5.3.4, "Using Limit Lines", on page 59.	
Channel table	*.chnta
See Chapter 5.3.5, "Using Channel Table", on page 61.	
Standards table	*.semst, *.chpst, *.obwst, *.tdmst
See Chapter 5.3.6, "Using Standards", on page 62.	
Quick name table	*.qnt
See Chapter 5.3.7, "Using Quick Name Table", on page 66.	
Ama limits	*.aamlim, *.fmlim
See Chapter 5.3.8, "Using Analog Modulation Analysis AM Limits", on page 67 and Chap- ter 5.3.9, "Using Analog Modulation Analysis FM Limits", on page 68.	
Datasets	*.set, *xset, *cset,
See Chapter 5.2.8, "Save Active Dataset", on page 53 and Chapter 5.2.9, "Activate Dataset to Instrument", on page 53.	
EMF	*.emcf, *.emrf, *.emdf
See Chapter 5.3.12.2, "EMF Measurement Set Edi- tor", on page 79 and Chapter 5.3.12.1, "EMF Mea- surement Configuration Editor", on page 76.	
See also Chapter 5.4.5, "EMF Measurement Result", on page 92.	
Screenshot	*.png, *.bmp, jpg, *.gif
See Chapter 5.2.6, "Screenshot", on page 51.	
Trace measurement with setup configuration details	*.set
See Chapter 5.1, "Working with Trace Windows", on page 32.	

Options

Description	File format
Measurement wizard set	*.mdf, xmdf
See Chapter 5.3.10, "Wizard Set Editor", on page 69	
Map data	*.idm, *prj, *.gpx
See Chapter 5.3.11, "Map Creator", on page 73.	
Spectrogram	*.spm
See Chapter 5.4.1, "Spectrogram", on page 84.	
Scope waveforms with setup configuration details	*scset
See Chapter 6, "Using R&S InstrumentView with an Oscilloscope", on page 101	
CSV instrument file reconstruction supportsTrans- ducer , Cable Model, Channel Table, Limit Line, AMA AM Limit, AMA FM Limit and Standard	*.csv

4.4 Open Instrument

🗼 Open

The "Open" menu allows you to open existing trace measurements, datasets or oscilloscope waveform file from the PC and display them. After selecting a file, a new tab is opened in the "Tab header bar".

For trace measurement details, see Figure 5-1.

For supported dataset details, see Chapter 5.3, "Working with Instrument Datasets", on page 55.

For use with the oscilloscope waveforms, see Chapter 6, "Using R&S InstrumentView with an Oscilloscope", on page 101.

Context menu

For details, see Chapter 3.1, "Context Menu", on page 16.

4.5 Options

🛱 Options

The "Options" menu allows you to configure the application preference such as the color settings of the trace element, selection of instrument type family, directory path setting , display of keyboard shortcuts and software information.

•	Color Settings	26
•	Directory Settings	28
•	Application Settings	30
•	Keyboard Shortcuts	30
•	Command-Line Tool	31
•	About	31

4.5.1 Color Settings

The "Color Settings" dialog provides settings for the color displayed of the different trace elements in the trace window. See Figure 4-4. You can select if you want to display the analyzers or the oscilloscopes color settings.



Figure 4-4: Color settings dialog for spectrum and network analyzers

- 1 = "Color Settings" menu display the color of each trace element in the trace window
- 2 = "Preview" window displays each trace element color in the trace window

Options



Figure 4-5: Color settings dialog for oscilloscopes

The following settings are provided:

- Background
- Grid line
- Text display on the trace window
- Up to four trace lines
- Up to four memory trace lines
- Up to maximum 4/16 trace lines for spectrum analyzers/ oscilloscopes
- Up to four minimum trace lines
- Up to four average trace lines
- Indicator line
- Display line
- Marker and delta marker line
- Upper and lower limit line
- Tx and adjacent channel indicator
- Channel bandwidth
- Up to two cursor lines

Select the desired trace element in the "Color Settings" menu and the "Color selection" dialog is displayed for configuration. See Figure 4-6.

There are a few ways to change the color settings in the "Color Selection" dialog:

• Select the desired color settings in the color display area

Options

- Selects the desired brightness setting in the brightness level indicator
- Modify the RGB color codes
- Modify the hex color codes



Figure 4-6: Color selection dialog

- 1 = Color display area
- 2 = Brightness settings indicator
- 3 = Color preview area
- 4 = RGB color codes 5 = HEX color codes

Select the "Default" button to restore the default settings of the trace element color. See Figure 4-4.

4.5.2 Directory Settings

The "Directory Settings" dialog provides the list of default path directories settings for the different type of files used in the application.

To change the path directories setting, double-click the desired file type and select the new directory.

Upon selection, the "Browse For Folder" dialog is displayed to configure the path directory setting. See Figure 4-7.

R&S®InstrumentView

Options

Default Local Directories	
Name	Directory
Local Home	C:\Users\Public\Documents\Rohde-Schwarz\InstrumentView
Datasets	C:\Users\Public\Documents\Rohde-Schwarz\InstrumentView\Datasets
Screenshots	C:\Users\Public\Documents\Rohde-Schwarz\InstrumentView\Screen Shots
Limit Lines	C:\Users\Public\Documents\Rohde-Schwarz\InstrumentView\Limit Lines
Limit Files	C:\Users\Public\Documents\Rohde-Schwarz\InstrumentView\Limit Files
Transducers (1)	C:\Users\Public\Documents\Rohde-Schwarz\InstrumentView\Transducers
Channel Tables	C:\Users\Public\Documents\Rohde-Schwarz\InstrumentView\Channel Tables
Standards	C:\Users\Public\Documents\Rohde-Schwarz\InstrumentView\Standards
Quick Name Tables	C:\Users\Public\Documents\Rohde-Schwarz\InstrumentView\Quick Naming Tables
Wizard Sets	C:\Users\Public\Documents\Rohde-Schwarz\InstrumentView\Wizard Sets
Wizard Results	C:\Users\Public\Documents\Rohde-Schwarz\InstrumentView\Wizard Results
Cable Models	C:\Users\Public\Documents\Rohde-Schwarz\InstrumentView\Cable Models
Calibration Kits	C:\Users\Public\Documents\Ro Browse For Folder
Spectrogram Recording Results	C:\Users\Public\Documents\Ro
Maps	C:\Users\Public\Documents\Ro
GPX Files	C:\Users\Public\Documents\Ro 4 3 3 7
EMF Measurements and Definitions	C:\Users\Public\Documents\Ro
EMF Results	C:\Users\Public\Documents\Ro
Default OK Cancel	Datasets Din Mod Limits
	→ Big Mode Linits
(2) (3) (4)	Make New Folder OK Cance

Figure 4-7: Directory settings dialog

- 1 = List of the different file types directory setting
- 2 = Press "Default" to reset the path directory to default settings
- 3 = Press "OK" button to confirm the settings of the path directory
- 4 = Press "Cancel" button to exit the path directory settings
- 5 = File browser for path directory selection

Options

4.5.3 Application Settings

Application Settings							
Retrieve	the full dataset. This includes calibration data when applicable.						
✓ Network	k disconnect detection.						
Meter Length	unit to display.						
Visual Settings							
Home Screen Logo RS Lo	go Light 🔻						
Menu Visibility							
Show O	scilloscope menu entries only.						
OK Cance	el						

By default, the calibration data (if applicable) is not included in the saved dataset.

If necessary, enable the checkbox to retrieve the full dataset including the calibration data.

By default, the "Network disconnect detection" status is checked. When enabled, the R&S InstrumentView reflects the network connection status accordingly. See Table 2-1.

In the "Visual Settings" menu, you can select if you want to use the R&S Instrument-View only with an oscilloscope.

The length unit displays the desired unit shown in the calibration data (if applicable).

4.5.4 Keyboard Shortcuts

There are several shortcut keys that you can use to navigate in the application, see Shortcut keyboard.

Options

🖶 Available Keybo	ard Shortcuts			×			
Open Save Print Copy Graphics View Disp. Line Reset Zoom Screeshot Get Trace	OpenCTRL + OSaveCTRL + SPrintCTRL + PCopy GraphicsCTRL + GView Disp. LineCTRL + LReset ZoomCTRL + RScreeshotCTRL + IGet TraceCTRL + W						
				Close			
Figure 4-8: Shortc	ut keyboard						

4.5.5 Command-Line Tool

The command-line tool is only applicable for R&S ZVH & R&S ZPH product series.

The command-line tool is run via the command prompt supported by PC's running Windows 7, 8 and 10.

The tool supports two types of command:

ConvertToZPH
 Converts individual dataset or datasets in a directory to compatible dataset of the desired device type.

Example: Example of syntax for the ZVH -> ZPH converter:

```
InstrumentView.exe -ConvertToZPH "input.set" "output.set"
InstrumentView.exe -ConvertToZPH "inputDirectory" "outputDirectory"
```

• ConvertToCSV Converts individual files to CSV compatible format.

Example: Example of syntax for the dataset -> .CSV converter:

InstrumentView.exe -ConvertToCSV "input.set" "output.csv"

4.5.6 About

See "About the software information" on page 7.

5 Using R&S InstrumentView with a Spectrum and Network Analyzer

The following chapters illustrate the functionality of the R&S InstrumentView for use with a spectrum analyzer in details.

Prerequisites

To enable the spectrum/network analyzer and CAT functionalities for the R&S InstrumentView, enable "Show Spectrum, Network analyzer and CAT functionalities" in the "Option >Settings " dialog. See also Chapter 4.5.3, "Application Settings", on page 30.

Application Settings							
✓	Retrieve the full dataset. This includes calibration data when applicable.						
	Network disconnect detection.						
Meter 🔻	Length unit to display.						
Visual Setting	gs						
Home Screen Logo	o RS Logo Light 🔹						
Menu Visibility							
	Show Oscilloscope menu entries only.						
ОК	Cancel						

5.1 Working with Trace Windows

The following illustrates the ways how you can work with the trace measurements in R&S InstrumentView.

Context menu

For details, see Chapter 3.1, "Context Menu", on page 16.

•	Get Trace	33
•	Add Trace	38

5.1.1 Get Trace

🖳 Get Trace

The "Get Trace" menu allows you to capture the current trace measurement from the instrument and display it in the trace window. A new tab is formed in the "Tab header bar" for every new trace captured from the instrument. See index 1 in Figure 5-1.

Each trace measurement result consists of two tabs:

- "Measurement"
 - "Measurement Setup"
 Details of the instrument measurement settings. See user manual of the respective instrument for details of measurement settings.
 - "Measurement Results" (if any) Pass/Fail result of the limit test. See index 6 and 7 in Figure 5-1.
 - "Markers" (if any) Setting of the markers position.
 - "DTF List"

Available for "DTF" mode measurements.

• "Setup"

Trace measurement details captured from the instrument are displayed in the "Setup" tab. You can edit existing setup information or add additional setup information on the selected trace measurement. See index 3 in Figure 5-1.

Start

Measurement Results Time Instrument MeasurementMode

ApertureSteps Suppression StartFrequency

FrequencyOffset Range TraceMode NofSweepPoints InternalDCBias

Copy Labels Setup (11)

Markers
Date
GPSLongitude

InstrumentMode

CalibrationState

CenterFrequency

Downlink StopDistance

StopDistance
 CenterFrequer
 RefLevel
 TriggerDelay
 TraceDetector
 VelocityFactor

Apply

Working with Trace Windows

Name GPSLatitude FirmwareVersion

StartDistance StopFrequency

Uplink

Span TriggerMode TraceMath CableModel

MeasurementFormat



Figure 5-1: Trace measurement window

- 1 = Tab header bar
- 2 = "Measurement" tab
- 3 = "Setup" tab
- 4 = Marker position
- 5 = Delta marker position
- 6 = Upper limit of limit line 1
- 7 = Trace shows that result failed at limit line 1
- 8 = Lower limit of limit line 2

Working with Trace Windows

- 9 = Trace Setup 10 = Marker Setup
- 11 = Copy Label Setup

Trace Setup

▼ Trace Setup											
Trace 1 Trace 2 Trace 3 Trace 4											
Trace Settings Limit Line Settings											
Show Trace			Test Limit	Select							
Trace Unit	dBm	•	Show Limit Line 1								
Trace Range 100 dB (10.0 dB/Div) Upper Limit Lower Limit											
Show Memory Trace No Limit Line Selected Select											
Trace Math	Memory - Trace	•	Show Limit Line 2								
Math Position (%)		0	Upper Limit								

Figure 5-2: Trace setup

The "Trace Setup" dialog is divided into three different settings: trace setup, memory trace and limit line settings.

- Each trace is represented with a different trace color. If there is more than one trace in the same trace window, you can go to the individual trace tab to disable or enable the "Show Trace" checkbox to set the trace display. See Figure 5-2. The following "Trace Unit" and "Trace Range" are selectable:
 - "Trace Unit"
 - "dBm", "dBmV", "dµV", "V", "W"
 - "Trace Range"
 - "150 dB (15.0 dB/Div)", "130 dB (13.0 dB/Div)", "120 dB (12.0 dB/Div)", "100 dB (10.0 dB/Div)", "50 dB (5.0 dB/Div)", "30 dB (3.0 dB/Div)", "20 dB (2.0 dB/Div)", "10 dB (1.0 dB/Div)", "5 dB (0.5 dB/Div)", "3 dB (0.3 dB/Div)", "2 dB (0.2 dB/Div)", "1 dB (0.1 dB/Div)", "Linear 0-100%"
- The "Show Memory Trace" is only enabled if the trace measurement captured from the instrument contains the memory trace information. With the memory trace, you can apply "Trace Math" method ("Trace - Memory", "Memory - Trace") between the trace and memory and see the result on the trace window. The "Math Position" shifts the trace resulted from "Trace Math" to the position defined in the entry box.

For more information on the memory trace, see the respective instrument user manual.

The "Limit Line Settings" provides two sets of limit line that you can apply on the trace window. Each set of the limit line provides the selection to apply it as "Upper Limit" or "Lower Limit". The test result of the limit line is displayed in the "Measurement" tab. See index 2 in Figure 5-1.

Selects "Select" to select the desired limit line from the "Limit Lines" folder directory in the PC. See Chapter 4.5.2, "Directory Settings", on page 28. You can enable or disable the display of the limit line using the "Show Limit Line 1" or "Show Limit Line 2" checkbox.

Marker Setup

 Marker Se 	tup													
	oft	Mat	, ter Delt	a Maike	ė L	aluelHzl		topet	at to he	t Peak To Mi	nimum Searc	n Limit Search	n Limit	alimit2
Marker 1 (M1)	\bigcirc	0					0	×	* "	¥	\bigcirc	\bigcirc	\bigcirc	
Marker 2 (D2)	\bigcirc	\bigcirc	\bigcirc		116	160563.3	80282	\mathbf{X}	* .»	\mathbf{Y}	\bigcirc	\bigcirc	\bigcirc	
Marker 3 (M3)	\bigcirc	0	\bigcirc		820	07042.25	35211	$\dot{}$		\mathbf{Y}	\bigcirc	0	\bigcirc	
Marker 4	0	\bigcirc	\bigcirc			20000	00000	X		\searrow				
Marker 5	0	\bigcirc	\bigcirc			20000	00000	$\overline{\mathbf{x}}$.⊼ _∞	\searrow				
Marker 6	0	\bigcirc	\bigcirc			20000	00000	Ň		¥	۲			
All Markers	Q,	Q,	Q					~			Q	Q	Q	
Start Search 1			70	* •	MHz	Sto	op Searc	h 1		90	• N	ЛНz		
Start Search 2			0	* •	MHz	Sto	op Searc	h 2		4000	÷ N	ЛНz		
N dB (M1)			3	* *	dB									

Figure 5-3: Marker setup

The "Marker Setup" allows you to label the trace measurement with up to six different markers. For more information on marker details, see the respective instrument user manual.

The first marker is always set as "M1" with the rest labeled as marker (M2, M3, M4, M5, M6) or delta marker (D2, D3, D4, D5, D6). See Figure 5-3.

The marker value can be individually positioned in the following ways:
- Value (Hz) Key in the desired frequency value in the entry box.
- "To Peak", "To Next Peak", "To Minimum" Auto-positioning of the marker value by selecting the peak, next peak or minimum value across the span width of the trace measurement.
- Auto positioning of marker value ("To Peak", "To Next Peak", "To Minimum") in the area defined by the search limit ("Search Limit 1" or "Search Limit 2"). The "Start Search 1", "Start Search 2", "Stop Search 1" and "Stop Search 2" defined the search start and stop limit. You can also find the auto positioning of the marker value using the "N dB (M1)".

This search function is only restricted to "M1" and available in spectrum operating mode.

"All Markers" This section is used to synchronize the criteria of all the marker positions.

Cable Setup

This setup is only available, if the instrument is in the "DTF" measurement mode.

You can set a DTF threshold and define the settings of your cable like velocity factor, frequency and cable loss. Optionally you can also import this settings from a file.

 Cable Setup 				
DTF Setting				
✓ DTF Threshold	0	🔹 d	В	
Cable Model Settings				
User Settings:			Current Model	No Cable Model Selected
Cable Velocity Factor			2	Select From File
Cable Frequency		Hz	Ap	oply User Settings
Cable Loss		dB/m	Clea	r File/User Settings

Figure 5-4: Cable setup for DTF measurements

Copy Label Setup

"Copy Label Setup" is only available with R&S ZPH product series.

The "Copy Label Setup" allows you to check or uncheck the measurement fields that are copied when using the context menu "Copy Graphic with Label".

Working with Trace Windows



Figure 5-5: Copy Labels Setup dialog

5.1.2 Add Trace

The "Add Trace" is not applicable for R&S ZPH product series.

Add Trace The "Add trace

The "Add Trace" menu allows you to add additional trace measurement captured from the instrument to an existing trace measurement displayed in the trace window. Each trace is represented with a different trace color. See Figure 5-6.

See details of the "Measurement" tab in index 2 of Figure 5-1.

See details of the "Setup" tab in index 3 of Figure 5-1.



Figure 5-6: Add a trace to an existing trace measurement

5.2 Working with Instrument

🖶 Instrument

The "Instrument" menu provides the following functions:

- Remote display and control of the instrument
- Snapshot display of all connected instrument
- Files transfer between instrument and PC
- File synchronization between instrument and PC
- Multiple updates of screenshot from instrument to PC
- Screenshot captured from the instrument
- Date and time synchronization between instrument and PC
- Saves a dataset from the instrument to PC
- Activates a dataset from PC to instrument
- Firmware update

•	Remote Display	40
•	Lab Display	. 43
•	File Transfer	44
•	Synchronization	47
•	Multi-Transfer	49
•	Screenshot	51
•	Date Time Synchronization.	. 52
		-

•	Save Active Dataset	53
•	Activate Dataset to Instrument	53
•	Firmware Update	54

5.2.1 Remote Display



To enter value:

- Select the left side of the rotary knob local to decrease entry value and right side of the rotary knob local to increase entry value.
- Select the center of the rotary knob
 to confirm the entry value

The "Remote Display" provides the remote display and control of the instrument. You can remotely control and display the instrument via the softkey and hardkey function displayed. See Figure 5-7.

See the respective instrument user manual for details of each of the softkey and hardkey functions.



Figure 5-7: Remote display of the instrument

5.2.1.1 Remote Display with Troubleshooting

When establishing a remote connection with the instrument, a message "Establishing Remote Connection..." is displayed. When there is a connection failure, the "Connection Error" popup message is displayed. The timeout for connection error is 30 seconds.



There are two possibilities for a connection failure:

USB device not initialized

The virtual network adapter for the USB device has not yet initialized after plugging in the USB cable. This process takes at least 10 seconds and it varies per PC setup.

You can view the status of the USB device under

Control Panel\Network and Internet\Network Connections settings in the PC operating system.

USB device not ready



USB device ready



RNDIS drivers not properly installed

You can verify the RNDIS drivers status in two ways:

 Under Control Panel\Programs\Programs and Features settings: The R&S InstrumentView RNDIS Driver (32-Bit or 64-bit) and Windows Driver Package - Rohde & Schwarz ESNA installments must be present.

R&S InstrumentView RNDIS Driver (64-Bit)	Rohde & Schwarz

Windows Driver Package - Rohde & Schwarz ESNA (05/01/2017 7.0.0.0)

Under

Control Panel\System and Security\System -> Device Manager **set**tings:

For FPH/ZPH/FPC, it should contain the following three devices:

- USB Composite Device with VID_0AAD
- USB Test and Measurement Device (IVI) with VID_0AAD
- Network adapter with the name Rohde & Schwarz <device type> Instrument. The highlighted "Rohde & Schwarz ZPH Instrument" network adapter would not show up in case the RNDIS driver is not correctly installed on the PC.

Rohde & Schwarz



If connection failure still persists, it is recommended to uninstall and reinstall the R&S InstrumentView software package. See Chapter 1, "Installing R&S InstrumentView", on page 7.

5.2.2 Lab Display

The "Lab" menu displays a snapshot of all the connected instruments in the display window.

Each snapshot provides you an instrument identity and overview of the current measurement:



Figure 5-8: Snapshot of all connected instruments

Context menu

Right-click on the instrument snapshot for the following menus:

Recall file on this device	"Recall file on this device": recalls a dataset stored on the PC to the selected device.
• Copy setup	"Copy setup": copies the measurement setup of the selected device to the internal clipboard of R&S InstrumentView. "Paste setup": pastes the measurement setup from the internal clipboard of R&S InstrumentView to the selected device.
Paste setup	Remote display "Recall all from this device": retrieves the measurement setup of the selected device and recalls it on all currently connected devi-
Remote display •	ces in the display window. "Recall all from file": recalls a dataset stored on the PC to the all connected devices in the display window.
Recall all from this device	
Recall all from file	

5.2.3 File Transfer

The "File Transfer" provides the file transfer between the instrument and PC. You can make single or multiple files transfer or perform a file synchronization between the instrument and PC. See Figure 5-9.



Figure 5-9: File transfer dialog

- 1 = Instrument icon.
- 2 = PC icon.
- 3 = Homepage
- 4 = File transfers from the instrument to PC and vice versa
- 5 = Instrument's folder directories
- 6 = PC's folder directories
- 7 = File transfer tools
- 8 = Templates & result synchronization
- 9 = List of selected files from the instrument

- 10 = List of selected files from the PC
- 11 = Progress bar showing the current folder synchronizing between the instrument and PC
- 12 = Progress bar showing the current file synchronizing between the instrument and PC
- 13 = Progress update dialog for "Templates and Results" synchronizing

Table 5-1: File transf	er tools
------------------------	----------

Icon	Function
"Delete"	Deletes the selected file.
"Lock"	Locks or unlocks the selected file.
	Alternative, you can select the a " icon to unlock or lock the file.
	Note: A locked file is a read-only file, it can only be viewed and transferred.
"Refresh"	Refreshes the file content in the selected folder directory.
43	
"Search"	Performs a file search function in the selected folder directory
Q	
"View"	Views the details of the trace measurement file.
•	For viewing, see Chapter 4.3, "Save Instrument", on page 23 for a list of file format supported.
	When a file is selected to be viewed, a tab is displayed in the header bar of the screen layout. See index 11 of Figure 5-11.

Homepage

When activated, the homepage helps you to set the directory path back to the root directory.

- \Public for instrument
- ..\Users\Public\Documents\Rohde-Schwarz\InstrumentView for PC

See Chapter 4.5.2, "Directory Settings", on page 28.

Templates & result synchronization

The "Templates & Result" synchronizes the different datasets and screenshots between the instrument and PC.

When activated, the file synchronization dialog box is displayed. It shows the progress status of the current folder and filename being synchronized. See index 13 in Figure 5-9.

When a file transfer conflict is detected during the synchronization process, the conflict dialog box is displayed to resolve the conflict. See Figure 5-10

Limit Lines X				
The destination folder already contains a file named 'GSM_Lower.rellim'. What would you like to do?				
Existing File: 191 Last Modified: 7/15/2015 8:38 AM New File: 191 Last Modified: 9/9/2015 10:33 PM				
Overwrite older files				
Do this for all conflicts				
	Skip	Overwrite	Cancel	

Figure 5-10: Conflict dialog box

- 1. Select "Overwrite older files" to overwrite older file with the newer file.
- 2. Select "Do this for all conflicts" to perform the "Skip" or "Overwrite" function in the current folder.

5.2.4 Synchronization

The "Synchronization" menu allows you to synchronize files between the local PC to instrument, vice versa.

You can use the overwriting option to decide how you want to synchronize the files when there is a conflict of files transfer.

		3	-			5
	\Public\Datasets		C:\Users\Public\Documents\Rohde-Schwarz\Instrument View\Datasets			Ð Ű
Ð	\Public\Screen Shots	$\langle \rangle$	C:\Users\Public\Documer	nts\Rohde-Schwarz\Instrume	nt View\Screen Shots	
	\Public\Wizard Results	<>	C:\Users\Public\Documer	nts\Rohde-Schwarz\Instrume	nt View\Wizard Results	
	\Public\Cable Models	<>	C:\Users\Public\Documer	nts\Rohde-Schwarz\Instrume	nt View\Cable Models	
	\Public\Calibration Kits	<>	C:\Users\Public\Documer	C:\Users\Public\Documents\Rohde-Schwarz\Instrument View\Calibration Kits		
	\Public\Channel Tables	<>	C:\Users\Public\Documer	C:\Users\Public\Documents\Rohde-Schwarz\Instrument View\Channel Tables		
	\Public\Limit Lines	<>	C:\Users\Public\Documer	C:\Users\Public\Documents\Rohde-Schwarz\Instrument View\Limit Lines		
	\Public\Limit Files	<>	C:\Users\Public\Documer	C:\Users\Public\Documents\Rohde-Schwarz\Instrument View\Limit Files		
	\Public\Quick Naming Table	<>	Cilleory BublickBocuments\Rohde-Schwarz\Instrument View\Quick Naming Tables			
	\Public\Standards	<>	Always Ask c\Dpcuments\Rohde-Schwarz\Instrument View\Standards			
UVERWITE ALL c)Documents\Rohde.Schwarz\Instrument View\Transdurers						
É			Overwrite Older	š≣ Default	🕂 Add	👿 Delete
To R	emote Synchronize	To Local	Always Ask	10	🖆 Remote	🖆 Local

- = Checkbox to select file directories for transfer
- 2 = Instrument file directories
- 3 = Direction of files transfer
- 4 = PC file directories
- 5 = Scrollbar to navigate files directories window
- 6 = File transfer icon to active file transfer from PC to instrument
- 7 = File synchronization icon to active file synchronization between PC and instrument, vice versa
- 8 = File transfer icon to activate file transfer from instrument to PC
- 9 = Overwriting option dialog box

10 = File manger icons

Table 5-2: File manager icons

File manager icon	Function
š ≣ Default	Presets the file directories window to default config- uration
🕂 Add	Adds a new file directory to the file directories win- dow
Delete	Deletes a new file directory to the file directories window
🖆 Remote	Accesses instrument file directories
🖆 Local	Accesses to local home directory

Context menu

Right-click on the instrument snapshot for the following menus:

٠



Synchronization dialog box

- "Include All", "Exclude All": includes or excludes all the directories for file transfer.
 - "Move Up", "Move Down": navigates the directories list.

Vertical scrollbar/ Horizontal scrollbar

• For details, see Chapter 3.1, "Context Menu", on page 16.

5.2.5 Multi-Transfer

The "Multi Transfer" menu allows you to capture and save trace measurements from the instrument. See Figure 5-11.



Figure 5-11: Multi-transfer dialog

- 1 = "Multi Transfer" tab displays the "Multi Transfer" dialog for settings
- 2 = Measurement results tab (see index 11 in Figure 5-11)
- 3 = Drop-down icon to display the tab hidden in the "Tab header bar" (see index 4 in Figure 3-1)
- 4 = Number of updates
- 5 = Display settings to configure the display of results for the trace measurement
- 6 = Auto save settings for the auto save function
- 7 = "Start/Stop icon" on page 51 to record or stop the trace measurements captured from instrument
- 8 = Overview display area for trace measurement captured from the instrument
- 9 = File browser to show that trace measurement files are captured with a prefix "MT20151028" defined in "Session name"
- 10 = Details of the hidden tab displayed from the drop-down icon
- 11 = Details of the selected trace measurement in the "Tab header bar"

Number of updates

The trace measurement can be updated with the following conditions:

- Single sweep with a fixed number. Default value is 5. Maximum value is 100000.
- Continuous sweep

The trace measurement is captured with a fixed interval timing defined by "Interval". Default value is 10. Maximum value is 3600.

Results

There are two ways to display the trace measurements captured from the instrument.

- The trace measurement in the overview area. See index 8 in Figure 5-11.
- The individual trace measurement result in the "Tab header bar". See index 2 in Figure 5-11.
- Select the individual trace measurement captured in the overview area to display the details information of trace measurement in the "Tab header bar".

See index 11 in Figure 5-11.

See also Chapter 5.1.1, "Get Trace", on page 33.

Auto save

The "AutoSave" performs an auto save function on the trace measurement updates from the instrument to PC hard disk.

The trace measurements are saved with a prefixed filename configure in the "Section name" and with an incremental order from _"000001" to _"xxxxxx". The "Save in" defined the file directory where these trace measurements are saved.

See index 9 in Figure 5-11 to view the trace measurements captured in the file directory.

Start/Stop icon

	~		
1	5	ィ	
\	2	5	/

The R&S InstrumentView prompts you to save unsaved data captured in the last recording session when the "Start" function is activated. See Figure 5-12.

Multi Transfer			×
Do you want to save t	hese items?		
	Yes	No	Cancel



The "Start" icon e e performs the recording function to capture the trace measurement updates from the instrument.

Depending on the setting in the "Results" section (see index 5 in Figure 5-11), the trace measurement updates can be displayed in the overview area (see index 8 in Figure 5-11) or individually displayed as a new tab in the tab header bar (see index 2 in Figure 5-11).

When the "Start" is activated, the "Start" icon • changes to "Stop" icon • . The "Stop" icon allows you to stop the recording process. When the "Stop" is activated, the R&S InstrumentView opens the "Delete" dialog. See Figure 5-13.

Delete		×
Are you sure to stop recording?		
	X	N
	Yes	No

Figure 5-13: Delete dialog

Select "Yes" to stop the recording process.

5.2.6 Screenshot

The "Screenshot" is used to capture the active instrument screen and display it in the trace window. See Figure 5-14.

This trace window is printed or saved for further editing in the application.



Figure 5-14: Screenshot

Context menu

Right-click on the instrument snapshot for the following menus:



5.2.7 Date Time Synchronization

The"Date Time Sync" is used to synchronize the date and time of the connected instrument with PC.

Select "OK" to confirm the "Date and Time" synchronization. See Figure 5-15.



Figure 5-15: Date and time synchronization

5.2.8 Save Active Dataset

The "Active to Dataset" is used to save the current active dataset from the instrument to PC.

 Select "Active to Dataset" to browse to the local PC directories to save the dataset file.

A message is displayed when the dataset file is saved successfully.

Active to Dataset	×
Dataset succesfully saved.	
	ОК

5.2.9 Activate Dataset to Instrument

The "Dataset to Active " menu is used to activate a dataset file from PC to the instrument.

To view dataset image, see Chapter 5.4.4, "Dataset Image", on page 91.

Select "Dataset to Active" to browse a dataset file from the local PC directories and activate it to the instrument.

A message is displayed when the dataset file is activated successfully.



5.2.10 Firmware Update

Instrument selected for firmware update must be powered by a power adapter. USB or SD card storage is needed in each device during the firmware update.

The "Firmware Update" menu provides the firmware update for the range of instruments supported by R&S InstrumentView.

Firmware update can be performed concurrently on the selected instruments belonging to the same instrument family.

Settings Status	
Instrument Family	
FPH 3	•
Selected Instruments	
EPH 101061 172.25.57.150 V1.40 FPH 101251 172.25.57.172 V1.20 Image: Section of the section of	_6
Note: USB or SDCard storage is needed in each device for software update.	Devices
I'miware Folder OK Cancel C:\Users\Low_Yo\Documents\Project\Test\FPH\Firmware\V1.12 Update	Select

Figure 5-16: Firmware update dialog

- 1 = Settings for the firmware update
- 2 = Status of the firmware update process
- 3 = Instrument family selection (FPH, ZPH, FPC. FSC, FSH4, ZVH4)
- 4 = Instrument list
- 5 = File browser to display the file folders
- 6 = Displays the Connection Manager
- 7 = Displays file browser to search instrument firmware

	Prenaration
67	rieparation

The "Preparation" menu allows you to configure the different dataset used in the instrument. See the following sections for more information on the dataset editor.

•	Using Transducers	. 55
•	Using Cable Models	.57
•	Using Calibration Kits	.58
•	Using Limit Lines	.59
•	Using Channel Table	.61
•	Using Standards	.62
•	Using Quick Name Table	.66
•	Using Analog Modulation Analysis AM Limits	.67
•	Using Analog Modulation Analysis FM Limits	. 68
•	Wizard Set Editor.	. 69
•	Map Creator	.73
•	EMF Editor Tool	75

5.3.1 Using Transducers

The frequency-dependent transducers table is used to correct the level values of the trace measurement for frequency-dependent components such as antennas, splitters and cables used in the test measurements.

The R&S InstrumentView comes with a list of predefined transducers tables for R&S components such as antennas and matching pad. Using the "Transducers" editor menu, you can customize the transducers table used for the frequency-dependent components introduced in your test measurements. See "Transducers table editor" on page 55.

Each transducer table may consist of up to 1000 reference values.

Transducers table editor

The "Transducers" table editor allows you to open, edit and save the transducers table. See Figure 5-17.

Name	HE200P-HF)	Data	Preview 6	
Description	HE200 passive 9	kHz - 30MHz (2)		Frequency (Hz)	TRD (dBµV/m)
			1	9000	88.7
Unit	dBμV/m	3.	2	10000	88.7
Tuno	Primary		3	12000	88.4
type	rimary	(4)	4	14000	88.1
			5	16000	87.7
			6	18000	87.1
			7	20000	86.5
			8	22000	86.1
			9	24000	85.7
			10	26000	85.4
			11	28000	85.1
			12	30000	84.7
			13	32000	84.4
			14	34000	84.1
			15	36000	83.8
			16	38000	83.5
			17	40000	83.2
			18	42000	82.8
() ()			19	44000	82.5
New Oper	n Save				D Sort

Figure 5-17: Transducer table editor

- 1 = Name of the transducers table
- 2 = Description of the transducers table
- 3 = "Unit" defines the level unit used in the transducers table ("dBµV/m", "dBµA/m")
- 4 = "Type" defines the type of transducer factor ("Primary", "Secondary", "Isotopic") used for the transducer table
- 5 = "Data" tab shows the details of the transducers table
- 6 = "Preview" tab displays the transducers table in a chart (see "Preview transducer table" on page 56)
- 7 = Editor of the transducers table
- 8 = Scroll bar
- 9 = "New" button creates a transducer table for entry
- 10 = "Open" button loads an existing transducers table
- 11 = "Save" button saves the current transducers table
- 12 = "Sort" button sorts the "Frequency (Hz)" of the transducers table in ascending order

Preview transducer table

The "Preview" tab displays the transducer table in a chart. It provides an overview of the frequency response of transducer table. See Figure 5-18.



Figure 5-18: Preview transducer table

5.3.2 Using Cable Models

Cable model is only applicable for R&S ZPH, R&S FSC, R&S FSH4 and R&S ZVH product series.

The R&S InstrumentView comes with a list of channel models which describes the cable characteristics. Using the "Cable Models" editor menu, you can customize the cable model according to your requirements.

Cable models editor

The "Channel Models" editor allows you to open, edit and save the cable model. See Figure 5-19.

Name		1	Data		
Description		2	۶≣	Frequency (Hz)	(5) Attenuation (dB/m)
		-	1		
Preset	User Setting 🔻		2		
(3) Absolute		mle	3		
			4		
Relative		%	5		
Rel. Dielectric Constant			6		
			7		
			8		
			9		
			10		
			11		
			12		
			13		
			14		
			15		
			16		
			17		I
			18		C
78	9		19		10
New Open	Save				Sort

Figure 5-19: Cable models editor

- 1 = Name of the cable model
- 2 = Description of the cable model
- 3 = Propagation velocity of the cable model
- 4 = Cable frequency
- 5 = Cable attenuation
- 6 = Scroll bar to navigate the cable model editor
- 7 = "New" button creates a cable model for entry
- 8 = "Open" button loads an existing cable model
- 9 = "Save" button saves the current cable model
- 10 = "Sort" button sorts the "Frequency (Hz)" of the cable model in ascending order

Propagation velocity

You can customize the propagation velocity for the cable model or use the following preset configuration:

Туре	Absolute m/s	Relative %	Rel. dielectric constant
Solid polyethelene	197700000	65.9	2.3
Foam polyethelene	24000000	80.1	1.56
Foam polystyrene	273000000	91.1	1.21
Solid teflon	208200000	69.4	2.07

5.3.3 Using Calibration Kits

The "Calibration Kits" editor is only applicable for R&S ZPH, R&S FSH4 and R&S ZVH product series.

The "Calibration Kits" editor provides the necessary parameters for you to define the calibration kit file associated with the calibration kit.

(1) Name	ZV-Z121 FEMALE				
Description					
Open (2)		Short	3		
Length	14.8	mm Ler	ngth	16	mm
Co	82	fF	Lo	10	pН
C1	0.5	fF/GHz	L1	-0.5	pH/GHz
C ₂	0.09	fF/GHz ²	L2	0.25	pH/GHz ²
C3	-0.003	fF/GHz ³	L3	-0.013	pH/GHz ³
Through (4)					
Length	72.3	mm			
56	\bigcirc				
New Open	Save				

1 = Name and description of the calibration kit

- 2 = Parameters for "Open" standard
- 3 = Parameters for "Short" standard
- 4 = Parameters for "Through" standard
- 2 = "New" button creates a calibration kit file for entry
- 3 = "Open" button loads an existing calibration kit file for modification
- 4 = "Save" button saves the current calibration kit file

5.3.4 Using Limit Lines

The limit line is used to identify if a signal complies with a certain level of characteristics. It is made up of two or more points that are connected to a line and each of the point that defines the shape of the limit line consist of two coordinates. One coordinate defines the absolute, relative or logarithmic value of the X-Unit position ("Hz", "s","m") and the other coordinate is the Y-Unit position ("dB", "dBm", "dBµV", "dBmV", "dBµA/m", "V", "V/m", "W/m²", "VSWR"). See "Limit lines table editor" on page 59.

The R&S InstrumentView comes with a list of limit lines table which is according to the test transmission standards. Using the "Limit Line" editor menu, you can customize the limit lines table which is deviated from the test transmission standards. See "Limit lines table editor" on page 59.

Limit lines table editor

The "Limit Line" table editor allows you to open, edit and save the limit lines table. See Figure 5-20.

Name	GSM_Lower	5 Data Prev	iew 6
Description	2	≸ ≣ Time	(s) dB (8)
	U	1 -0.00027	139 -100
3 X-Unit	s v Relative v	2 -0.00027	139 -5
(4) Y-Unit	dB	3 0.00027	139 -5
U	dB	4 7 0.00027	139 -100
	dBm	5	
	dBuV	6	
	dBuA	7	
	dBmV	8	
	dBuV/m	9	
	dBuA/m	10	
	v	11	
	V/m	12	
	w	13	
	14//7	14	
9 (10) New Open	(1) Save	14	12 Sort

Figure 5-20: Limit lines table editor

- 1 = Name of the limit lines table
- 2 = Description of the limit lines table
- 3 = "X-Unit" defines the unit used on the x axis of the limit lines table
- 4 = "Y-Unit" defines the unit used on the y axis of the limit lines table
- 5 = "Data" tab shows the details of the limit lines table
- 6 = "Preview" tab displays the limit lines in a chart (see "Preview limit lines table" on page 60)
- 7 = Editor of the limit lines table
- 8 = Scroll bar
- 9 = "New" button creates a limit line table for entry
- 10 = "Open" button loads an existing limit lines table
- 11 = "Save" button saves the current limit lines table
- 12 = "Sort" button sorts the x axis of the limit lines table in ascending order

Preview limit lines table

The "Preview" tab displays the limit lines in a chart. It provides an overview of the frequency response of the limit lines. See Figure 5-21.



Figure 5-21: Preview limit lines

5.3.5 Using Channel Table

The R&S InstrumentView comes with a list of channel tables which are according to the test transmission standards. Using the "Channel Table" editor menu, you can customize the channel table which is deviated from the test transmission standards. See "Channel table editor" on page 61.

Channel table editor

The "Channel Table" editor allows you to open, edit and save the channel table. See Figure 5-22.

	Name Description	cdma2k_10 (Sec 800 cdma2k_10 (Sec 800	MHz Band) ① MHz Band) ②			
∭ ≣	Band Name 3)	4 1st Ch	5 f(1st Ch) (MHz)	6 # of Chs	Spacing (MHz)
1	cdma2k(Sec 800)		0	851	720	0.025
2	cdma2k(Sec 800)		720	935	200	0.025
3						
4						
5						
6						
7						
8						
9		8				
10						
12						
13						
14						
15						
(9 ()	\bigcirc				
Ν	ew Oper	n Save				Sort

Figure 5-22: Channel table editor

- 1 = Name of the channel table
- 2 = Description of the channel table
- 3 = Band name in the channel table
- 4 = Starting channel number in the frequency band
- 5 = Starting frequency of the "1st Ch" channel
- 6 = Number of channels in the frequency band
- 7 = Channel spacing between two channels
- 8 = Editor of the channel table
- 9 = "New" button creates a channel table for entry
- 10 = "Open" button loads an existing channel table
- 11 = "Save" button saves the current channel table
- 12 = "Sort" button sorts the "1st Ch" of the channel table in ascending order

5.3.6 Using Standards

The "Standards" table editor is only applicable for R&S FPH, R&S FSC, R&S FSH4 and R&S ZVH product series.

The R&S InstrumentView comes with a list of mobile radio standards with predefined test measurement settings according to the standard's requirements. Using the "Stand-

ards" editor menu, you can customize the test measurement settings which are deviated from the standards. See Chapter 5.3.6.1, "Standards Table Editor", on page 63.

5.3.6.1 Standards Table Editor

The "Standards" table editor allows you to open, edit and save the measurement settings for a test standard. See Figure 5-23.

See the respective instrument user manual for details of each of the measurement settings in the dialog.

	(1) Name	cdma2000 1x							
	(2) De	scription	cdma2000 1x							
(Measurem	ent Type	Channel Power	•						
0	Settings	Chanr	nel Power Adjacen	t Settings 5						
	Resolution	Bandwidtł	1	10000	Hz	Auto	Trace Detector	RMS	•	
	Video	Bandwidt	1	300000	Hz	Auto	Channel Bandwidth		1228800	Hz
	9	Sweep Time	2	0.1	s	Auto	Power Unit	dBm	•	
		Spar	1	1474560	Hz	🖌 Auto				
	6	\bigcirc	8							
	New	Oper	Save							

Figure 5-23: Standard table editor

- 1 = Name of the standard table
- 2 = Description of the standard table
- 3 = Measurement Type ("Channel Power", "Occupied Bandwidth", "TDMA", "Spectrum Emission Mask")
- 4 = Details of the "Settings" tab are associated with the "Measurement Type" selected (see Chapter 5.3.6.2, "Measurement Type", on page 63)
- 5 = Details of the "Channel Power Adjacent Settings" tab are associated with the Measurement Type selected
- 8 = "New" button creates a new standard table for entry
- 9 = "Open" button loads an existing standard table
- 10 = "Save" button saves the current standard table

5.3.6.2 Measurement Type

Depending on the mobile radio standard used in the test measurements, there are four different types of "Measurement Type" which you can select to customize your measurement settings.

See the respective instrument user manual for details of each of the measurement type.

Channel power

The channel power measurement selectively measures the power of a specified transmission channel and adjacent channels. The following dialog provides the required measurement settings in the "Settings" tab and the TX channels and adjacent channels configuration in the "Channel Power Adjacent Settings" tab.

Settings Channel	Power Adjacent Settings					
Resolution Bandwidth	0	Hz	🖌 Auto	Trace Detector	Auto Peak	
Video Bandwidth	0	Hz	🖌 Auto	Channel Bandwidth	3840000	Hz
Sweep Time	0	s	🖌 Auto	Power Unit	dBm 🔻	
Span	0	Hz	🖌 Auto			

Figure 5-24: Channel power settings

Settings	Channel Power Adjacent Sett	ings				
TX Chani	nel	A	djacent Chai	nnels		
TX Bandwid	th 3840000 Hz	N	r of Adjacent Cha	nnels 2	Use Channel Filter	Off •
§≣ Sp	acing f(Hz)	ة≣	Bandwidth	Spacing f(Hz)	Relative Limits	Absolute Limits
TX 1-2	3840000	Ad	j 3840000	5000000	0	0
TX 2-3	3840000	Alt	3840000	5000000	0	0
TX 3-4	3840000					
TX 4-5	3840000					
TX 5-6	3840000					
TX 6-7	3840000					
TX 7-8	3840000					
TX 8-9	3840000					
TX 9-10	3840000					
TX 10-11	3840000					
TX 11-12	3840000					

Figure 5-25: Channel power adjacent settings

Occupied bandwidth

The occupied bandwidth is defined as the bandwidth that contains a specified percentage of the entire power of the transmitter. Default occupied bandwidth for the entire power of the transmitter is predefined at 99%. The following dialog provides the required measurement settings in the "Settings" tabs.

Settings							
Resolution Bandwidtł	0	Hz	🖌 Auto	Trace Detector	Auto Peak	•	
Video Bandwidth	0	Hz	🖌 Auto	Channel Bandwidth		0	Hz
Sweep Time	0	s	🗹 Auto				
Span	0	Hz	🖌 Auto				

Figure 5-26: Occupied bandwidth settings

TDMA power

The TDMA (time division multiple access) power is measured in the time domain of the instrument. In the mobile radio standard like, e.g. GSM, several users share a channel and each user is assigned a period of time or timeslot for usage. With TDMA power measurement, you can determine the power over one of the timeslot. The following dialog provides the required measurement settings in the "Settings" tabs.

Setting	s							
Resoluti	on Bandwidtł	300000	Hz	Auto	Trace Detector	Auto Peak	•	
Vide	eo Bandwidth	1000000	Hz	Auto	Burst Length		0.00047	s
	Sweep Time	0.001	s	Auto				

Figure 5-27: TDMA settings

Spectrum emission mask

The spectrum emission mask (SEM) measurement is a method used to detect the spurious emissions or intermodulation products of a signal. When performing the SEM measurement, the instrument checks the signal against a spectral mask to determine whether the signal complies with a specific standard. The following dialog provides the required settings to define the spectral mask in the "SEM" tab. The "Preview" tab illustrates the spectral mask defined in the "SEM" tab.

S	EM P	review							
	Use Char	nnel Filter	Off	•					
ÿ≣	Limit Cl	heck Mode	e Range Start	Range Stop	RBW	Limit Start Abs (dBm)	Limit Stop Abs (dBm)	Limit Start Rel (dB)	Limit Stop Rel (dB)
1	Absolute	2	-4000000	-2300000	1000000	-21	-21		
2	Abs and	Rel	-2300000	-1815000	30000	-36	-36	-50	-50
3	Abs and	Rel	-1815000	-1015000	30000	-36	-28	-45	-45
4	Abs and	Rel	-1015000	-815000	30000	-28	-28	-45	-45
5	Ref Chan	Power	-815000	815000	30000				
6	Abs and	Rel	815000	1015000	30000	-28	-28	-45	-45
7	Abs and	Rel	1015000	1815000	30000	-28	-36	-45	-45
8	Abs and	Rel	1815000	2300000	30000	-36	-36	-50	-50
9	Absolute	2	2300000	4000000	1000000	-21	-21		

Figure 5-28: SEM settings

5.3.7 Using Quick Name Table

The "Quick Name Table" is only applicable for R&S FSC, R&S FSH4 and R&S ZVH product series.

The R&S InstrumentView comes with a predefined quick name table which provides a set of naming elements that can be used to create meaningful name in a faster and convenient manner. Using the "Quick Name Table" editor menu, you can customize the frequently used terms when compiling a filename. See "Quick name table editor" on page 66.

Quick name table editor

The "Quick Name Table" editor allows you to open, edit and save the quick name table. See Figure 5-29.

ý ≣ 1	2	3	4	5	6
1 Location	Site	RL	Sector	UL	450
2		IL	A	DL	700
3		VSWR	В		850
4		DTF	С	GSM	900
5		ISOL	D	UMTS	1800
6		POW	E	CDMA2000	1900
7		SPECTR		EVDO	2100
8		ACLR		LTE	
9				TD-SCDMA	
10					
11					
12	Û				
13					
14					
15					
16					
17					
18					
19					
20	A				
New Op	ben Save				

Figure 5-29: Quick name table editor

- 1 = Editor of the "Quick Name Table"
- 2 = "New" button creates a new quick name table for entry
- 3 = "Open" button loads an existing quick name table
- 4 = "Save" button saves the current quick name table

5.3.8 Using Analog Modulation Analysis AM Limits

The "Analog Modulation Analysis (AMA) AM Limits" is only applicable for R&S FPH and R&S FPC product series.

Using the "AMA AM Limits" editor menu, you can customize the "AMA AM Limits" table which is used to evaluate the performance of the amplitude modulated signal. See Figure 5-30.

AMA AM limits table editor

The "AMA AM Limits" table editor allows you to open, edit and save the AMA AM limits table . See Figure 5-30.

Nan	ne							
¥	Туре	Enable	Upper limit	Unit	Enable	Lower Limit	Unit	
	Carrier Freq Offset	:	99999999.9	Hz		-99999999.9	Hz	
	Carrier Power		200	dBm		-200	dBm	
	Modulation Index		100	%		0	%	
	+Peak		1 999	%		0	%	
	-Peak		0	%		-999	%	
	±Peak/2		999	%		0	%	
	RMS		999	%		0	%	
	Mod. Freq		2000000	Hz		0	Hz	
	SINAD		100	dB		-20	dB	
	THD		20	dB		-100	dB	
	2 3	4)					
١	New Oper	n Sav	/e					

Figure 5-30: AMA AM limits table editor

- 1 = Editor of the "AMA AM Limits" table
- 2 = "New" button creates an AMA AM limits table for entry
- 3 = "Open" button loads an existing AMA AM limits table
- 4 = "Save" button saves the current AMA AM limits table

5.3.9 Using Analog Modulation Analysis FM Limits

The "Analog Modulation Analysis (AMA) FM Limits" is only applicable for R&S FPH and R&S FPC product series.

Using the "AMA FM Limits" editor menu, you can customize the "AMA FM Limits" table which is used to evaluate the performance of the frequency modulated signal. See Figure 5-31.

AMA FM limits table editor

The "AMA FM Limits " table editor allows you to open, edit and save the AMA FM limit table . See Figure 5-31.

Name							
§ ≣ Туре	Enable	Upper limit	Unit	Enable	Lower Limit	Unit	
Carrier Freq Offset		9999999.9	Hz		-99999999.9	Hz	
Carrier Power		200	dBm		-200	dBm	
Frequency Deviation		2000000	Hz		0	Hz	
+Peak		1) 2000000	Hz		0	Hz	
-Peak		0	Hz		-2000000	Hz	
±Peak/2		2000000	Hz		0	Hz	
RMS		2000000	Hz		0	Hz	
Mod. Freq		400000	Hz		0	Hz	
SINAD		100	dB		-20	dB	
THD		20	dB		-100	dB	
2 3	4						
New Open	Save						

Figure 5-31: AMA FM limits table editor

- 1 = Editor of the "AMA FM Limits" table
- 2 = "New" button creates an AMA FM limits table for entry
- 3 = "Open" button loads an existing AMA FM limits table
- 4 = "Save" button saves the current AMA FM limits table

5.3.10 Wizard Set Editor

The "Wizard Set Editor" is not applicable for the R&S FSC product series.

Using the "Wizard Set Editor" menu, you can customize the measurement table list which consists of several datasets used to perform a specific instrument setting and measurements, for example frequency setting, power meter measurement, analog modulation measurement. To acquire a dataset, set up the instrument as per your requirement and save the configuration. You can also use one of the predefined datasets to customize the measurement table list.

For instrument setup using the R&S FSH4 or R&S ZVH, the editor provides additional selection for calibration method use in the wizard measurement. See the respective instrument user manual for the list of available calibration method.



The measurement table list forms the measurement sequence in the wizard set. See item 5 in Figure 5-32

For more information on dataset, see Chapter 4.3, "Save Instrument", on page 23.

Wizard

The "Wizard " editor allows you to open, edit and save the measurement wizard set. See Figure 5-32.

To arrange the measurement sequence in the wizard set, double clicked or "Add" the desired dataset from the PC folder directory to the measurement table list. See index 4 and 5 of Figure 5-32.

				✓ Encryption
				Encryption Enabled
Datasets on PC	,		Wizard Settings Measurement Settings 6	Authentication
C:\Users\Public\Documents\Rohde-Schv	warz\Instrument View\Datasets		- Global	Password ••••••
Name	Date	Time		Confirm Password
Am-mod.set	4/4/2017	9:26 AM	Measurement Set Name Simple RF Measurement	
Dataset 201704031127.set	4/3/2017	11:28 AM	Description (Optional) Measurement using power meter	Use all Instrument Serial Numbers
sem.set	4/4/2017	3 9:26 AM	Description /	Specific Serial Numbers
sem1.set	4/4/2017	9:41 AM	Measurement Font	Add new Serial Number
			Default Calibration Factory 💌	💥 Add 🕅 Remove
			Allow Variable Number of Allow Skip Measurements	·
💿 View 💥 Add	(4)	🗴 Up 🙁 Down 🍿 Remove	— Sequence steps — a Pinish wizard sequence	101053
Measurements	<u> </u>		Encryption	Stored Serial Numbers
Name Instructions		Hardware Settings	Cable Definition for Antenna & Cable Test	101055
Spectrum Tast Please connect the cable from R	RF output to DUT			
Denna Malas Tast. Diseas segment the neuron mater	to DE cable of the DI IT			
DUIT Test				- Cable Definition for Antenna & Cable Test
Contra Co	~			
G				Cable Settings
				Cable Model EC4-50 1-2
			New Open Save	Cable Length (Meter) 12
				🗃 Browse 前 Remove

Figure 5-32: Wizard editor

- 1 = Homepage icon
- 2 = Opens the PC window explorer
- 3 = List of datasets that are available in the PC
- 4 = Navigation icon to preview, add, navigate and remove dataset in the measurement table list
- 5 = List of selected datasets used in the measurement table list. The "Name", "Instructions" and "Hardware_Setting" column are defined in the Measurement Settings dialog.
- 6 = Measurement settings tab
- 7 = Global dialog box
- 8 = Encryption dialog box
- 9 = Cable definition for antenna & cable test dialog box
- 10 = "New" button creates a wizard set for entry
- 11 = "Open" button loads an existing wizard set entry
- 12 = "Save" button saves the current wizard set entry

Navigation icon

Navigation icon	Function
 View 	Previews a selected dataset in the measurement table list.
😵 Add	Adds a selected dataset from the PC dataset list into the measurement table list.
🛠 Up	Navigates upward in the measurement table list.
😵 Down	Navigates downward in the measurement table list.
🗑 Remove	Removes a selected dataset from the wizard set.

Global

The "Global" dialog box provides the following settings that configure the wizard set:

- "Measurement Set Name" Name of the measurement wizard set. This field is displayed in the instrument as a read-only parameter.
- "Description (Optional)" Description of the measurement task. This field is displayed in the instrument as a read-only parameter.
- "Description / Measurement Font" Font type for on-screen instructions (Latin, Chinese/Japanese and Korean fonts are supported).
- Default calibration Sets the default calibration method use during the wizard measurement. See the respective instrument user manual for the calibration method information.
- "Allow Variable Number of Sequence Steps"
 If enabled, this field is configurable in the instrument and it allows you to remove steps from the measurement wizard set.
 If not enabled, this field is displayed in the instrument as a read-only parameter.
- "Allow Skip Measurements & Finish Wizard Sequence" If enabled, this field is configurable in the instrument and it allows you to skip the measurement step or finished the measurement wizard set. If not enabled, this field is displayed in the instrument as a read-only parameter.

Encryption

The "Encryption" dialog box provides the encryption function to secure the edited measurement wizard set.

The encrypted wizard set is only visible in the instrument with serial number configured in the "Encryption" dialog.

To enable the "Encryption" dialog, activate the "Encryption Enabled" checkbox.

To limit the usage of the wizard set on a selective number of instruments, add the instrument serial number defined in the field of "Specific Serial Numbers".

Cable definition for antenna & cable test

The "Cable Definition for Antenna & Cable Test" dialog box configures the cable model and cable length used in the instrument antenna & cable test mode.

To enable a different cable characteristic after each individual measurement in a wizard sequence (such as to perform same measurement for different cables), enable the checkbox "Prompt User to Cange Cable Settings".

Measurement settings

The "Measurement" tab configures the individual dataset used in the measurement table list.

Navigates from the list of datasets in the measurement table list (see index 5 of Figure 5-32) and select the desired dataset for configuration.

Defines the "Measurement Name" and describes the "Instructions" necessary for the measurement step.

Note: The description defined in the "Instructions" is displayed in the wizard message box during the exaction of the wizard set. See index 2 of Figure 5-34.



Figure 5-33: Measurement settings tab
Working with Instrument Datasets

- 1 = Defines the measurement name of the selected dataset
- 2 = Identifies the dataset filename that the measurement setting is linked to
- 3 = Defines the instruction description displayed in the wizard message box
- 4 = Instruction picture dialog
- 5 = Previews the configured measurement wizard dialog
- 6 = Hardware settings to configure the instrument's BNC input ("Trigger Input" or "Reference Input")

Instruction picture

The "Instruction Picture" section allows you to display a graphical image during the execution of the measurement wizard set. See Figure 5-34.

To select the desired picture, selects "Browse" button to open the PC window explorer and select the graphic image to use.

The "Preview" button allows you to preview the selected graphical image.



Figure 5-34: Wizard dialog box

1 = Instruction picture image

2 = wizard message box

5.3.11 Map Creator

The "Map Creator" is only applicable for R&S FPH and R&S FSH4 product series.

The "Map Creator" menu allows you to create a customize map for the indoor mapping application in the instrument. The tool is divided into the map section and the setup section. The purpose of the tool is to generate a small archive of images including an IDM file for use on the instrument and in the maps workspace.

In addition to creating a map, you can also specify the exact geographical location of the area you are measuring. To do so, you can specify three GPS reference points in

the entry field (see item 4 of Figure 5-35). With a GPS referenced map, it provides the following useful features:

- The map created is automatically rotated with the north side faces up.
- The instrument calculates and displays the distance between measurement points (in meters or feet, depending on the regional settings).
- You are able to embed the collected data into maps with a larger scale. Thus, you are able to, for example, combine measurement data recorded with the "Outdoor Mapping" application and data recorded with the "Indoor Mapping" application in a single map. For more information, see "Collecting Map Data chapter" in the user manual.



Figure 5-35: Map creator dialog box

- 1 = Map section
- 2 = Map folder name
- 3 = GPS reference coordinate
- 4 = Entry fields for the GPS reference coordinates.
- 5 = Load image supporting file format: "*.png", ".bmp", ".tiff," ".gif", ".jpg"
- 6 = Generate map

GPS reference coordinates

This GPS reference coordinate allows you to create a georeferenced map (with GPS coordinates) or a non-geo-reference map (without GPS coordinates). When enabled, three GPS reference coordinate positions ("Latitude" and "Longitude") are required to enter in the setup section with reference of the GPS targets **?** shown on the map. You can move the GPS target on the map which represents the corresponding values of the GPS reference coordinates.

Generate map

When generating the map, the R&S Instrume selected folder.	entView d	leletes all e	existing cotent in the	
Warning		×		
The selected folder appears to contain data. An empty folder is required to generate Indoor Maps				
Do you want to permanently delete all files and folders \Desktop\Singapore ?	in C:\Users\	TempAcc		
	Vac	No		
	res	INO		

The generated map data consists of different zoom level of the images stored in separate folders, a PNG file of the image and an IDM file of the map data.

(D:) Removable	Disk 🕨	floor-plan-for-house 🕨							
lder	der								
-		Name	Date modified	Туре	Size				
		18	7/21/2016 2:50 PM	File folder					
		49	7/21/2016 2:50 PM	File folder					
		Jan 20	7/21/2016 2:50 PM	File folder					
		Jan 21	7/21/2016 2:50 PM	File folder					
		📄 map.idm	7/21/2016 2:51 PM	IDM File	1 KB				
		📭 map.png	7/21/2016 2:50 PM	PNG image	532 KB				

Context Menu

Move the mouse scroll wheel to zoom in or zoom out on the map.

5.3.12 EMF Editor Tool

The EMF editor tool is used to configure the EMF measurement configuration file (EMCF) and the EMF definition file (EMDF). It consists of the EMF measurement set editor and EMF measurement configuration editor.

5.3.12.1 EMF Measurement Configuration Editor

(0	
٢		
	-	

Live editing

Live editing requires an EMF receiver to be connected to R&S InstrumentView and can be enabled using the "Live Editing" button.

To ensure consistency, settings are communicated with the connected EMF receiver upon change. Any inconsistences are solved by the EMF receiver and the settings are then immediately read back by R&S InstrumentView.

The EMF measurement configuration editor is used to configure the EMF measurement configuration file (*.emcf). The configuration file contains the information on the instrument settings, transducer factor for the equipment (antenna and cable) and also the necessary site-specific correction factor for the equipment and measurement.

Each measurement configuration file is made up of a list of center frequencies for measurement. Each center frequency represents a sub-measurement in the measurement configuration file.

EMF measurement modes

There are six types of "Measurement Mode" supported:

- "Quick Scan": determines the strongest peak field strength values in a defined frequency range. Frequencies that violate a threshold line are noted as result.
- "Spectrum": the field strength of the center frequency is used as EMF result value.
- "Channel Power": the channel power level is used as EMF result value.
- "3GPP WCDMA": the P-CPICH signal power is used as EMF result value.
 Up to 10 strongest scrambling code signal strength results per sub-measurement.
- "LTE-FDD": the power display (displayed cell property) is used as EMF result value. The possible power display modes are PSYNC, SSYNC, RSRP and RSPWR (default).
 - Up to 8 strongest cell ID signal strength results per sub-measurement.
- "TD-LTE": the power display (displayed cell property) is used as EMF result value. The possible power display modes are PSYNC, SSYNC, RSRP and RSPWR (default).

Up to 8 strongest cell ID signal strength results per sub-measurement.

See also Table 5-4.

Working with Instrument Datasets

👷 FSH4 EMF	Config 🗙				5		6	(7)
Measurement	t Configuration	1)			Sub-Measure	ments	Equipment	Con	rections
Measurement M	lode LTE-FDD 👻				Fre	quency		Descript	ion
Measurement N	ame				1	1.71	GHz L	.TE(B 10)	
Measurement 1	Type E-Field v				2	1.72	GHz L	TE(B 10)	
				_	3	1.73	GHz L	TE(B 10)	
Acquisition Co	onfiguration	2			-	1.74	anz i		
Resolution Bandw	idth 100	kHz 🔻 🗹 Auto							
Channel Bandw	idth 10 MHz (50 RB) 🔻								
Trace M	lode Clear / Write 🔻								
Power Dis	play RSPWR •						-		_
RF Attenua	tion 0	dB Auto		-	•	1.75	GHz •	LIE(B 10)	_
RF Preampl	ifier On 👻				_	H	Insert	Ŵ	Remove
Reference L	evel 140			0	Generate Fr Generate Ch	equencie nannel Nu	s umbers		
						🏷 Seler	ct .	LTE (Band	10)_ul
					First Channe	4	Last Channel		Step Size
					22 Band	150	2274	9	1
\odot					LTE(B 10)	•		+	Generate
Import Dat	taset				New (Dpen	Save		
Inport Da	laser in Live Luting			(8 (9	(10)		
	Sub-Measurements Equip	ment Corrections					\cup		
	Antenna 6)		Sub-Measure	ements f	Equipment	Correct	tions	
	Select	No Transducer Selected	E	Equipment			(7)	
	Description	No Description Available		An	tenna Anisotr	ору		0	dB
	Directions (Axis)	x/y/z •		Instru	ment Uncerta	inty		0	dB
	MIMO Configuration	MIMO 2x2 Over The Air 💌							
	Cabla			vieasureme	ent			0	-18
	Constant			Ext	rapolation Fa	ctof	=	U	db
	Attenuation	0 dB						1	Lin
	Transducer								

Figure 5-36: EMF measurement configuration editor

- 1 = "Measurement Configuration" provides general information of the configuration file. See Table 5-3
- 2 = Availability of acquisition settings depends on the selected "Measurement Type" and most settings are not editable. See Table 5-4
- 3 = Only compatible dataset can be imported to the "Acquisition Configuration". See Table 5-4
- 4 = Allows "Live Editing" from InstrumentView to the instrument. The reference level can only be edited live, if an antenna is selected.
- 5 = Sub-measurement contains a list of center frequencies for execution
- 6 = Equipment tab provides control settings such as antenna and cable transducer factors
- 7 = Correction tab provides settings for site-specific correction factor for equipment and measurements
- 8 = New button resets all data and creates a measurement configuration file for entry
- 9 = Open button loads an existing measurement configuration file for entry
- 10 = Save button saves the currently configured measurement configuration file

Parameters	Function
Measurement	Provides settings of the EMF measurement modes.
configurations	Provides a text box to configure "Measurement Name". This name is used as a filename suggestion when saving a new EMF measurement configuration file.
	Selection of the "Measurement Type". Only Electric Field (E-field, field strength expressed in V/m, dBuV/m or W/m ²) is available.
Acquisition	Availability of the acquisition settings depends on the selected EMF measurement modes.
configurations	For details on the acquisition settings, see the respective user manual for information.
	See also information on Table 5-4.
	Note: "RF attenuation" and "Reference level" are editable only in "Live Edit " mode.
Sub-Measure- ments	Contains a list of center frequencies for execution. Each center frequency in the fre- quency list represents a sub-measurement. The amount of sub-measurement that can be added to the frequency list is limited based on the selected measurement mode: Spectrum and channel measurement: Up to 99 sub-measurements WCDMA: Up to 10 sub-measurements LTE-FDD and TD-LTE: Up to 10 sub-measurements
	 Each sub-measurement can be added by the followings: Inserting a single center frequency within the frequency list "Generate Frequencies": Adding a range of center frequencies with a fixed "Step Width" in Hertz
	• "Generate Channel Numbers": Adding a range of center frequencies by specifying a channel table and providing the channel range.
	You can remove a single or multiple center frequencies from the frequency list.
Equipment set- tings	Contains the controls regarding the equipment settings such as antenna and cable trans- ducer factors.
	You can specify an antenna transducer factor such as primary (*.pritrd) or an isotropic transducer file (*.isotrd) at the window browser dialog (e.g. file types). The Y-unit of the transducer file must be compatible with the selected measurement type. If the unit is not compatible, the file is rejected and error message is displayed.
	You can also define the antenna's direction of measurement ("X", "Y", "Z" or "X/Y/Z (All)") and the MIMO configuration for LTE measurement ("SISO Over The Air", "MiMO 2x2 Over The Air", "MiMO 4x4 Over The Air")
	Cable attenuation can be specified by either using a constant value (dB) or using a sec- ondary transducer file (*.sectrd).
	For viewing the response of the transducer file, see Preview transducer table.
Corrections	Defines the site-specific correction factors for equipment and measurements.
	You can set the antenna anisotropy (correction made for any deformities in all orientation of an isotropic antenna for incoming waves) and instrument uncertainty in dB level.
	For measurement type selected for WCDMA, LTE-FDD and TD-LTE, an additional extrapolation factor is available for correction. It can either set as dB or as a dimensionless linear value.
	For measurement type selected for LTE-FDD, you can also make correction factor for "Time Division Duplex" in dB.

Table 5-3: Measurement configuration layout

Working with Instrument Datasets

Mea- sure- ment mode	Resolu- tion band- width	Video band- width	Span	Chan- nel band- width ¹	Trace mode ¹	Power display ¹	Detec- tor	RF Attenu- ation	Refer- ence level
Quick Scan	1	1	1		✓		1	1	1
Spec- trum	1	1	1		✓		1	1	1
Channel Power	1	1	1	1	✓		1	1	1
3GPP WCDMA	1			1	✓			1	1
LTE- FDD	1			1	1	1		1	1
TD-LTE	1			1	1	1		1	1

Table 5-4: Relation between configurable dataset settings and measurement modes

¹Configurable dataset settings

5.3.12.2 EMF Measurement Set Editor

The EMF measurement set editor is used to configure the EMF measurement definition file (*.emdf). The definition file consists the sequence order of one or more EMF measurement configuration files for execution. The following EMF measurement set editor illustrates the different sections to configure the EMF measurement definition file.

Working with Instrument Datasets

Maaguramant Librany		0	\odot	Overview			
C:\Users\Public\Documents\Robde-Schw	varz\InstrumentView\FMI	E Sets		(8) (9)			
Name	Dete		Time	Measurement Definition	on		
iname	Date		Time	Measurement Set Name	EMF Measurement Test Set		
CHP_796_1815.emcf	6/15/2018		2:41 PM	Mooruromont Sot Description	Cample		
LTE_FDD_800_1800_for manual.emcf	6/14/2018		6:43 PM	measurement set bescription	Sample		
UMTS_2100_for_Manual.emcf	6/14/2018		6:44 PM	Measurement Type	E-Field 🔹		
(5) (5)				Automatically Save Results Limits Limit Line 1 Limit Line 2 	Gen. Public Limit Line (Upper) Worker Limit Line (Upper)		
+ Add 🖉 Edit	6 🎗 Up	💥 Down	Remove	UMTS_2100 Setup Start Frequency Stop Frequency RBW Channel Bandwidth	UMTS_2100 WCDMA 2.11568 GHz 2.16912 GHz Auto 3.84 MHz		
iteductionente Sector iteductionente Sector iteductionente Sector iteductionente Sector	e [hh:m Count	Instruction	Next Step	Trace Mode RF Attenuation Reference Level	Clear / Write 0 dB 140 dBμV/m		
1 UMTS_2100 Count 00:06:	:00 2	Yes	Manual	 Equipment 			
2 LTE_FDD_800_ Time 00:06:	00 1	No	Auto	Antenna Factor Axis Cable Factor ▼ Corrections	TSEMF-B1_typical All 0 dB		
Ũ				Extrapolation Factor Antenna Anisotropy Instrument Uncertainty	10 dB 0 dB 0 dB		
				Instruction for Operator Continue to 2nd Measurement LTE mode switch New Open Save 10 12			

Figure 5-37: EMF measurement set editor

- 1 = Displays measurement library directory path
- 2 = "Refresh" button refreshes file content in the selected measurement library directory
- 3 = Homepage
- 4 = Opens the PC window explorer to set measurement library directory path
- 5 = List of EMF measurement configuration files
- 6 = Measurement set navigator
- 7 = List of currently configured measurement set
- 8 = Overview tab
- 9 = Limits tab
- 10 = New button resets all data and creates a measurement definition file for entry
- 11 = Open button loads an existing measurement definition file for entry
- 12 = Save button saves the currently configured measurement definition file

Editor layout	Function
Measurement library table	The measurement library populates the table with EMF measurement configuration files (*.emcf) extracted from the selected "Measurement Library" path.
Measurement set table	 The EMF measurement set table provides a list of currently configured EMF measurement set. It displays the sequence order of individual EMF measurement configuration files. Each measurement configuration contains five inline controls which you can use to define the execution behavior: "Cycle": Provides a dropdown box to select "Time" or "Count". If selected as "Time", sub-measurements are individually executed for the specified minimum duration. If selected as "Count", sub-measurements are individually executed for a specified number of runs. "Time [hh:mm:ss]": Defines the minimum amount of time each sub-measurement is executed for. "Count": Defines the number of times each sub-measurement is executed for. "Instruction": If instruction is set "Yes", an instruction popup box is displayed on the EMF receiver before the starting of this measurement. If "Instruction" is set "No", the EMF receiver starts this measurement without showing an instruction. The instruction description is entered in the "Instruction for Operator" text box. "Next Step": Provides a dropdown box to select "Auto" or "Manual". If selected as "Auto", the EMF receiver automatically proceeds to next step when this measurement is finished. If selected as "Manual", the EMF receiver holds before proceeding to the next step when this measurement result. To navigate the table in the measurement set table, see Measurement set navigator.
Overview setup	Provides an overview of the selected EMF measurement configuration file including the measurement-specific information. See Overview display and limit lines
Limits settings	Provides the limit setup for the selected EMF measurement configuration file in the measurement set table. See Overview display and limit lines.

Table 5-5: Measurement set layout

Measurement set navigator

The measurement set navigator allows you to edit the sequence order in the EMF measurement set table.

Navigator	Function
Add	Adds the selected EMF measurement configuration file from the measurement library table.
Edit	Edits the selected EMF measurement configuration file in the measurement set table. For more information, see Chapter 5.3.12.1, "EMF Measurement Configuration Editor", on page 76.
Up / Down	Moves up / down the selected EMF measurement file in the table.
Remove	Deletes the selected EMF measurement file from the table.

Overview display and limit lines

The "Overview" tab contains information regarding the entire EMF measurement set. It contains the general information and displays measurement-specific details of the measurement setup. The "Limits" tab allows you to define the limit settings used in the measurement set.

Limit Lines

The limit lines are always treated as upper limit settings. This means that values exceeding the specified boundaries may result in an exposure warning or failed measurement result.

					_	
Measurement Definition		Limit Lin	ies			
Measurement Set Name EMF Measurem	nent Set	Limit Lin	ne 1			
Manuscreat Sat Description		2	Select	No Limit Line Selected		Ŵ
measurement set bescription Sample		Limit Lin	ne 2			
Measurement Type E-Field	× .	2	Select	No Limit Line Selected		Ŵ
Automatically Save Results 🖌	1	Quick S	can			
Limits		Limit Li	ine			
- LITING		2	Select	No Limit Line Selected		Ŵ
LTE_FDD_800_1800	3	Evaluatio	on Threshold			
▼ Setup		(belo	ow limit line)		0	dB
Start Frequency 791 MHz Stor Frequency 791 MHz Stor Frequency 791 MHz Channel Bandwidth 10 MHz (5 Charnel Bandwidth 10 MHz (5 Charl Karl Market 10 MHz (5 Reference Level 140 dBµV, ▼ Equipment Antenna Factor TSEMF-81 All MIMO Configuration MIMO 2xi Cable Factor 0 dB < Corrections Extrapolation Factor 0 dB Instrument Uncertainty 0 dB	50 RB) Irite I_typical 2 Over The Air					
Instruction for Operator	4					

Figure 5-38: Overview and Limits Tab

- 1 = "Measurement Definition" provides general information of the EMF measurement definition file. See Table 5-5
- 2 = Limit line displays the upper limits settings. See "Limit Lines" on page 82
- 3 = Measurement-specific setup. See details in Chapter 5.3.12.1, "EMF Measurement Configuration Editor", on page 76
- 4 = Text box to set instructions

Parameters	Function
"Measurement Defi- nitions"	Provides a text box to configure the name of the "Measurement Set Name". This name is used as a filename suggestion when saving a new EMF definition file.
	Provides a text box to configure the optional description of the measurement set. This description is visible on the EMF receiver after loading the measurement set.
	You can also enable "Automatically save reults".
	Selection of the "Measurement Type". Only "Electric Field" (E-field, field strength expressed in V/m, dBuV/m or W/m ²) is available. This setting determines the type of EMF measurement configuration that can be added in the measurement set table
"Limits"	Displays the limit line configured in the "Limits" tab. See Overview display and limit lines.
	For the "Quick Scan" measurement "Evaluation Threshold" is available. This is a configurable margin below the selected Limit Line. It can be seen as virtual line. Measurement peaks greater than this virtual line are displayed during analysis (evaluation). Peaks below the line are not displayed in the graphical representation (neither peak list or bar chart).
Measurement-spe- cific information	Displays measurement-specific information configured in Chapter 5.3.12.1, "EMF Measurement Configuration Editor", on page 76.
"Instruction for Operator"	Text box to set instructions for operator. When "Instruction" is enabled in the "Mea- surement Set" table, a popup box with the instruction is displayed on the EMF receiver before the start of the measurement.

Context menu

Right-click in the measurement library table to access the following menus:

- "Edit" edits the selected measurement configuration file, it opens the measurement configuration editor, see Chapter 5.3.12.1, "EMF Measurement Configuration Editor", on page 76
- "Add": adds the selected measurement configuration file to the measurement set table
- "Delete": deletes the selected measurement configuration file from the measurement library path directory

Right-click in the measurement set table to access the following menus:

- "Up" / "Down": navigates the selected measurement configuration file up/down in the table
- "Remove" : removes the selected measurement configuration file in the table

Vertical / horizontal scrollbar

• For details, see Chapter 3.1, "Context Menu", on page 16.

5.4 Analyze the Instrument Dataset

- 🔍 Analysis

The "Analysis" menu allows you to perform data analysis for instrument data collected from spectrogram, map measurement and EMF measurement results. It also allows you to export GPX file to KMZ and CSV file format.

Analyze the Instrument Dataset

•	Spectrogram	84
•	Map Analysis	88
•	GPX Conversion	. 89
•	Dataset Image	91
•	EMF Measurement Result	. 92

5.4.1 Spectrogram

Spectrogram is only applicable for R&S FPH, R&S FSC, R&S FSH4 and R&S ZVH product series.

The spectrogram provides a workspace to analyze the spectrogram which is also known as long time recording. The workspace is divided into five sections, each providing specific information and or means to analyze the spectrogram data further.



1 = Compression spectrogram

- 2 = Spectrogram section
- 3 = Spectrum section
- 4 = Measurement section
- 5 = Selects "Open" button to load the spectrogram file
- 6 = Setup section

Compression spectrogram

Analyze the Instrument Dataset



The compressed spectrogram displays a compressed overview of the recorded spectrogram data. In the compressed spectrogram view, a selected line is displayed showing the location of the part that is currently displayed in the spectrogram and the spectrum section. You can use the mouse to move the line in the compressed spectrogram to analyze the data in the spectrogram.

You can right-click on the compressed spectrogram to set the current line as reference value. When using the current line as a reference, the reference is subtracted from all the records in the compressed spectrogram and the color spectrum changed accord-ingly. You can also right-click on the scroll bar to display the different scrolling options to navigate the data in the compressed spectrogram view.

Upon loading the next spectrogram, the R&S InstrumentView will prompt you to save the generated compressed spectrogram file.

Spectrogram section

The spectrogram section shows a part of the recorded spectrogram in the highest time resolution, e.g. one line in a spectrogram file represents in one sweep on the spectrum section. You can change the spectrogram frequency resolution by holding the CTRL key and moving the mouse scroller in the spectrum view. For more information on the mouse behavior, see Table 5-6. The amplitude of the signal in the spectrogram view is displayed in color spectrum according to the configuration setup in the "Color Setup" dialog box"Setup section" on page 87.



- 1 = Displays of color table
- 2 = Spectrogram section
- 3 = Displays of marker 1 line
- 4 = Displays of marker 2 line
- 5 = Context menu for spectrogram
- 6 = Scroll bar
- 7 = Displays of T1 time-line
- 8 = Left-click on the mouse to display of current selection line. This line is synchronized to the information displayed in the compressed spectrogram and spectrum section.

- 9 = Context menu for vertical scrollbar
- 10 = Displays of T2 time-line
- 11 = Indication of the spectrogram filename loaded

Spectrum section

The spectrum shows the spectrum at the current selected line in the spectrogram view. The spectrogram shows the amplitude as colors, the spectrum view shows the amplitude as Y deflection in the graph. It is possible to move the markers display, change and move the zoom area of the spectrum display by using the mouse. For more information on the mouse behavior, see Table 5-6



Mouse behavior	Function
.897 1.907 1.	Positions the mouse icon over the marker line until the icon display changed. Hold and left-click on the mouse and drag to move the marker display.
	Positions the mouse icon anywhere on the spectrum view, hold the CTRL key and move the mouse scroller to change the frequency resolution of the spectrum and spectrogram display.
317 1.838 1.8	Positions the mouse icon over the spectrum display until the icon display changed. Left-click and hold on the mouse key to change the spectrum position.

Table 5-6: Mouse behavior in spectrum section

Measurement section

•



The measurement section consists of three subsections:

- Measurement setup The measurement setup contains all the setup properties required for specific measurement. The data displayed in this section is the same as the spectrum section.
- Frequency maker The data displays in the frequency marker corresponds to the settings in the "Marker Setup" configured in the setup section.
- Time marker

The time markers section is used to display the time marker value and results as positioned in the spectrogram section.

Setup section

The setup consists of two sections:

• Viewer setup

The viewer setup allows you to configure the display view ("Time", "Frequency markers" and "Time markers") in the spectrogram section and define the maximum reference level and range different for the color table.

Using the "Auto range" function, you can automatically adjust the maximum reference level and the range different of the color table for optimum display. For more information, see "Working with the Spectrogram Result Display" in the user manual.

 Color Setup 						
Offset	-41					
Range	50					
Auto range	Reset					
Color table	T					
▼ Show						
Time in spectrogram ✔						
Frequency markers 🗹						
	Time markers 🗸					

 Marker setup For more information, see "Marker Setup" on page 36.

Context menu

Right-click on the spectrogram, vertical scrollbar or spectrum to access the following menus:

Spectrogram

• "Set time marker 1/2 here": displays a vertical blue line in the spectrogram.

Vertical scrollbar

For details, see Chapter 3.1, "Context Menu", on page 16.

Spectrum

 "Reset Zoom", "Reset Move": resets the spectrum display to original zoom level or position.

5.4.2 Map Analysis

Map is only applicable for R&S FPH, R&S FSC and R&S FSH4 product series.

The "Map Analysis" menu allows you to view maps and overlay it with the signal strength level from the GPX file. The "Map Analysis" workspace is divided into the map section and the setup section.



- 1 = Map section
- 2 = GPX position ("X (Pixels)", "Y (Pixels)") of the measurement
- 3 = Indices of the measurement
- 4 = Signal strength level of the measurement
- 5 = Selects "Load Map" to open file browser to search for IDM or PRJ map file
- 6 = Selects "Load GPX" to load the GPX file
- 7 = Legend of the color spectrum used for signal strength level
- 8 = Color settings dialog
- 9 = Enables / disables the display of GPX index on the map
- 10 = Enables / disables the display of signal strength level on the map
- 11 = GPX list loaded from the GPX file. The highlighted GPX list is shown blinking on the map.
- 12 = Positions the legend on the exported image
- 13 = Selects "Export Image" to file format (*.png, *.gif, *.bmp, *.jpg, *.tiff, *tif)
- 14 = Exports the "GPX List" to CSV format

Color settings

The color settings dialog allows you to select the color representing the signal strength level to display on the map. After the configuration, the legend of the color spectrum reflects the color changes accordingly.

Bad			Average	Good
-80			-70	-45
▼ Color	Settings			
	Color		Level	
Good:	Green	•	-45	
Average:	Magenta	٠	-70	
Bad:	Red	•	-80	
	Magenta			
	Light Blue			
	Cyan			
	Green			
	Yellow			
	Red			

Figure 5-39: Color settings dialog

5.4.3 GPX Conversion

GPX conversion is only applicable for R&S FPH, R&S FSC and R&S FSH4 product series.

The "GPX Conversion" provides a workspace where you can merge different GPX files into a single collection of measurement list and export the merge GPX data to KMZ or CSV file format. You can then edit the data within this collection by adding "Name" and "Description". Furthermore, you can also modify the colorized representation of the GPS positions for use in Google Maps.

The tool is divided into the grid section and setup section.

Analyze the Instrument Dataset

Inc	lude Latitude	2 Longitude	Level 3	Name (4)	Description	Load	d GPX	5			
(1)	1° 19.4395'	N 103° 56.1076' E	-53.4 dBm			Bad		Average			Goo
	1° 20.6597'	N 103° 56.2003' E	-57.4 dBm					70			
	1° 19.9853'	N 103° 54.8356' E	-76.5 dBm			-₀u ▼ Color S	Settings	-/0	6)		-3
	1° 19.2593'	N 103° 55.4794' E	-49 dBm			_	Colo	or		Level	
	1° 20.5104'	N 103° 55.5309' E	-51.9 dBm			Good:	Green	•	-50		
	1° 20.0625'	N 103° 56.6947' E	-76.6 dBm			Average:	Magenta	•	-70		
	1° 19.1049'	N 103° 56.7565' E	-76.6 dBm			Bad	Red		-80		
	1° 19.6146'	N 103° 57.1891' E	-58.1 dBm			bau.	Reu		-00		
	1° 24.0267'	N 103° 53.7078' E	-76.5 dBm			Default Indi	cator	(7) B	est		•
	1° 20.3283'	N 103° 57.8650' E	-76.2 dBm	rs	ref	Maximum Z	oom Distance	8 20)		
	1° 20.0033'	N 103° 57.7517' E	-76.5 dBm	cbp		Show Ir	ndices on Maj	9 (9)			
	1° 19.9950'	N 103° 58.2133' E	-76.4 dBm	goodyear-co		GPX Files	(10)	U			
	1° 20.3283'	N 103° 57.8650' E	-54.2 dBm	rs		D:\Indoor	Mapping\Ind	oorMappin	g003.gpx	7	Ŵ
	1° 20.2911'	N 103° 57.8805' E	-62.1 dBm			D:\Indoor	Mapping\Ind	oorMappin	g002.gpx	Ī	Ŵ
	1° 19.9950'	N 103° 58.2133' E	-75.4 dBm	Goodyear		D:\Indoor	Mapping\Ind	oorMappin	g001.gpx	ī	Ŵ
						D:\Outdoo	or Mapping\C	utdoorMap	ping.gpx	Ī	Ŵ
				In	lude All						
				Ex	clude All 14	Auto op Conve	oen KMZ file (rt to KMZ	1) E	xport C	sv 🕄	

Figure 5-40: GPX conversion dialog box

- 1 = Checkbox to include or exclude the measurement indices in the CSV or KMZ file
- 2 = GPS position of the measurement ("Latitude" and "Longitude")
- 3 = Measured result of the measurement
- 4 = Editable field ("Name" and "Description")
- 5 = Load GPX file with valid GPS coordinates
- 6 = Color setting dialog
- 7 = Default indicator determines the preferred visible measurement when multiple measurements are grouped at a certain zoom level ("Best", "Average", "Worst")
- 8 = "Maximum Zoom Distance" determines the number of zoom layers stored in KMZ file. A higher zoom distance means fewer zoom layers and vice versa
- 9 = Checkbox to enable or disable the display of measurement indices on the map
- 10 = GPX files list table
- 11 = Checkbox to auto-open the KMZ file in Google Earth after creation
- 12 = Converts the GPX file list to KMZ file format
- 13 = Exports the GPX file list to CSV file format
- 14 = Context menu in GPX list

Color setting dialog

You can define the different color used to represent the level measured at the GPS position. Available colors for selection:

- "Magenta"
- "Light Blue"
- "Cyan"
- "Green"
- "Yellow"
- "Red"

Context menu

Right-click on the GPX list to access the following menus:

- "Include All": includes all the GPS coordinates in the GPX list.
- "Exclude All": excludes all the GPS coordinates in the GPX list.

5.4.4 Dataset Image

The "Dataset Image" menu is used to view screenshot embedded in the saved dataset with the optional display of measurement settings (if enabled).

This is a useful feature which allows the viewing of dataset image before activating dataset file from PC to the instrument. See Chapter 5.2.9, "Activate Dataset to Instrument", on page 53



Figure 5-41: Dataset image with measurement settings

- 1 = Dataset image
- 2 = Measurement settings

Context menu

Right-click on the trace window to access the following menus:

- "Show measurement setup": if enabled, the instrument settings and trace data are displayed below the screenshot. See Figure 5-14.
- "Copy to clipboard": if enabled, the dataset image with instrument settings and trace data is copied to the clipboard.

5.4.5 EMF Measurement Result

The EMF analysis workspace allows you to analyze and export EMF measurement results stored in the EMF result files (EMRF). You can analyze the measurement set and the sub-measurements results. The result values in the measurement set are presented in the following:

- Result: result value per center frequency, cell ID or scrambling code presented in "Sub-Measurement" tab
- Subtotal: sum of all sub-measurement results presented in "Measurement" and "Sub-Measurement" tab
- Total: sum of all totals of all measurements presented in "Measurement" tab



Figure 5-42: EMF Analysis measurement overview

- 1 = Measurement results including measurement totals. Results are presented in data grid and are visualized using a bar chart
- 2 = Sub-measurement results per center frequency and scrambling code or cell ID, including measurement subtotals. Results are presented in a data grid and are visualized using a bar chart.
- 3 = Measurement header
- 4 = Measurement result table
- 5 = Measurement result bar chart
- 6 = Overview tab containing global measurement set information and measurement-specific data
- 7 = Setup tab contains controls which affect all measurements in the measurement set
- 8 = Export tab containing result export options

- 9 = Sub-measurement header
- 10 = Sub-measurement result table
- 11 = Sub-measurement result bar chart
- 12 = Open button loads an existing EMRF file
- 13 = Save button saves post measurements corrections and limits in the EMRF file (*.emrf)
- 14 = Reset button reverts corrections and limits to how they were originally specified
- 15 = Copy button copies CSV data of the measurement to the operating system clipboard
- 16 = Export button exports the available data into a report

Quick Scans	Measurements	Sub-Measurements					Overview	Setup	Export		
SimpleQS2 RMS Start Time 13:31 Duration 00.00.00:18 Stop Time 13:32 Measurement Completed						Simple Meas Set Start Date 1/14/2019 Start Time 13:31 Stop Date 1/14/2019					
Measurement	t		Peak Value 404.86 μV/m		Number of Peaks 97		GF GPS	Stop Date Stop Time Duration PS Latitude Longitude	1/14/2019 13:32 00.00:00:56		
3 SimpleQS2			333.19 µV/m		95		 Limit Line Quick Scan SimpleQS2 Setup 	es Limit Line	50dBuV_m L	imitline_curve (i	(Upper)
 Frequency 801.8413 MHz 802.2857 MHz 811.5873 MHz 811.6508 MHz 811.6825 MHz 811.7143 MHz 		Field Stren 106.07 µV/n 117.79 µV/n 133.51 µV/n 133.71 µV/n 172.83 µV/n 183.69 µV/n	gth	Limit (V/m) 50.00 51.41 51.35 51.32 51.29	Δ to Limit (V/ 9.49 8.58 8.90 8.83 6.57 6.00	m) I	Start Stop I Tr RF At Refer ▼ Equipme Anter Ca	Name Mode Frequency RBW XBW Span ace Mode Detector tenuation ence Level mt ma Factor Axis ble Factor	SimpleQS2 Quick Scan 8.08 MHz 811.92 MHz Auto 200 MHz Clear / Write Max Peak Auto 100 dBµV/m HA-Z901 X 0 dB		
ф 100 mV/m 798.22 10 mV/m - 1 mV/m - 100 μV/m - 10 μV/m -	2	803.29	808.37	813.44	818.52	82359 MHz	Correctic Ant Instrur Open Export	ons enna Anisotr nent Uncerta Save	opy inty Reset	c Copy	0 dB 0 dB

Figure 5-43: EMFQuick Scan analysis measurement overview

Parameters	Function
Measurement header	Displays the name of the selected measurement following by the result mode (Avg, Max, Min, RMS) in which the results are presented.
	Displays the measurement start time, stop time and measurement duration (stop time - start time).
Measurement result table	Overview of the available results of all measurements in the EMF measurement set. It displays the subtotal results of the sub-measurements ("Field Strength", "Exposure 1 (%)", "Exposure 2 (%)") and the total sum results of these subtotal values for all measurements.
	The "Peak Value" displays the maximum single value of the field strength mea- surement.
Measurement result bar chart	Visual display of the measurement result (field strength) of all the measurement set.
	A marker line is placed on the selected measurement identify the exact field strength on th bar chart.
Sub-measurement header	Displays the selected sub-measurement result mode (Avg, Max, Min, RMS) in which the results are presented.
	Displays the measurement start time, stop time and measurement duration (stop time - start time).

Parameters	Function
Sub-measurement result table	Detailed displays of the selected measurement. The sub-measurement contains a list of measurements (Field Strength, Limit 1 (V/m), Limit 2 (V/m), Exposure 1 (%), Exposure 2 (%)) on frequencies configured in the selected measurement including a subtotal sum of "Field Strength", "Exposure 1 (%)" and "Exposure 2 (%)").
	Note: Limit 1 (V/m), Limit 2 (V/m) can be configured in the "Setup" tab.
	Depending on the selected meaurement mode, additional parameters of "Scram- bling Code" or "Cell ID" is displayed.
	The "Cyces" shows the number of runs the sub-measurement was executed.
Sub measurement result bar chart	Visual display of the sub-measurement result (field strength). A marker line is placed on the selected measurement identify the exact field strength on th bar chart.
Quick Scan	Quick Scan measurement results. The Quick Scan tab is only available if a Quick Scan measurement is part of the EMRF.

Overview

The "Overview" tab contains information regarding the entire measurement, it includes the general information, limit lines results and measurement-specific details of the selected measurement.

For more information on the measurement-specific details, see Chapter 5.3.12.2, "EMF Measurement Set Editor", on page 79 and Chapter 5.3.12.1, "EMF Measurement Configuration Editor", on page 76.

Analyze the Instrument Dataset

EMF			
1	Start Date Stop Date Start Time Stop Time GPS Latitude GPS Longitude Duration	5/11/2018 5/14/2018 01:24 PM 08:58 AM 02.19:34:15	
 Limit Lines 2 Res 	Limit Line 1 ult Limit Line 1	ICNIRP_GP (U PASS	pper)
WC meting			
 Setun 			
· Setup	Name	WC meting	
3 S Chan R	Mode tart Frequency top Frequency RBW nel Bandwidth Trace Mode RF Attenuation deference Level	WCDMA 2.11568 GHz 3.10192 GHz Auto 3.84 MHz Clear / Write 0 dB 140 dBμV/m	
▼ Equipment			
4	Antenna Factor Axis Cable Factor	TS-EMF_Exam All TSEMFZ2 exar	iple mple
 Corrections 			
Antenna Aniso	tropy	þ	dB
Instrument Uncert	ainty	2	dB
Extrapolation Fa	ector	3	dB
	_	-	
		2	Lin

Figure 5-44: Overview tab dialog

- 1 = General information for the measurement set
- 2 = Displays limit line details and limit test result
- 3 = Displays of measurement-specific details reflected from settings in Chapter 5.3.12.2, "EMF Measurement Set Editor", on page 79 and Chapter 5.3.12.1, "EMF Measurement Configuration Editor", on page 76

Parameters	Function
General information	Displays start date, start time, stop date, stop time and measurement duration of the selected measure- ment.
	Displays the GPS latitude and longitude reading.
Limit Lines	Displays the selected limit lines from the setup tab.
	It also displays the global pass / fail limit lines test result. If a single sub-measurement's field strength result exceeds the interpolated limit at that specific frequency, the limit result is considered failed. "Exposure Ratios" below 100%, indicates a passed limit result
Measurement-specific details	The measurement-specific details reflect the set- tings from Chapter 5.3.12.2, "EMF Measurement Set Editor", on page 79 and Chapter 5.3.12.1, "EMF Measurement Configuration Editor", on page 76.
	The parameters in "Setup" and "Equipment" sec- tions are read-only parameters.
	The parameters in "Corrections" section can be overwritten and the settings affect the results in both "Measurements" and "Sub-Measurements" tab.
	Note: "Extrapolation Factor" - Only applicable for "3GPP WCDMA", "LTE-FDD" and "TD-LTE" mea- surement mode.
	Note: "Time Division Duplex" - Only applicable for "TD-LTE" measurement modes.

Table 5-8: Details of overview tab

Setup tab

The "Setup" tab contains controls affect all measurements in the measurement set.

For details on the affected parameters, see Chapter 5.3.12.2, "EMF Measurement Set Editor", on page 79, Chapter 5.3.12.1, "EMF Measurement Configuration Editor", on page 76 and Overview.

Analyze the Instrument Dataset

Presentation						
	Result	t Mode	RMS		•	
Units						
	Field St	rength	V/m		•	
	Exposure Rat	tio (ER)	Percent (%)		•	
Limit L	ines					
Limit	Line 1					
	Select		ICNIRP_GP		Ŵ	
Limit	Line 2					
	Select	No	Limit Line Selected		Ŵ	
Quick Scan						
Lim	it Line					
	Select	No	Limit Line Selected		Ŵ	
Evalu (uation Threshold below limit line)	-		0	dB	

Figure 5-45: Setup tab dialog

Parameters	Function
Presentation	Sets the result mode in the measurement set. Avail- able result modes are: "Average", "RMS", "Maxi- mum" and "Minimum".
	By default, result mode is set to "RMS".
Units	Sets the field strength unit in the measurement set: • E-Field measurement sets - dBuV/m, V/m and W/m ² .
	Sets the "Exposure Ratio (ER)" unit: Available units are E ² / L ² , %, % _o and PPM (parts per million).

Parameters	Function
Limit Lines	Defines the limit lines using limit line files. The Y- Unit of the limit line file must be compatible with the selected field strength unit. If unit is not compatible, the file is rejected and an error message is dis- played.
	Selects the 🔳 to discard limit line selection.
Quick Scan	Defines the limit lines for the quick scan using limit line files.
	Also the "Evaluation Threshold" is available. This is a configurable margin below the selected Limit Line. It can be seen as virtual line. Measurement peaks greater than this virtual line are displayed during analysis (evaluation). Peaks below the line are not displayed in the graphical representation (neither peak list or bar chart).

Export tab

The "Export" tab contains controls which determine the content and format of reports for exporting. Selects the checkbox "Open after Generation" to open report file after exporting the report.

Analyze the Instrument Dataset

ent			
verage Results	Max Results		
MS Results	Min Results		
General Informati	on 🗹 Mea	asurement Settings	
Data Tables	🗹 Graj	phics	
Frontpage Logo	User Logo	•	
🖆 Select	No Lo	ogo Selected	
Footer Logo	R&S Logo	•	
	ROHDE	&SCHWARZ	
ons			
English	Format	PDF 🔻	
Generation			
	ent verage Results MS Results General Informati Data Tables Frontpage Logo Cons Footer Logo Ons English	ent verage Results Max MS Results Min General Information Mea Data Tables I Gra Data Tables I Gra Frontpage Logo User Logo I Select No Logo Footer Logo R&S Logo Footer Logo R&S Logo CONS English Format Generation	

Figure 5-46: Export tab dialog

Table 5-9: Details of export tab

Parameters	Function
Report content	Selection of result mode to be presented in the report. Available selections are Average, RMS, Max and Mini results.
	Selection of the details to be presented in the report. Available selections are "General Information", "Data Tables" for sub-measurement results, "Mea- surement Settings " for measurement-specific details and "Graphics" presentation.
Logo	Selection of logo file used in the front page and footer of the report.

Context menu

Right-click in the measurement table to access the following items:

- "Copy Data": copies all data in the measurement list to the clipboard as commaseparated values (e.g. Excel).
- "Copy Graphics": copies the bar chart graph to the clipboard.

Vertical/horizontal scrollbar

• For details, see Chapter 3.1, "Context Menu", on page 16.

6 Using R&S InstrumentView with an Oscilloscope

The oscilloscope settings are only applicable for the following R&S oscilloscopes:

- R&S RTA4000
- R&S RTB2000
- R&S RTC1000
- R&S RTH1000
- R&S RTM3000

In the scope workspace, you can analyze imported oscilloscopes waveforms (working in offline mode) or analyze waveforms on a connected oscilloscope (working in online mode).

Menu visibility

To show only the oscilloscope functionalities for the R&S InstrumentView, enable "Show Oscilloscope menu entries only" in the "Option > Settings " dialog. See also Chapter 4.5.3, "Application Settings", on page 30.

Application	Settings
 ✓ 	Retrieve the full dataset. This includes calibration data when applicable.
✓	Network disconnect detection.
Meter 🔻	Length unit to display.
Visual Settin	gs
Home Screen Log	RS Logo Light 🔻
Menu Visibility	
	Show Oscilloscope menu entries only.
ОК	Cancel

6.1 Working in Offline Mode

When working in an offline mode, you do not need a connection to the oscilloscope. You can import the following waveforms:

- Files in *csv format with waveform details from your oscilloscope.
- Files in *scset format, which is a custom combined setting file generated from R&S InstrumentView when saved from the scope workspace.

To open a saved waveform:

- 1. Select "Open".
- 2. In the dialog, select the waveform file you want to analyze.

The scope workspace dialog opens. You can now view the waveform information and display measurement results on the active waveform.

- In the "Setup" tab, enable the measurements you want to perform. See "Measurement functions setup" on page 110.
- 4. If necessary, enable a cursor.
- 5. View the results of the measurements and information about the waveform in the "Measurement" tab.

6.2 Working in Online Mode

When working in online mode, you can connect to an oscilloscope and get its trace, show measurement results or make a screenshot.

To work in online mode:

- Connect to an oscilloscope. See Chapter 2, "Connecting the Instrument", on page 9.
- 2. Select "Get Trace".

The scope workspace dialog opens. You can now view the waveform information and display measurement results on the active waveform.

- In the "Setup" tab, enable the measurements you want to perform. See "Measurement functions setup" on page 110.
- 4. If necessary, enable a cursor.
- 5. View the results of the measurements and information about the waveform in the "Measurement" tab.
- 6. Optionally, press "Add Trace" to add a new trace.

 Optionally, you can make a screenshot of your measurement and the current settings of your connected oscilloscope. See Chapter 6.6, "Screenshot", on page 111

6.3 Scope Workspace Settings

The scope workspace allows you to analyze your oscilloscope waveforms. It looks the same for the offline and online mode.



Figure 6-1: Scope workspace dialog

- 1 = Header for measurement selection
- 2 = Diagram settings
- 3 = Enabled cursor
- 4 = Annotation
- 5 = Measurement tab
- 6 = Setup tab
- 7 = Waveform data
- 8 = Measurement results data
- 9 = Cursor data

In the diagram, the waveform of each channel is displayed in a different color. You can change this color in the "Options > Color Settings" menu, see Chapter 4.5.1, "Color Settings", on page 26.

You can click a waveform to select it and movie it up and down on the diagram. You can also change the vertical scale by moving the mouse scroll wheel or by using the header bar buttons (see Diagram settings).

Each scope workspace measurement result consists of two tabs:

• "Measurement ":

- "Waveform data": waveform measurement settings. See the user manual of the respective instrument for details of measurement settings.
- "Measurement results data": displays the result for all enabled measurements.
- "Cursor data": displays the trace of the enabled cursors.
- "Setup"
 - "Cursor settings": see "Cursor settings" on page 109.
 - "Graph settings": see "Graph settings" on page 110.
 - "Measurement Functions Setup": see "Measurement functions setup" on page 110.

In the tab you can define the cursors, the graph settings and select the measurement functions.

6.3.1 Scope Workspace Header Settings

In the following sections, the different settings that you can access through the scope workspace header bar are described.

	₩ Curso	r≯	Q	Zoom	×	Т	Annotation	Reset/Scale	۲	Measurement	×
(Cursor										
	₩ Curso	r ⊧	٩	Zo							
	Verti	al C	ursor								
	Horiz	onta	al Curso	r							

You can add up to two horizontal, vertical or cross-hair cursors. For further available cursor settings, see "Cursor settings" on page 109.

Zoom

-::::::

Zoom In	
Zoom Reset	

You can zoom in on your measurement or reset the settings.

To zoom in on the diagram

Cross Hair Cursor

1. In the header bar, select "Zoom > Zoom In".

2. In the scope workspace, click and hold. A rectangular appears with which you can select the zoom area.



You can further move the rectangle shown in the zoom area to change the displayed area.

Annotation editor

🖶 Annotation Editor			×
Text			
Font	12	Co	lor
Show Symbol			
Link To Channel	None	•	
		OK	Cancel

In the annotation editor dialog, you can create annotations and display them on the screen.

The following settings are available:

Settings	Description
Text	Sets the text for the annotation that is displayed
Font	Sets the font size
Color	Sets the color of the annotation text.
Show symbol	Shows a small triangle marker symbol below the text.
Link to channel	Links the annotations to a selected channel. If no channel is selected, you can move the mark free on the screen.

Reset /Scale

Reset/Scale	ŀ
To Default	
Single Scale	
Auto Scale	

In the "Reset" menu, you can select a scale for the display. The following settings are available:

Settings	Description
"To Default"	Selects a default measurement scale. The wave- forms of the different channels are shown on the screen with an offset.
"Single Scale"	Overlaps the waveforms of all channels on a single scale, without an offset.
"Auto Scale"	Zooms out on the measurements to display the most of the waveform.

Measurements



You can perform one of the following measurements on your waveform:

Measurement	Description
"Max"	Maximum value within the displayed waveform.
"High"	High level of the displayed waveform - the upper maximum of the sample distribution, or the mean value of the high level of a square wave without overshoot. The measurement requires at least one complete period of the signal.
"Low"	Low level of the displayed waveform - the lower maximum of the sample distribution, or the mean value of the low level of a square wave without over- shoot. The measurement requires at least one com- plete period of the signal.
"Min"	Minimum value within the displayed waveform.
"Peak to Peak"	Difference of maximum and minimum values.
"Period"	Time of the first period, measured on the 50% level. The measurement requires at least one complete period of the signal.
"Frequency"	Frequency of the signal, reciprocal value of the measured first period.
"Rising Slew Rate"	Steepness of the first rising edge, measured between the signal reference levels set in the "Setup" tab.
"Falling Slew Rate"	Steepness of the first falling edge, measured between the signal reference levels set in the "Setup" tab.

The results of the measurements are displayed in the "Measurement" tab.

Diagram settings

You can change the scale and position of your diagram using the buttons in the header bar.

	Description
★ X	Moves the vertical scale up/down
	Moves the vertical position up/down
	Moves the horizontal position to the left/right

6.3.2 Setup Dialog

In the "Setup" dialog you can define the cursors, the graph settings and select the measurement functions.
Scope Workspace Settings

Measurement Setup		
✓ Cursor Settings		
Cursor1 🗸 Vertical 🔹	Track Channel	None 🔻
Cursor2 Vertical •	Track Channel	None 🔻
▼ Graph Settings		
Hide Axis		
Hide Annotations		
 Measurement Functions Setup 		
Signal Reference Levels(%)		
20/80 10/90		
Gated By Cursor None 🔻		
Measurements		
Max		
High		
Low		
Min		
PeakPeak		
Period		
Frequency		
RisingSlewRate		
FallingSlewRate		

Cursor settings

Access: "Setup" tab.

• (Cursor Setti	ngs				
	Cursor1 🗹	Vertical	•	Track Channel	CH1	•
	Cursor2 🗹	Vertical	•	Track Channel	None	•

You can enable and define two separate cursors to analyze your data. Available are "Horizontal", "Vertical" and "CrossHair"(horizontal and vertical) settings. With "Track Channel", you can attach the cursor to a specific channel.

Graph settings

Access: "Setup" tab.

•	Graph Settings
	Hide Axis
	Hide Annotations

In the graph settings menu you can select, if the axis and the annotations are displayed in the scope workspace or not.

Measurement functions setup

In the measurement function setup menu, you can select which measurements are enabled. For a list of the available measurements, see "Measurements" on page 107.

You can also select the "Signal Reference Levels (%)" and gate them to a cursor.

• 1	Measurement Functions Setup
	Signal Reference Levels(%)
	20/80
	Gated By Cursor Cursor1 ▼
	Measurements
	Max Max
	IIIgh
	✓ Low
	Min
	PeakPeak
	Period
	Frequency
	RisingSlewRate
	FallingSlewRate

6.3.3 Context Menu

Right-click on the measurement diagram to access the context menu with the following settings:

Screenshot

	Add Annotation
	Copy Graphics
A	Zoom
\times	AutoScale Current Channel

- "Add Annotation": opens a dialog to add an annotation, see "Annotation editor" on page 105.
- "Edit Annotation": opens a dialog to edit the annotation.
- "Delete Annotation": deletes the selected annotation. Only available, if you rightclick on an existing annotation.
- "Copy Graphics": copies the current graphic window into your clipboard.
- "Zoom": zooms in on the measurement window.
- "Autoscale Current Channel": changes the scale of the selected channel to the autoset settings.
- "Remove Cursor": removes an enabled cursor. Only available, if you right-click on the displayed cursor.

6.4 Get Trace

The get trace functionalities are available only when there is a connection to an oscilloscope.

The "Get Trace" menu allows you to capture the current trace measurement from the instrument and display it in the scope workspace. A new tab is formed in the "Tab header bar" for every new trace captured from the instrument.

For information about the available settings, see Chapter 6.3, "Scope Workspace Settings ", on page 103.

6.5 Add Trace

The add trace functionalities are available only when there is a connection to an oscilloscope.

The "Add Trace" menu allows you to add additional trace measurement captured from the instrument to an existing trace measurement displayed in the trace window. Each trace is represented with a different trace color.

6.6 Screenshot

The screenshot functionalities are available only when there is a connection to an oscilloscope.

The "Screenshot" is used to capture the active instrument screen and display it in the trace window. This trace window is printed or saved for further editing in the application.



Context menu

Right-click on the instrument snapshot for the following menus:

Copy to clipboard

 "Copy to clipboard": copies the screenshot to the clipboard.

Index

Α

AMA AM limits	67
Analysis	
Dataset image	83
EMF measurement result	83
GPX conversion	
Map analysis	83
Spectrogram	83

С

Cable models	57 58
Channel table	61
Connecting the instrument	
LAN	9
USB	9
Customizing test report	20

Ε

Editor	55
Instrument datasets	55
EMF measurement configuration editor	75
EMF measurement modes	76
Relation between configurable dataset setting	s and
measurement modes	76
EMF measurement result	92
EMF measurement set editor	75

F

FM limits table	3
-----------------	---

I

Installing R&S InstrumentView	
Installing the R&S InstrumentView software	7
R&S InstrumentView software information	7
Running the R&S InstrumentView software	7
Instrument	. 39
Active dataset to instrument	. 39
Date time synchronization	. 39
File transfer	39
Lab display	39
Multi-transfer	39
Remote display	39
Save dataset from instrument	39
Screenshot	39
Synchronization	. 39
Instrument datasets	
AM limits	. 55
Cable models	55
Calibrations kits	. 55
Channel table	55
EMF editor	. 55
FM limits	. 55
Limit line	55
Map creator	55
Quick name table	55
Standards	. 55
Transducers	55
Wizard sets	55

Μ

Map creator	73
Measurement type	
Channel power	63
Occupied bandwidth	63
Spectrum emission mask	63
TDMA power	63

0

Open dataset	25
Options	
Color settings	
Command-line tool	25
Directory settings	
Instrument type selection	25
Keyboard shortcuts	
Oscilloscope	101

Ρ

Preview .	 18
Printing .	 18

Q

R

R&S InstrumentView screen layout	14
----------------------------------	----

S

Save dataset	23
Scope workspace	101

Т

Trace window	
Add trace	 32
Get trace	 32

U

Using limit lines Limit lines table	59 59
FIEVIEW	29
	. 32
Using standards	62
Measurement type	62
Standards table	.62
Using transducers	55
Preview	55
Transducers table	55
w	

Wizard set editor		69
-------------------	--	----