

## RJ45 connector - CUC-V14-C1ZNI-S/R4IP10G8 - 1149843

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Push-pull ADVANCE connector (version 14), die-cast zinc, with RJ45 connector insert, 8-pos., 10 Gbps, CAT6<sub>A</sub> (IEC 11801:2017), with IDC fast connection technology, for AWG 23 - 22 1-wire, 7-wire, and 19-wire conductors, for cable diameter of 5.5 mm ... 10 mm

### Your advantages

- ✓ Easy and time-saving assembly with IDC fast connection technology
- ✓ Future-proof due to CAT6<sub>A</sub> with 10 Gbps
- ✓ 360° shielding ensures reliable transmission, even in industrial applications
- ✓ Ideal companion for servicing or repairs in the field: no special tools required for mounting
- ✓ Locking system to prevent inadvertent release



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 063151 145538
GTIN	4063151145538
Weight per Piece (excluding packing)	89.050 g
Custom tariff number	85366990

### Technical data

#### Mechanical characteristics

Connection method	IDC fast connection
Minimum external conductor diameter	5.5 mm
Maximum external conductor diameter	10 mm
Overvoltage category	I
AWG solid min.	23
AWG solid max.	22
AWG multi-stranded min.	23
AWG multi-stranded max.	22
Tightening torque max	2.5 Nm

# RJ45 connector - CUC-V14-C1ZNI-S/R4IP10G8 - 1149843

## Technical data

### Mechanical characteristics

Number of positions	8
Degree of protection	IP20
Degree of pollution	2
Cable outlet	straight
No. of cable outlets	1
Locking type	Push Pull
Weight	89.05 g

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (assembly)	-10 °C ... 40 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

### Material data

Contact surface material	Au/Ni
Contact material	Cu/Sn
Contact carrier material	PC
Cable gland material	CuZn
Seal material	CR
	NBR
	NBR
Seal material, O-ring	NBR
Seal material cable seal	CR
Seal material	NBR
Width	22.4 mm
Height	34 mm
Length	95 mm
Wrench size	20.00 mm

### Electrical characteristics

Transmission speed	10 Gbps
Resistance	500 MΩ
Connection cross section AWG	23 ... 22 (solid)
	23 ... 22 (flexible)
Rated current	1.75 A
Test voltage Core/Core	1000 V
Test voltage Core/Shield	1500 V
Degree of protection when not plugged in	IP20

### Standards and Regulations

Standards/specifications	IEC 61076-3-117
Flammability rating according to UL 94	V0

# RJ45 connector - CUC-V14-C1ZNI-S/R4IP10G8 - 1149843

## Classifications

eCl@ss

eCl@ss 9.0	27440101
------------	----------

ETIM

ETIM 5.0	EC002636
----------	----------

## Approvals

Approvals

---

Approvals

EAC

---

Ex Approvals

---

## Approval details

EAC		B.01687
-----	--	---------

## Accessories

Accessories

Electronics pliers

Diagonal cutter - MICROFOX-SP-1 - 1212487



Electronic diagonal cutter, tapered head, without chamfer, with opening spring, non-reflective phosphate-treated surface, punched version

---

Stripping tool - VS-CABLE-STRIP-VARIO - 1657407



Stripping tool, for the multi-level stripping of shielded cables

---

