

Applications

- Zener diode
- Ultra-small surface mount package

**RoHS
Compliant**

Features

- Ideally suited for automated assembly processes
- Total power dissipation: max. 500mW
- General purpose, medium current
- Ideally suited for automated assembly processes
- The Plastic material carries

Maximum Ratings @ TA = 25°C unless otherwise specified


Characteristics	Symbol	Value	Unit
Maximum Forward Voltage @ IF = 10mA	V _F	0.9	V
Power Dissipation (Note 1)	P _{tot}	500	mW
Thermal resistance, Junction to ambient air	R _{θJA}	340	°C/W
Junction temperature	T _J	-55 to +150	°C
Storage Temperature Range	T _{STG}		

Note: 1. V_{ZT} is tested with pulses (20ms)

Electrical Characteristics (TA = 25°C unless otherwise noted)

Part Number	Zener Voltage Range				Dynamic Impedance				Max. Reverse Leakage Current		Marking
	V _{ZNOM}	V _{ZT}	V _{ZT}	AT I _{ZT}	ZZT	at I _{ZT}	ZZK	AT I _{ZK}	I _R	AT V _R	
	V	V (Min)	V (Max)	mA	Ω (Max.)	mA	Ω (Max.)	mA	μA	V	
BZT52C20	20	18.8	21.2	5	55	5	225	1	0.1	14	NR
BZT52C30	30	28	32	2	80	2	300	0.5		21	PA

Package SOD - 123



Dimensions : Inches (Millimetres)

Part Number Table

Description	Part Number
Zener Single Diode, 20V, 200mW	BZT52C20
Zener Single Diode, 30V, 200mW	BZT52C30

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro